

(12) **United States Patent**  
**Schechter et al.**

(10) **Patent No.:** **US 11,643,769 B2**  
(45) **Date of Patent:** **May 9, 2023**

(54) **ROBOTIC LAUNDRY SORTING DEVICES, SYSTEMS, AND METHODS OF USE**

(71) Applicant: **Monotony.ai, Inc.**, Newton, MA (US)

(72) Inventors: **Stuart E. Schechter**, Newton, MA (US); **Benjamin D. Bixby**, Newton Highlands, MA (US); **Samuel Duffley**, Cambridge, MA (US); **Samuel M. Felton**, Belmont, MA (US); **Wilson J. Mefford**, Somerville, MA (US); **Elliot Sinclair Pennington**, Lexington, MA (US); **Ross O. Schlaikjer**, Somerville, MA (US); **Jesse Sielaff**, Norfolk, MA (US); **Marissa A. Bennett**, Waltham, MA (US); **Gabriella McLellan**, Brighton, MA (US)

(73) Assignee: **MONOTONY.AI, INC.**, Allston, MA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 40 days.

(21) Appl. No.: **17/503,902**

(22) Filed: **Oct. 18, 2021**

(65) **Prior Publication Data**

US 2022/0120030 A1 Apr. 21, 2022

**Related U.S. Application Data**

(60) Provisional application No. 63/093,236, filed on Oct. 18, 2020.

(51) **Int. Cl.**  
**G06F 17/00** (2019.01)  
**D06F 93/00** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **D06F 93/00** (2013.01); **B07C 5/36** (2013.01); **B25J 9/0084** (2013.01); **B25J 9/045** (2013.01);  
(Continued)

(58) **Field of Classification Search**

USPC ..... 700/248  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,036,365 A \* 7/1977 Rosenfeld ..... B07C 5/3412  
209/3.3

4,885,853 A 12/1989 McCabe  
(Continued)

FOREIGN PATENT DOCUMENTS

CN 103582728 A 2/2014  
EP 0679755 A1 11/1995  
(Continued)

OTHER PUBLICATIONS

The \$1,000 laundry-folding robot is back and it's fine, I guess.  
(Year: 2019).\*

(Continued)


*Primary Examiner* — Ronnie M Mancho

(74) *Attorney, Agent, or Firm* — Myers Bigel, P.A.

(57) **ABSTRACT**

Devices, systems, and methods for autonomously sorting dirty laundry articles into batched loads for washing are described. For example, an autonomous sorting device includes an enclosed channel including a plurality of sequential work volumes and a stationary floor extending between an inlet end and an outlet end of the channel, a plurality of arms disposed in series along the enclosed channel for rotating, tilting, extending, and retracting a terminal gripper of each arm into an associated work volume for grabbing at least one of a plurality of deformable dirty laundry articles and passing the at least one deformable laundry article to an adjacent work volume for grasping and hoisting by an adjacent arm. The device includes an inlet orifice for receiving the dirty laundry articles into the enclosed channel and an outlet orifice adjacent the outlet end

(Continued)



through which each separated deformable article exits the enclosed channel into sorting bins.

### 32 Claims, 57 Drawing Sheets

#### (51) Int. Cl.

**D06F 34/18** (2020.01)  
**B07C 5/36** (2006.01)  
**B25J 9/00** (2006.01)  
**B25J 9/04** (2006.01)  
**B25J 15/02** (2006.01)  
**B25J 19/02** (2006.01)  
**B25J 21/00** (2006.01)

#### (52) U.S. Cl.

CPC ..... **B25J 15/0206** (2013.01); **B25J 19/021**  
 (2013.01); **B25J 21/00** (2013.01); **D06F 34/18**  
 (2020.02); **B07C 2501/0063** (2013.01); **G05B**  
**2219/39469** (2013.01); **G05B 2219/40532**  
 (2013.01)

#### (56) References Cited

##### U.S. PATENT DOCUMENTS

5,595,467 A 1/1997 Jensen  
 6,089,810 A 7/2000 Heinz et al.  
 6,287,066 B1 9/2001 Heinz et al.  
 6,618,968 B1 9/2003 Nielsen  
 6,655,890 B1 12/2003 Weir  
 6,826,856 B1 12/2004 McCabe  
 7,448,152 B2 11/2008 Jensen et al.  
 9,789,508 B2 \* 10/2017 Baumgartner ..... A61L 9/122  
 10,919,709 B2 \* 2/2021 Mattern ..... B25J 9/1612  
 11,053,620 B2 \* 7/2021 Alif ..... D06F 29/005  
 11,535,977 B2 \* 12/2022 Coney ..... D06F 34/14  
 2002/0157190 A1 10/2002 Imai et al.  
 2004/0105736 A1 6/2004 Nielsen  
 2005/0012349 A1 1/2005 Rauch et al.  
 2006/0191170 A1 8/2006 Jensen et al.  
 2006/0191171 A1 8/2006 Jensen et al.  
 2008/0149460 A1 6/2008 Harris  
 2012/0046783 A1 2/2012 Kechel  
 2012/0099947 A1 4/2012 Heinz et al.  
 2012/0103029 A1 5/2012 Darwin et al.  
 2012/0308339 A1 12/2012 McCabe  
 2014/0219732 A1 8/2014 Thorpe  
 2015/0361610 A1 12/2015 Yano

2016/0216712 A1 \* 7/2016 Baumgartner ..... A61L 2/24  
 2017/0066003 A1 \* 3/2017 Baumgartner ..... A61L 9/14  
 2019/0321984 A1 \* 10/2019 Yamazaki ..... B25J 15/12  
 2020/0042822 A1 2/2020 Chae  
 2020/0332449 A1 \* 10/2020 Alif ..... D06F 29/005  
 2022/0098779 A1 \* 3/2022 Coney ..... D06F 95/00  
 2022/0120030 A1 \* 4/2022 Schechter ..... B25J 15/0206

##### FOREIGN PATENT DOCUMENTS

EP 1498539 A1 1/2005  
 EP 2677078 A1 12/2013  
 EP 3280839 A1 2/2018  
 GB 1525491 A 9/1978  
 WO 9713914 A1 4/1997  
 WO 02077355 A1 10/2002  
 WO 2017153511 A1 9/2017  
 WO 2017182309 A1 10/2017  
 WO 2019072751 A1 4/2019  
 WO 2020079125 A1 4/2020  
 WO WO-2021243073 A1 \* 12/2021 ..... B25J 11/008  
 WO WO-2022082101 A1 \* 4/2022 ..... D06F 34/18

##### OTHER PUBLICATIONS

The laundry folding robot you've always wanted is coming next year. (Year: 2016).  
 Chicago CD, The Heavy Duty Automatic Flatwork Separating System CASCADE®, Bulletin #7560, available prior to filing.  
 Inwatec, Line 3: Automatic Sorting, <https://inwatec.dk/products/line-3-automatic-sorting/>, 4 pages, available as of filing date.  
 Smartlaundrey With Laundry Carts: The Success Story of the "Warener Waschfee", <https://www.kannegiesser.com/global/en/company/breaking-news/article/smartlaundry-with-laundry-carts-the-success-story-of-the-warener-waschfee.html>, 1 pg.  
 Inwatec—Fully Automatic Sorting of Soiled Workwear, retrieved from Youtube: <https://www.youtube.com/watch?v=mfOcVpMNdHg>, Feb. 16, 2018.  
 Soiled Side Sorting of the Future: Robot, RFID, X-ray, Automatic Sorting, retrieved from Youtube: [https://www.youtube.com/watch?v=-oDMVnP\\_p8](https://www.youtube.com/watch?v=-oDMVnP_p8), Mar. 26, 2018.  
 Paton, Scott, "Stepping Into the Future-AI in the Laundry", <https://laundryledger.com/the-future-of-ai-based-automation-in-the-laundry-industry/>.  
 Poe, Matt, "Artificial Intelligence: Future of Laundry Operations? (Part 1) Difference between artificial intelligence, automation", <https://americanlaundrynews.com/articles/artificial-intelligence-future-laundry-operations-part-1>, 5 pages., Dec. 17, 2020.  
 International Search Report and Written Opinion for PCT/US2021/055412 dated Jan. 31, 2022, 12 pages.

\* cited by examiner




FIG. 1





FIG. 2






FIG. 4








FIG. 5














FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14B




FIG. 14A






FIG. 15A







FIG. 15B








FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22






FIG. 23




FIG. 24B

FIG. 24A





FIG. 24C



25.




FIG. 26




FIG. 27









FIG. 28






FIG. 30A




FIG. 30B




FIG. 30C






FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38






FIG. 39A




FIG. 39B




FIG. 40A




FIG. 40B




FIG. 41A




FIG. 41B




FIG. 42A




FIG. 42B




FIG. 43A




FIG. 43B





FIG. 44






FIG. 46






FIG. 47




FIG. 48




FIG. 49




FIG. 50




FIG. 51A




FIG. 51B




FIG. 52A




FIG. 52B




FIG. 53








FIG. 55A




FIG. 55B




FIG. 56A






FIG. 56B



1

## ROBOTIC LAUNDRY SORTING DEVICES, SYSTEMS, AND METHODS OF USE

### CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims priority under 35 U.S.C. § 119(e) to U.S. Provisional Patent Application Ser. No. 63/093,236 filed Oct. 18, 2020, titled “Robotic Laundry Sorting Devices, Systems, And Methods of Use,” the entirety of which application is hereby incorporated by reference.

### BACKGROUND

The present disclosure is directed to robotic laundry devices, systems, and methods.

Automating and outsourcing mundane, time-consuming household chores to robotic devices is increasingly common. Time saving home robots include, for example, floor vacuuming and floor washing robots. Outsourcing responsibilities include, for example, engaging grocery shopping and delivery services, and manually operated and human-operator dependent laundry washing and dry-cleaning pick up and return services.

Many homes are appointed with a dedicated washer and dryer for family use. Domestic washers and dryers are increasingly sophisticated and include IoT connectivity features and push notifications for alerting users about cycle progress and energy and resource usage. These technologically advanced machines, however, require human interaction and cannot eliminate the time required for processing loads of laundry in the home. Although more modern, “high efficiency” machines are equipped with sensors for metering water usage and dryer temperatures, the efficiency gains are capped by the constraints of sequentially processing single loads of laundry. Grey water is output to the city water and sewer system for mitigation with each load of laundry processed. Energy is consumed with each load of laundry washed and dried.

Households can outsource laundry chores to gig worker services and/or laundromat facilities for a fee in exchange for time. Laundromats and gig services offering residential mixed load laundering services, however, require human interaction for intake and sorting of dirty laundry, transferring loads from washer to dryer, and then manually folding clean laundry. These are costly processes as measured in time, energy consumption, water consumption, and wastewater output, and they rely on human intervention to keep the process running at every transition and throughout several process steps. This invites delays at every stage. Because these processes are human-dependent and inefficient, the costs are passed along to customers outsourcing their laundry for cleaning. Human-reliant laundering services also require that employees touch the belongings of the customer, potentially exposing the employee to contaminants in the dirty laundry and potentially exposing the clean laundry to transferable pathogens, dust, hair, and other debris emanating from a laundromat employee. In addition to potentially introducing undesirable contact contamination from the employees processing the loads of laundry, a privacy barrier is breached. Outsourcing household laundry to a laundromat or gig economy worker involves employees interacting with customers’ personal belongings including bodily worn garments.

Industrial laundry services exist for handling uniform, batched business-related items, such as batches of hospital or hotel bed sheets, batches of medical scrubs, and batches

2

of hotel towels, each batch having consistent characteristics between and within loads for determining expectedly consistent washing and drying processes. Such industrial machines are tailor-made to accept one type of laundry item of one size or style. For example, unique folding machines exist to accept a dedicated one of washed flat sheets, fitted sheets, hotel towels, and hotel bathrobes. These machines require human operators to load the washed article into its dedicated machine, which is sized and designed to fold that one type and size of article. This type of process line relies on a human operator for properly aligning and loading the clean article into the machine, which could introduce bodily contaminants, bacteria, and viral matter into the clean articles. Like laundromat services and gig workers washing in their home appliances, these industrial services rely on human intervention and potentially introduce bio-contaminants into clean loads of laundry. Because these services are only profitable by processing large volumes of like items, these industrial processors are generally subscription-based services for large clients like hotels and hospitals producing standard-size, repeat laundry articles and are not available to consumers at an individual household level. Additionally, these services are configured to combine laundry from more than one source and are not configured to isolate and process separate loads for individual households.

Autonomous robotic devices are provided to process loads of household laundry. Such devices eliminate human contact with deformable laundry articles. As such, the devices need to be designed to be efficient and reliable for replacing the common, human-dependent chore of laundry.

### SUMMARY

In one example, an autonomous sorting device for separating and sorting a plurality of amassed deformable articles includes an enclosed channel, a plurality of arms, an inlet orifice, an outlet orifice, at least one sensor, and a controller. The enclosed channel includes a plurality of sequential work volumes and a stationary floor extending between an inlet end and an outlet end of the channel. A portion of the stationary floor is within a first work volume of the plurality of sequential work volumes being configured to receive thereon the plurality of deformable articles adjacent the inlet end. The plurality of arms are disposed in series along the enclosed channel. Each one of the plurality of arms includes an actuatable terminal gripper configured to selectively grasp at least one of the plurality of deformable articles and at least one drive configured to at least one of rotate, tilt, extend, and retract the terminal gripper, each of the plurality of arms being associated with one of the plurality of sequential work volumes. The inlet orifice is disposed in at least one of a ceiling and a wall of the enclosed channel, and the plurality of deformable articles are received into the enclosed channel through the inlet orifice. The outlet orifice is disposed adjacent the outlet end in at least one of a wall of the enclosed channel and the stationary floor, each one of the plurality of deformable articles exiting the enclosed channel through the outlet orifice. The at least one sensor is disposed at least one of on, adjacent to, and within one or more of the plurality of sequential work volumes. The at least one sensor is configured to detect at least one of the plurality of deformable articles disposed within at least one of the plurality of sequential work volumes, and output a signal indicative of at least one of the presence and location of the at least one of the plurality of deformable articles relative to the terminal gripper of one of the plurality of arms associated with the at least one of the plurality of sequential

3

work volumes within which that at least one of the plurality of deformable articles is detected. The controller is in operable communication with the at least one drive and the at least one sensor. The controller is configured to receive a signal from the at least one sensor indicative of detecting at least one of the plurality of deformable articles being disposed within at least one of the plurality of sequential work volumes. The controller is configured to determine a location of the at least one of the plurality of deformable articles on the stationary floor relative to an arm associated with one of the plurality of sequential work volumes within which the at least one of the plurality of deformable articles is detected. The controller is configured to instruct the at least one drive to position a terminal gripper to grasp the at least one of the plurality of deformable articles, the terminal gripper being disposed on the arm associated with the at least one of the plurality of sequential work volumes within which the at least one of the plurality of deformable articles is detected. The controller is configured to instruct an actuator of the terminal gripper to close on the at least one of the plurality of deformable articles, instruct the at least one drive to raise the closed terminal gripper of the associated arm and the grasped at least one of the plurality of deformable articles to a hoist height above the stationary floor and rotate toward the outlet end into an adjacent work volume, instruct the actuator of the terminal gripper to open the gripper to release the at least one of the plurality of deformable articles in the adjacent work volume, receive a signal from the at least one sensor configured to detect the released at least one of the plurality of deformable articles within the adjacent work volumes, and determine, based on the received signal, a state including at least one of: one or more of the plurality of deformable articles are present on the stationary floor, none of the plurality of deformable articles are present on the stationary floor, and one of the plurality of deformable laundry articles exited the enclosed channel through the outlet orifice.

Implementations of the device may include one or more of the following features.

In examples, the plurality of deformable articles are non-uniform.

In examples, the plurality of sequential work volumes includes three or more work volumes.

In examples, the outlet orifice is disposed in a last work volume of the plurality of sequential work volumes, the last work volume being adjacent the outlet end.

In examples, the outlet orifice is disposed in the stationary floor of a last of the plurality of sequential work volumes.

In examples, a number of work volumes including the plurality of sequential work volumes is one greater than the number of the plurality of arms and each of the plurality of arms is associated with a work volume directly adjacent at least one other work volume associated with one of the plurality of arms.

In examples, the plurality of sequential work volumes includes three or more work volumes and the plurality of arms includes three or more arms, each of the three or more arms being associated with one of the three or more work volumes.

In examples, the plurality of sequential work volumes includes three or more work volumes and an outlet-facing end of each of the three or more work volumes overlaps with an inlet-facing end of an adjacent sequential one of the three or more work volumes such that each arm of the plurality of arms is configured to extend into one or more adjacent work volumes of the plurality of sequential work volumes.

4

In examples, the controller is further configured to, based on determining one or more deformable articles are present on the stationary floor in the adjacent work volume, iteratively determine a location of the at least one of the plurality of deformable articles on the stationary floor relative to an arm associated with the adjacent work volume, instruct the at least one drive of the arm associated with the adjacent work volume to position the terminal gripper of the arm associated with the adjacent work volume at the determined location to grasp the at least one of the plurality of deformable articles, instruct an actuator of the terminal gripper of the arm associated with the adjacent work volume to close on the at least one of the plurality of deformable articles, instruct the at least one drive to raise the closed terminal gripper of the arm associated with the adjacent work volume and the grasped at least one of the plurality of deformable articles to a hoist height above the stationary floor and rotate toward the outlet end into a next sequential adjacent work volume of the three or more work volumes, instruct the actuator of the terminal gripper to open the gripper to release the at least one of the plurality of deformable articles in the next sequential adjacent work volume, receive a signal from the at least one sensor configured to detect the at least one of the plurality of deformable articles, and determine, based on the received signal, a state including at least one of the following conditions: one or more of the plurality of deformable articles are present on the stationary floor, none of the plurality of deformable articles are present on the stationary floor, and one of the plurality of deformable articles exited the enclosed channel through the outlet orifice. In examples, the controller is configured to stop iterating when the plurality of deformable articles exits the enclosed channel through the outlet orifice as solitary deformable articles.

In examples, the controller is further configured to instruct two or more of the plurality of arms to operate simultaneously within each associated one of the plurality of sequential work volumes. The terminal grippers of the two or more of the plurality of arms operating simultaneously can simultaneously grasp at least one of the plurality of deformable articles.

In examples, the controller is further configured to, based on determining none of the plurality of deformable articles are present on the stationary floor in the adjacent work volume, receive a signal from the at least one sensor indicative of at least one of the plurality of deformable articles remaining disposed within the one of the plurality of sequential work volumes preceding the adjacent work volume, determine a location of the at least one of the plurality of deformable articles on the stationary floor relative to the associated arm, instruct the at least one drive to position the terminal gripper of the associated arm at the determined location to grasp the at least one of the plurality of deformable articles, instruct an actuator of the terminal gripper of the associated arm to close on the at least one of the plurality of deformable articles, instruct the at least one drive to raise the closed terminal gripper of the associated arm and the grasped at least one of the plurality of deformable articles to a hoist height above the stationary floor and rotate toward the outlet end into the adjacent work volume, instruct the actuator of the terminal gripper to open the gripper to release the at least one of the plurality of deformable articles in the adjacent work volume, and determine, based on the received signal, a state including at least one of the following conditions: one or more of the plurality of deformable articles are present on the stationary floor, none of the plurality of deformable articles are present on the stationary

5

floor, and one of the plurality of deformable articles exited the enclosed channel through the outlet orifice.

In examples, the enclosed channel is fully enclosed on all sides and at the inlet and outlet ends. The inlet orifice and outlet orifice can each further include an actuated covering for selectively exposing and sealing each of the orifices, the controller being in operative communication with the actuation of each covering.

In examples, the stationary floor includes a substantially level surface from the inlet end to the outlet end. The stationary floor can include a substantially continuous surface throughout all of the plurality of sequential work volumes.

In examples, the enclosed channel is raised.

In examples, the one or more bins are configured to be disposed beneath the stationary floor, each of the one or more bins being configured to receive one or more of the plurality of deformable articles having one or more characteristics associated with at least one of the one or more bins. One of the one or more bins (e.g., sorting bins) can be disposed beneath the exit orifice for receiving each one of the plurality of deformable articles exiting the enclosed channel individually.

In examples, each of the one or more bins includes an identification marker for associating an identity of the bin. The one or more characteristics can include at least one of color, size, material composition, article type, degree of dirtiness, and fabric heat tolerance. The device can include an actuated carousel in operable communication with the controller, the actuated carousel being configured to receive thereon the one or more bins and rotate the one or more bins beneath the enclosed channel to match a characteristic of one of the one or more bins positioned beneath the outlet orifice with the one or more characteristics of each one of the plurality of deformable articles exiting the enclosed channel. In examples, the identification marker includes at least one of a machine-readable serial number, a bar code, a machine-readable QR code, an RFID code, NFC tag, a WIFI enabled tag, a ZIGBEE enabled tag, and an active radio telemetry system. A memory in communication with the controller can be configured to store at least one relation including one of the one or more characteristics associated with the bin, the bin identification marker for each of the one or more bins, and a customer identity shared by the plurality of deformable articles received into the enclosed channel.

In examples, the controller is in communication with a communication network and a remote terminal in communication with the communication network is configured to receive a customer input including the one or more characteristics associated with the plurality of deformable articles.

In examples the at least one sensor is configured to detect the one or more characteristics of each one of the plurality of deformable articles and output a signal to the controller including the detected one or more characteristics. The at least one sensor can include at least one of a 3-D camera, an IR sensor, a 2-D camera, LIDAR, LADAR, a sonar proximity sensor, an ultrasonic ranging sensor, a radar sensor, a pair of stereo depth cameras, and a spectrometer. In examples, the at least one sensors outputs at least one of depth map, RGB images, and IR images. The at least one sensor can be configured to output 3-D image data to the controller. The at least one sensor are configured to output one or more 2-D images to the controller. In examples, the at least one sensor is a camera, and the camera is calibrated to the floor of the enclosed channel and one or more of the plurality of arms.

6

In examples, the controller is further configured to determine, based on a comparison of a received output signal of the at least one sensor to data stored in a memory in communication with the controller, at least one of an article type, an article color, an article size, and an article fabric. At least one of the at least one sensor is a 2-D camera and the data associated with repositioned deformable laundry article is size invariant image data. The memory can further include a neural network and determining the one or more characteristics of each one of the plurality of deformable articles includes processing the received output signal of the at least one sensor of each of the plurality of work volumes with a neural network classifier.

In examples, the controller is further configured to receive an output signal including an image, determine, based on the output signal, a number of pixels in each of an upper half and a lower half of the image, the number of pixels being representative of at least one deformable article being grasped by a terminal gripper and held at a hoist height, and determine based on the number of pixels in the lower half of the image exceeding a preset threshold that the at least one deformable article is a large sized article.

In examples, the controller is further configured to receive an output signal including an image of a deformable article in the enclosed channel, determine, based on the output signal and a calibrated coordinate space, where in the calibrated coordinate space each pixels of the image lies, and determine at least one of a location, shape, and size of the deformable article. In examples, the at least one sensor is a camera and the camera is calibrated to the floor of the enclosed channel and one or more of the plurality of arms.

In examples, the controller is further configured to determine, based on receiving a signal from the at least one sensor disposed within at least one of the plurality of sequential work volumes, that none of the plurality of deformable articles remain on the stationary floor in any of the plurality of sequential work volumes. Upon determining that none of the plurality of deformable articles remain on the stationary floor in any of the plurality of sequential work volumes, the controller is further configured to instruct an actuator of the carousel to transit the one or more bins of the sorted plurality of deformable articles to one or more autonomous combination washing and drying machines.

In examples, a retractable cleaner is configured to advance through the enclosed channel from the inlet end to the outlet end while cleaning one or more interior surfaces. The retractable cleaner can form the inlet wall of the enclosed channel in a fully retracted position. In implementations, the retractable cleaner includes a planar profile contoured and fitted to a cross sectional profile of the enclosed channel. The retractable cleaner includes an actuatable cleaning drive in operable communication with the controller. Upon determining that none of the plurality of articles remain on the stationary floor in any of the sequential work volumes, the controller is configured to instruct the retractable cleaner to advance from the inlet end to the outlet end of the enclosed channel. The controller can be configured to instruct the plurality of arms to retract from their associated work volumes prior to the retractable cleaner advancing through the plurality of work volumes such that only the terminal gripper of each of the plurality of arms remains within an associated work volume. The retractable cleaner can include a slot configured to pass over and clean the terminal gripper.

In examples, one or more UV lights are in operable communication with the controller. The one or more UV lights illuminate the one or more sequential work volumes of the enclosed channel after the retractable cleaner advances

to the outlet end and retracts to the inlet end. The one or more UV lights can be disposed on an interior surface of the enclosed channel. The controller can be further configured to instruct the plurality of arms fully extend into the enclosed channel before the one or more UV lights are illuminated.

In examples, the retractable cleaner further includes one or more wheels extending from a face of the retractable cleaner for guiding motion of the retractable cleaner along one or more interior surfaces of the enclosed channel.

In examples, the retractable cleaner further includes a plurality of spray ports disposed along a continuous outer surface of the retractable cleaner facing the one or more interior surfaces of the enclosed channel. A service line can be in fluid communication with the plurality of spray ports. The service line can be configured to provide a cleaning fluid for application to the one or more interior surfaces via the plurality of ports. The cleaning fluid includes at least one of steam, water, detergent, germicide, and pesticide. The service line can further include at least one of a vacuum line and a power conduit.

In examples, the retractable cleaner further includes a plurality of evacuation ports disposed along the continuous outer surface of the retractable cleaner facing the one or more interior surfaces of the enclosed channel. The plurality of evacuation ports can be in operative communication with the vacuum line for suctioning remaining moisture from the one or more interior surfaces of the enclosed channel upon advancement of the retractable cleaner through the enclosed channel.

In examples, the retractable cleaner includes a squeegee on a trailing edge of the continuous outer surface of the retractable cleaner facing the one or more interior surfaces of the enclosed channel.

In examples, the device further includes at least one fill sensor in communication with the controller. The at least one fill sensor is configured to detect an occupied volume of the one or more bins. The at least one fill sensor can be an optical sensor configured to detect a minimum threshold fill line and a maximum threshold fill line disposed on an interior surface of one of the one or more bins positioned beneath the exit orifice. The fill sensor can be configured to detect whether the of one or more of the plurality of deformable articles received in the one of the one or more bins reaches or surpasses the minimum threshold fill line. In examples, the maximum threshold fill line is a top edge of the one of the one or more bins, and the fill sensor is configured to output a signal indicative of the occupied volume of the one of the one or more bins being with a threshold range between the minimum threshold fill line and maximum threshold fill line. Upon determining an occupied volume of the one of the one or more bins is within a threshold range indicative of being filled, the controller is further configured to instruct the carousel to unload the filled one of the one or more bins containing the sorted plurality of deformable articles to an autonomous combination washing and drying machine.

In examples, the at least one fill sensor is a weight sensor disposed beneath the one of the one or more bins positioned beneath the exit orifice and configured to detect whether the weight of the one of the one or more bins reaches or surpasses a minimum threshold weight indicative of a bin full condition. The weight sensor can be a scale.

In examples, the at least one fill sensor is configured to output a signal indicative of a bin full condition. Upon determining a bin full condition, the controller is further configured to instruct the carousel to unload the filled one of

the one or more bins containing the sorted plurality of deformable articles to an autonomous combination washing and drying machine.

In examples, the plurality of deformable articles includes one or more loads of dirty household laundry. The plurality of deformable articles can include two or more article types of at least one of different sizes, different shapes, different colors, and different fabrics.

In examples, the device further includes an actuated outlet door in operable communication with the controller. The controller can be further configured to receive a signal from the at least one sensor indicative of the presence of a deformable article above the outlet orifice, and actuate the outlet door to reveal the outlet orifice when a deformable article is positioned above the outlet orifice for exiting the channel.

In examples, the inlet orifice is disposed in ceiling of the enclosed channel. The device further includes an actuatable inlet door in operable communication with the controller. The actuatable inlet door is configured to selectively seal and expose the inlet orifice. Upon alignment of a sealed container containing the plurality of deformable articles above the inlet orifice, the controller is further configured to actuate the inlet door to reveal the inlet orifice. In examples, the device further includes a pair of rotatable clamps configured to engage the container and rotate the container to an inverted position for dropping the plurality of deformable articles onto the stationary floor of the enclosed channel. A hinged lid of the sealed container can be configured to open into the inlet orifice upon rotation to an inverted position.

In examples, the plurality of arms of the device each further include a rod configured to extend from an anchor at corresponding individually anchored positions. The rod includes a fully extended length of between about 0.25 m and 4 m. The anchor includes at least one drive, and the at least one drive includes a pan drive, a tilt drive, and an extend drive. The controller can be further configured to drive the at least one drive in at least one of alternating side-to-side and alternating up and down motions to shake a grasped deformable article of the plurality of deformable articles at the hoist height.

In examples, each one of the plurality of arms includes between one and three degrees of freedom.

In examples, each one of the plurality of arms includes at least one compliant joint. The at least one compliant joint can include a compliant wrist disposed between the extendable rod and the terminal gripper.

In examples, the terminal gripper of each of the plurality of arms includes at least two actuatable fingers. The at least two actuatable fingers can include an overmold including a durometer of between about 40 A to 80 A.

In examples, the terminal gripper of each of the plurality of arms is at least one of cable driven and pneumatically driven, and an actuator of each terminal gripper is in operable communication with the controller.

In examples, the device further includes a wrist disposed between each of the plurality of arms and an associated terminal gripper. The wrist includes one or more sensors configured to detect forces applied to the terminal gripper.

In examples, each anchor is disposed on a base outside the enclosed channel and the associated one of the plurality of arms disposed on the base extends through a side wall of the enclosed channel. The device can further include a plurality of openings in a sidewall of the enclosed channel, each of the plurality of openings being configured to receive a rod of each one of the plurality of arms therethrough and a seal disposed about each of the plurality of openings through

which the rod of each one of the plurality of arms extends. The seal can include and/or be manufactured from a flexible material configured to stretch as the rod extends, pans, tilts, and retracts. The seal can be pleated and compressible. The seal can be configured to enable the rod to retract so that only the terminal gripper remains exposed within the enclosed channel. The flexible material can include at least one of NEOPRENE, vinyl, rubber, plastic, leather, urethane, silicone, and elastane (SPANDEX).

In examples, a plurality of anchors each associated with the plurality of arms are disposed on at least one of a wall, the stationary floor, and the ceiling of the enclosed channel.

In examples, the hoist height is a predetermined hoist height. The predetermined hoist height can include a range of between about 0.5 to 4 m above the stationary floor.

In examples, the device further includes one or more weight sensors disposed on each of the plurality of arms. The one or more weight sensor are in operative communication with the controller and configured to continuously detect a rate of change as each one of the plurality of deformable laundry articles is raised. The controller is configured to determine each one of the plurality of deformable laundry articles is raised to a hoist height when the one or more weight sensors detect an unchanging rate of change of measured weight.

In examples, the at least one sensor of the device includes at least one of a 3-D camera, an IR sensor, a 2-D camera, LIDAR, LADAR, a sonar proximity sensor, an ultrasonic ranging sensor, a radar sensor, and a pair of stereo depth cameras. The at least one sensor can output to the controller at least one of a depth map, RGB images, and IR images. The at least one sensor can be configured to output 3-D image data to the controller. Additionally or alternatively, the at least one sensor can be configured to output one or more 2-D images to the controller. In examples, the at least one sensor is a camera and the camera is calibrated to the floor of the enclosed channel and one or more of the plurality of arms.

In examples, determining a location of the at least one of the plurality of deformable articles on the stationary floor further includes determining one or more grip points on the at least one of the plurality of deformable articles. In examples, the one or more grip points are disposed on a high point of the at least one of the plurality of deformable articles. Additionally or alternatively, the one or more grip points are disposed on an edge of the at least one of the plurality of deformable articles. Additionally or alternatively, the controller is configured to generate a mask of the at least one of the plurality of deformable articles and identify one or more grip points that are disposed within an area of the mask.

In examples, the at least one sensor is disposed outside the enclosed channel above one or more of the plurality of sequential work volumes.

In examples, the at least one sensor is disposed adjacent a transparent window in a ceiling of the enclosed channel and includes a field of view encompassing the associated work volume.

In examples, the at least one sensor is disposed within the enclosed channel adjacent one of the plurality of arms and includes a field of view encompassing the work volume associated with the adjacent one of the plurality of arms.

In one example, a method of robotically sorting a plurality of deformable laundry articles into loads for washing includes receiving, at a controller, a signal from at least one sensor disposed at least one of on, adjacent to, and within one or more of a plurality of sequential work volumes, the

signal being indicative of at least one of the plurality of deformable laundry articles being disposed within the at least one of the plurality of sequential work volumes. The method includes determining, based on the received signal, a location of the at least one of the plurality of deformable articles on a stationary floor within at least one of the plurality of sequential work volumes, the plurality of sequential work volumes being constituent to an enclosed channel and the stationary floor extending between an inlet end and an outlet end of the enclosed channel, a portion of the stationary floor adjacent the inlet end being configured to receive thereon the plurality of deformable laundry articles. The method includes instructing at least one drive of at least one of a plurality of arms disposed in series along the enclosed channel to at least one of rotate, tilt, extend, and retract a terminal gripper configured to selectively grasp at least one of the plurality of deformable laundry articles at the determined location, each one of the plurality of arms being associated with one of the plurality of sequential work volumes. The method includes instructing, by the controller, an actuator of the terminal gripper to close on the at least one of the plurality of deformable laundry articles. The method includes instructing the at least one drive to raise the closed terminal gripper and the grasped at least one of the plurality of deformable laundry articles to a hoist height above the stationary floor, and rotate toward the outlet end into an adjacent work volume. The method includes instructing the actuator of the terminal gripper to open the gripper to release the at least one of the plurality of deformable laundry articles in the adjacent work volume, receiving a signal from at least one sensor in the adjacent work volume of the plurality of sequential work volumes, and determining, based on the received signal, a state including at least one of the following: one or more of the plurality of deformable laundry articles are present on the stationary floor, one or more of the plurality of deformable laundry articles are not present on the stationary floor, and one the plurality of deformable laundry articles exited the enclosed channel through an outlet orifice disposed in the stationary floor adjacent the outlet end.

Implementations of the method may include one or more of the following features.

In examples, the plurality of sequential work volumes includes three or more work volumes.

In examples, the outlet orifice is disposed in a last work volume of the plurality of sequential work volumes, the last work volume being adjacent the outlet end.

In examples, the outlet orifice is disposed in the stationary floor of a last of the plurality of sequential work volumes.

In some examples, a number of work volumes including the plurality of sequential work volumes is one greater than the number of the plurality of arms and each of the plurality of arms is associated with a work volume directly adjacent at least one other work volume associated with one of the plurality of arms.

In examples, the plurality of sequential work volumes includes three or more work volumes, and the plurality of arms includes three or more arms. Each of the three or more arms is associated with one of the three or more work volumes.

In examples, the plurality of sequential work volumes includes three or more work volumes and an outlet-facing end of each of the three or more work volumes overlaps with an inlet-facing end of an adjacent sequential one of the three or more work volumes such that each arm of the plurality of arms is configured to extend into one or more adjacent work volumes of the plurality of sequential work volumes.



11

In examples, the method further includes, based on determining clothes are present on the stationary floor in the adjacent work volume, iteratively determining a location of the at least one of the plurality of deformable laundry articles on the stationary floor relative to an arm of the plurality of arms associated with the adjacent work volume, instructing the at least one drive of the arm associated with the adjacent work volume to position the terminal gripper of the arm associated with the adjacent work volume at the determined location to grasp the at least one of the plurality of deformable laundry articles, instructing an actuator of the terminal gripper of the arm associated with the adjacent work volume to close on the at least one of the plurality of deformable laundry articles, instructing the at least one drive to raise the closed terminal gripper of the arm associated with the adjacent work volume and the grasped at least one of the plurality of deformable laundry articles to a hoist height above the stationary floor and rotate toward the outlet end into a next sequential adjacent work volume of the three or more work volumes, instructing the actuator of the terminal gripper to open the gripper to release the at least one of the plurality of deformable laundry articles in the next sequential adjacent work volume, receiving a signal from the at least one sensor configured to detect the at least one of the plurality of deformable laundry articles in the next sequential adjacent work volume of the plurality of sequential work volumes, and determining, based on the received signal, a state including at least one of the following: one or more of the plurality of deformable laundry articles are present on the stationary floor, one or more of the plurality of deformable laundry articles are not present on the stationary floor, and one of the plurality of deformable laundry articles exited the enclosed channel through the outlet orifice.

In examples, the method further includes stopping iterating when each one of the plurality of deformable laundry articles exits the enclosed channel through the outlet orifice as a solitary deformable article.

In examples, the method further includes instructing two or more of the plurality of arms to operate simultaneously within each associated one of the plurality of sequential work volumes. The terminal grippers of the two or more of the plurality of arms operating simultaneously are configured to simultaneously grasp at least one of the plurality of deformable articles.

In examples, the method further includes instructing the at least one drive to move the terminal gripper in at least one of alternating side-to-side and alternating up and down motions to shake a grasped deformable article of the plurality of deformable articles at the hoist height.

In examples, the at least one sensor of the device includes at least one of a 3-D camera, an IR sensor, a 2-D camera, LIDAR, LADAR, a sonar proximity sensor, an ultrasonic ranging sensor, a radar sensor, and a pair of stereo depth cameras. The at least one sensor can output to the controller at least one of a depth map, RGB images, and IR images. The at least one sensor can be configured to output 3-D image data to the controller. Additionally or alternatively, the at least one sensor can be configured to output one or more 2-D images to the controller. In examples, the at least one sensor is a camera and the camera is calibrated to the floor of the enclosed channel and one or more of the plurality of arms.

In examples, determining a location of the at least one of the plurality of deformable articles on the stationary floor further includes determining one or more grip points on the at least one of the plurality of deformable articles. In examples, the one or more grip points are disposed on a high

12

point of the at least one of the plurality of deformable articles. Additionally or alternatively, the one or more grip points are disposed on an edge of the at least one of the plurality of deformable articles.

In examples, the method further includes, based on determining clothes are not present on the stationary floor in the adjacent work volume, receiving a signal from the at least one sensor indicative of at least one of the plurality of deformable laundry articles remaining disposed within the one of the plurality of sequential work volumes preceding the adjacent work volume, determining a location of the at least one of the plurality of deformable laundry articles on the stationary floor relative to the associated arm, instructing the at least one drive to position the terminal gripper of the associated arm at the determined location to grasp the at least one of the plurality of deformable laundry articles, instructing an actuator of the terminal gripper of the associated arm to close on the at least one of the plurality of deformable articles, instructing the at least one drive to raise the closed terminal gripper of the associated arm and the grasped at least one of the plurality of deformable laundry articles to a hoist height above the stationary floor and rotate toward the outlet end into the adjacent work volume, instructing the actuator of the terminal gripper to open the gripper to release the at least one of the plurality of deformable laundry articles in the adjacent work volume, and determining, based on the received signal, a state including at least one of the following: one or more of the plurality of deformable laundry articles are present on the stationary floor, one or more of the plurality of deformable laundry articles are not present on the stationary floor, and one of the plurality of deformable laundry articles exited the enclosed channel through the outlet orifice.

In examples, determining a location of the at least one of the plurality of deformable laundry articles on the stationary floor relative to the associated arm includes the controller executing a series of instructions to perform a background subtraction routine on an input signal including a 2D image to locate at least one of the plurality of deformable laundry articles disposed on the stationary floor.

In examples, the background subtraction routine includes outputting a location of a perimeter of the at least one of the plurality of deformable laundry articles on the stationary floor relative to the at least one sensor and a current position of the terminal gripper.

In examples, the method further includes receiving a current signal from the at least one drive indicative of none of the plurality of deformable laundry articles being grasped in the terminal gripper at the hoist height. The controller can determine that the terminal gripper closed without grasping the detected at least one of the plurality of deformable laundry articles and repeat the steps of determining a location of the at least one of the plurality of deformable laundry articles on the stationary floor relative to an arm of the plurality of arms associated with the adjacent work volume, instructing the at least one drive of the arm associated with the adjacent work volume to position the terminal gripper of the arm associated with the adjacent work volume at the determined location to grasp the at least one of the plurality of deformable laundry articles, and instructing an actuator of the terminal gripper of the arm associated with the adjacent work volume to close on the at least one of the plurality of deformable laundry articles.

In examples, the method further includes receiving a contact sensor signal from at least one contact sensor on a gripping surface of the terminal gripper indicative of none of the plurality of deformable laundry articles being grasped in

13

the terminal gripper at the hoist height. The method further includes determining that the terminal gripper closed without grasping the detected at least one of the plurality of deformable laundry articles and repeating the steps of determining a location of the at least one of the plurality of deformable laundry articles on the stationary floor relative to an arm of the plurality of arms associated with the adjacent work volume, instructing the at least one drive of the arm associated with the adjacent work volume to position the terminal gripper of the arm associated with the adjacent work volume at the determined location to grasp the at least one of the plurality of deformable laundry articles, and instructing an actuator of the terminal gripper of the arm associated with the adjacent work volume to close on the at least one of the plurality of deformable laundry articles.

In examples, the method further includes, upon the at least one sensor outputting a signal that none of the plurality of deformable articles are present on the stationary floor, receiving another signal output from the at least one sensor. In examples, the signal includes a 2D image, and the controller is configured to determine a perimeter of at least one of the plurality of deformable articles disposed on the stationary floor. In examples, the another signal includes a 3D image and the controller is further configured to determine a height above the stationary floor of at least one article of the plurality of deformable articles disposed on the stationary floor. In examples, the another signal includes a 2D image and the controller is further configured to perform a background subtraction routine to locate at least one of the plurality of deformable articles disposed on the stationary floor.

In examples, one or more bins are configured to be disposed beneath the stationary floor, and each of the one or more bins is configured to receive one or more of the plurality of deformable laundry articles having one or more characteristics associated with at least one of the one or more bins. In examples, one of the one or more bins (e.g., sorting bins) is disposed beneath the exit orifice for receiving each one of the plurality of deformable laundry articles exiting the enclosed channel individually. In examples, each of the one or more bins includes an identification marker for associating an identity of the bin. The one or more characteristics include at least one of color, size, material composition, article type, degree of dirtiness, and fabric heat tolerance.

In examples, the method further includes actuating a carousel in operable communication with the controller, the carousel being configured to receive thereon the one or more bins. Actuating the carousel includes repositioning the one or more bins beneath the enclosed channel to match a characteristic of one of the one or more bins positioned beneath the outlet orifice with the one or more characteristics of each one of the plurality of deformable laundry articles exiting the enclosed channel.

In examples, the identification marker includes at least one of a machine-readable serial number, a bar code, a machine-readable QR code, an RFID code, NFC tag, a WIFI enabled tag, a ZIGBEE enabled tag, and an active radio telemetry system.

In examples, the method further includes storing on a memory in communication with the controller, at least one relation including one of the one or more characteristics associated with the bin, the bin identification marker for each of the one or more bins, and a customer identity shared by the plurality of deformable laundry articles received into the enclosed channel. In examples, the method further includes receiving the one or more characteristics associated

14

with the plurality of deformable laundry articles via a communication network configured to receive a customer input at a remote terminal in wired or wireless communication with the controller in communication with the communication network. In examples, the method further includes receiving the one or more characteristics of each one of the plurality of deformable laundry articles as an output signal from the at least one sensor in communication with the controller.

In examples, the at least one sensor includes at least one of a 3-D camera, an IR sensor, a 2-D camera, LIDAR, LADAR, a sonar proximity sensor, an ultrasonic ranging sensor, a radar sensor, a pair of stereo depth cameras, and a spectrometer. The at least one sensor can output to the controller at least one of a depth map, RGB images, and IR images. The at least one sensor can be configured to output 3-D image data to the controller. Additionally or alternatively, the at least one sensor can be configured to output one or more 2-D images to the controller. In examples, the at least one sensor is a camera and the camera is calibrated to the floor of the enclosed channel and one or more of the plurality of arms.

In examples, the controller is further configured to determine, based on a comparison of a received output signal of the at least one sensor to data stored in a memory in communication with the controller, at least one of an article type, an article color, an article size, and an article fabric. In examples, the at least one of the at least one sensor is a 2-D camera and the data associated with the deformable laundry article is size invariant image data. In examples, the memory further includes a neural network, and determining the one or more characteristics of each one of the plurality of deformable laundry articles includes processing the received output signal of the at least one sensor associated with each one of the plurality of work volumes with a neural network classifier.

In examples, the method further includes receiving, by the controller, an output signal including an image, determining, based on the output signal, a number of pixels in each of an upper half and a lower half of the image, the number of pixels being representative of at least one deformable laundry article being grasped by a terminal gripper and held at a hoist height, and determining based on the number of pixels in the lower half of the image exceeding a preset threshold that the at least one deformable laundry article includes a large sized article.

In examples, the method further includes receiving, by the controller, an output signal including an image of a deformable article in the enclosed channel, determining, based on the output signal and a calibrated coordinate space, where in the calibrated coordinate space each pixels of the image lies, and determining at least one of a location, shape, and size of the deformable article.

In examples, the method further includes determining, based on receiving a signal from the at least one sensor disposed within each of the plurality of sequential work volumes, that none of the plurality of deformable articles remain on the stationary floor in any of the plurality of sequential work volumes. In examples, the method further includes upon determining that none of the plurality of deformable articles remain on the stationary floor in any of the plurality of sequential work volumes, instructing an actuator of a carousel supporting one or more bins for collecting the one or more deformable laundry articles to transit the one or more bins of the sorted plurality of deformable articles to one or more autonomous combination washing and drying machines.

15

In examples, the method further includes receiving, by the controller, an output signal of at least one fill sensor. The at least one fill sensor is configured to detect an occupied volume of the one or more bins. In examples, the fill sensor is an optical sensor focused on a minimum threshold fill line and a maximum threshold fill line disposed on an interior surface of one of the one or more bins positioned beneath the exit orifice. The fill sensor is configured to detect whether the of one or more of the plurality of deformable laundry articles received in the one of the one or more bins reaches or surpasses the minimum threshold fill line. The maximum threshold fill line can be a top edge of the one of the one or more bins. In examples, the method further includes receiving, by the controller, an output signal from the fill sensor indicative of the occupied volume of the one of the one or more bins being with a threshold range between the minimum threshold fill line and maximum threshold fill line. Upon determining an occupied volume of the one of the one or more bins is within a threshold range indicative of being filled, the method includes instructing the carousel to transit the filled one of the one or more bins containing the sorted plurality of deformable laundry articles to an autonomous combination washing and drying machine. Additionally or alternatively, in examples, the at least one fill sensor is a weight sensor disposed beneath the one of the one or more bins positioned beneath the exit orifice and configured to detect whether the weight of the one of the one or more bins reaches or surpasses a minimum threshold weight indicative of a bin full condition.

The at least one fill sensor is configured to output a signal indicative of a bin full condition. Upon determining a bin full condition, the method includes instructing the carousel to unload the filled one of the one or more bins containing the sorted plurality of deformable laundry articles to an autonomous combination washing and drying machine.

In examples, the at least one sensor of the device includes at least one of a 3-D camera, an IR sensor, a 2-D camera, LIDAR, LADAR, a sonar proximity sensor, an ultrasonic ranging sensor, a radar sensor, and a pair of stereo depth cameras. In examples, the method further includes receiving by the controller one or more outputs from the at least one sensor including at least one of a depth map, RGB images, and IR images. The at least one sensor can be configured to output 3-D image data to the controller. Additionally or alternatively, the at least one sensor can be configured to output one or more 2-D images to the controller. In examples, the at least one sensor is a camera and the camera is calibrated to the floor of the enclosed channel and one or more of the plurality of arms.

In examples, determining a location of the at least one of the plurality of deformable articles on the stationary floor further includes determining one or more grip points on the at least one of the plurality of deformable articles. In examples, the one or more grip points are disposed on a high point of the at least one of the plurality of deformable articles. Additionally or alternatively, the one or more grip points are disposed on an edge of the at least one of the plurality of deformable articles. In examples, the at least one sensor is disposed outside the enclosed channel above each of the plurality of sequential work volumes. Additionally or alternatively, in examples, the at least one sensor is disposed adjacent a transparent window in a ceiling of the enclosed channel and includes a field of view encompassing the associated work volume. Additionally or alternatively, in examples, the at least one sensor is disposed within the

16

enclosed channel adjacent an associated one of the plurality of arms and includes a field of view encompassing the associated work volume.

In examples, the controller includes at least one controller in operable communication with the at least one drive and the at least one sensor. In examples, the controller is in communication with a communication network and one or more memory stores in communication with the communication network. The controller can be in communication with one or more other controllers in remote communication with the communication network. The communication network is at least one of a wired and wireless network.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 depicts a schematic of an example autonomous robotic laundry process line.

FIG. 2 depicts a schematic of an example autonomous robotic laundry process line including one intake and output and a plurality of washing and drying robots.

FIG. 3 depicts a schematic of a plurality of autonomous robotic laundry process lines including a plurality of intakes and outputs and a plurality of washing and drying robots.

FIG. 4 depicts a schematic example of a system for controlling an autonomous robotic laundry process line.

FIG. 5 depicts a schematic example of a system of autonomous devices configured to separate and sort household laundry articles.

FIG. 6 depicts a perspective view of an arm side of an implementation of an autonomous laundry separating and sorting device.

FIG. 7 depicts a cut away perspective view of an interior of the autonomous laundry separating and sorting device of FIG. 6.

FIG. 8 depicts a perspective view of a back side of the autonomous laundry separating and sorting device of FIG. 6.

FIG. 9 depicts a schematic top down view of an implementation of an autonomous laundry separating and sorting device.

FIG. 10 depicts a schematic view of an implementation of an autonomous laundry separating and sorting system.

FIG. 11 depicts a schematic view of an implementation of an autonomous laundry separating and sorting system.

FIG. 12 depicts a perspective partial view of an implementation of the autonomous laundry separating and sorting device.

FIG. 13 depicts an end view cross section schematic of an implementation of a machine vision system of the autonomous laundry separating and sorting system.

FIG. 14A depicts an end view cross section schematics of an implementation of the autonomous laundry separating and sorting system with enclosure walls removed for clarity to show sensors and determination of grip points of an article.

FIG. 14B depicts the end view cross section schematics of FIG. 14 with a gripper engaging one of the grip points of the article.

FIG. 15A depicts a schematic perspective view of a portion of an implementation of an autonomous laundry separating and sorting system at the start of a sorting process.

FIG. 15B depicts the implementation of the autonomous laundry separating and sorting system of 15A at a next step in the sorting process.

FIG. 16A depicts the implementation of the autonomous laundry separating and sorting system of 15B at a next step in the sorting process.

17

FIG. 16B depicts the implementation of the autonomous laundry separating and sorting system of 16A at a next step in the sorting process.

FIG. 17A depicts the implementation of the autonomous laundry separating and sorting system of 16B at a next step in the sorting process.

FIG. 17B depicts the implementation of the autonomous laundry separating and sorting system of 17A at a next step in the sorting process.

FIG. 18 depicts a schematic perspective view of a portion of the autonomous laundry separating and sorting system during the sorting process.

FIG. 19 depicts a schematic perspective view of a portion of an implementation of an autonomous laundry separating and sorting system beginning a two-arm hoist of a deformable article.

FIG. 20 depicts a schematic perspective view of a portion of the autonomous laundry separating and sorting system of FIG. 19 during a two-arm hoist of a deformable article.

FIG. 21 depicts a schematic perspective view of a portion of the autonomous laundry separating and sorting system of FIG. 20 comprising a two-arm hoist of a deformable article.

FIG. 22 depicts a schematic perspective view of a portion of the autonomous laundry separating and sorting system having a large deformable article therein.

FIG. 23 depicts a perspective partial view of an implementation of the autonomous laundry separating and sorting device comprising an actuatable inlet orifice door.

FIG. 24A depicts a perspective side view schematic of the actuatable inlet orifice door of FIG. 23.

FIG. 24B depicts a side view schematic of the actuatable inlet orifice door of FIG. 23.

FIG. 24C depicts a partial perspective side view schematic of the actuatable inlet orifice door of FIG. 23.

FIG. 25 depicts an implementation of a system for introducing deformable articles into the autonomous laundry separating and sorting device.

FIG. 26 depicts a side view of the system of FIG. 25.

FIG. 27 depicts an enlarged view of a portion of a portion of the system of FIG. 25.

FIG. 28 depicts an elevator configured to raise a container (e.g., box) of dirty laundry articles for transfer to an autonomous dirty laundry box tipping assembly disposed above the separating and sorting robot.

FIG. 29A depicts an alternate schematic implementation of systems for introducing deformable articles into the autonomous laundry separating and sorting device with a vacuum tube.

FIG. 29B depicts an alternate schematic implementation of systems for introducing deformable articles into the autonomous laundry separating and sorting device comprising a lay-flat box configured to open and lay flat to reveal contents within an enclosed channel.

FIG. 29C depicts an alternate schematic implementation of systems for introducing deformable articles into the autonomous laundry separating and sorting device with a grabbing claw for removing articles from a container received within an enclosed channel.

FIG. 29D depicts an alternate schematic implementation of systems for introducing deformable articles into the autonomous laundry separating and sorting device with a sliding shelf configured to pass a container through an orifice, into an enclosed channel and rotate to dump the contents of the container within the enclosed channel.

FIG. 29E depicts an alternate schematic implementation of systems for introducing deformable articles into the autonomous laundry separating and sorting device compris-

18

ing an angled shelf for tilting a container introduced into an enclosed channel for emptying by an arm of the device.

FIG. 30A depicts an autonomous dirty laundry box tipping assembly for loading dirty laundry into an autonomous washing and drying device from a bin held therein.

FIG. 30B depicts the autonomous dirty laundry box tipping assembly of FIG. 30A in a partially overturned rotational position.

FIG. 30C depicts the autonomous dirty laundry box tipping assembly of FIG. 30A in a fully inverted rotational position.

FIG. 31 depicts an exploded view of the autonomous dirty laundry box tipping assembly of FIG. 30A relative to a box.

FIG. 32 depicts a partial cut away view of an end portion of an enclosed channel and a load sorting and batching system of an implementation of the autonomous laundry separating and sorting device.

FIG. 33 depicts a schematic implementation of a neural network for classifying and sorting articles.

FIG. 34 depicts a perspective end view of an implementation of a cleaning system of the autonomous laundry separating and sorting device.

FIG. 35 depicts a cross section schematic end view of a cleaning system of the autonomous laundry separating and sorting device.

FIG. 36 depicts an example of an arm of the autonomous separating and sorting robot.

FIG. 37 depicts a portion of the arm of FIG. 36 with partial transparency to reveal inner working elements of a drive system.

FIG. 38 depicts a rotated view of the portion of the arm of FIG. 37 showing an implementation of a drive system of the arm of the autonomous laundry separating and sorting device.

FIG. 39A depicts an example hinged gripper of the autonomous laundry separating and sorting device.

FIG. 39B depicts an example pulley driven gripper of the autonomous laundry separating and sorting device.

FIGS. 40A-B depict example grippers of the autonomous laundry separating and sorting device.

FIGS. 41A-B depict example grippers of the autonomous laundry separating and sorting device.

FIG. 42A depicts an example gloved gripper in an open position.

FIG. 42B depicts an example gloved gripper in a closed position.

FIG. 43A depicts a side cut away view of an example wrist of the autonomous laundry separating and sorting device.

FIG. 43B depicts a back perspective cut away view of the wrist of FIG. 43A.

FIG. 44 depicts a side perspective cut away view and close up of a portion of the wrist of FIGS. 43A-B.

FIG. 45 depicts an implementation of a method of autonomously separating and sorting a load of dirty laundry with an autonomous separating and sorting device.

FIG. 46 depicts a schematic of an implementation of image processing to detect an article disposed in the autonomous laundry separating and sorting device.

FIG. 47 depicts a state diagram of the autonomous laundry separating and sorting device.

FIG. 48 depicts an implementation of a load constructor for identifying and aligning designated bins with an outlet orifice of the separating and sorting device.

FIG. 49 depicts an exploded view of a portion of the load constructor of FIG. 48 showing a pop up transfer roller assembly raised above a drive roller.

19

FIG. 50 depicts a side view of an implementation of a single pop up transfer roller assembly of FIG. 49.

FIG. 51A depicts an example weight sensor disposed beneath a load constructor.

FIG. 51B depicts the weight sensor of FIG. 51A.

FIG. 52A depicts a single conveyor of the load constructor of FIG. 48.

FIG. 52B depicts a partial perspective view of a pop up transfer roller assembly of FIG. 52A.

FIG. 53 depicts a side perspective view of a plurality of interoperative pop up transfer roller assemblies geared to rotate together on a single conveyor of the load constructor of FIG. 48.

FIG. 54 depicts an end perspective view of the plurality of interoperative pop up transfer roller assemblies of FIG. 53.

FIG. 55A schematic view of a first introduction of a bin into a load constructor loading position.

FIG. 55B depicts a schematic view of an introduction of a second bin into the load constructor loading position of FIG. 55A.

FIG. 56A depicts a schematic view of potential movements of a bin disposed on a load constructor.

FIG. 56B depicts a schematic view of a plurality of cameras disposed about a load constructor.

FIGS. 57A-D depict a sequence of moves of a plurality of bins disposed on a load constructor for filling beneath an outlet orifice of a separating and sorting robot.

#### DETAILED DESCRIPTION

This disclosure relates to autonomous robotic devices, systems, and methods for handling residential loads of laundry without relying on human labor and human related injuries, inefficiencies, theft, and potential contamination. Laundry articles are collected from households and delivered to one or more process lines for cleaning, packing, and returning to the households. The autonomous processes are time and cost efficient, eliminate human intervention-based delays, eliminate line workers and associated potential introduction of human contaminants introduced by line workers, and eliminate any concerns with having private personal items handled by strangers. The system includes one or more autonomous process lines comprising a plurality of autonomous robotic devices configured to work in concert to process one or more dirty loads of household laundry from a collection of dirty, non-uniform articles to individually separated, cleaned, folded, and packed laundry articles. The plurality of autonomous robotic devices operate without human intervention to efficiently and effectively launder a plurality of customers' dirty items, including masses of both uniform and non-uniform articles. This disclosure relates to autonomous robotic devices configured to separate individual articles from a mass of a plurality of dirty laundry articles, sort the individual articles into one or more loads of laundry according to one or more load construction guidelines, and introduce the one or more loads of laundry to one or more combination washer dryers.

As shown in FIG. 1, in implementations of the system, a process line 100a comprises a plurality of autonomous robots configured to operate in series without human intervention to process and transport dirty laundry through the cleaning process, folding and repackaging the clean laundry for return to a household. In one implementation, the process line 100a comprises an automated intake robot 2000 for receiving a load of dirty household laundry comprising a plurality of deformable laundry articles. The deformable

20

laundry articles can be non-uniform in type, size, shape, thickness, color, and fabric (e.g., material type). For example, the plurality of deformable laundry articles can include items commonly laundered in homes, such as sheets, towels, table cloths, curtains, and adult and children's garments, for example, tee shirts, pants, socks, undergarments, dresses, dress shirts, and blouses. The autonomous intake robot 2000 is configured to introduce the plurality of deformable laundry articles to a separating and sorting robot 3000 configured to separate out each one of the deformable laundry articles of the plurality of deformable laundry articles. In implementations, the separating and sorting robot 3000 is configured to sort each one of the separated deformable laundry articles into one or more related batches for washing. In implementations, the separating and sorting robot 3000 is configured to intelligently batch the separated each one of the deformable laundry articles according to a programmed sorting algorithm based, for example, on criteria including at least one of material color, material type, article size, customer washing preference, water temperature requirements, stain treatment requirements, and load size (e.g., weight and/or physical volume). In implementations, the separating and sorting robot 3000 is configured to identify and record the number and types of garments in the load of laundry and provide this information to one or more robots of the process line 100a.

The separating and sorting robot 3000 outputs one or more intelligently sorted batches of deformable laundry articles to one or more washing and drying robots 4000 for laundering. The one or more washing and drying robots 4000 output the clean laundry articles to a clean laundry separating robot 5000. Implementations of the clean laundry separating robot 5000 can be similar or identical to the separating and sorting robot 3000. The clean laundry separating robot 5000 is configured to separate a load of clean laundry into individual deformable laundry articles for introduction into a repositioning robot 6000. In implementations, the repositioning robot 6000 receives a single deformable laundry article and manipulates and repositions it for automated introduction into a folding robot 7000, which automatically folds the laundry article for introduction to a packing robot 8000. In implementations, the packing robot 8000 automatically and autonomously packs the clean load of laundry comprising the plurality of clean and folded deformable laundry articles in a shipping container for automated redistribution to the customer. In implementations, the shipping container is a reusable container, or box (e.g., a box with a removable lid for sealing contents within). In implementations, the shipping container is a disposable container. In implementations, the shipping container is a non-deformable container with an ingress protection rating that includes an intrusion protection rating of 5 or 6 and a moisture protection rating of any and all of 1 through 6 in accordance with the Ingress Protection Code, IEC standard 60529. In reusable implementations, the shipping container can be washable.

Implementations of the process line 100a of household laundry cleaning robots can comprise one or more of each of the robots depicted in FIG. 1. For example, as shown in FIG. 2, each autonomous process line 100b can include a bank 4002 of washing and drying robots 4000a-n. In other implementations, as shown in FIG. 3, the autonomous process line 100c includes a bank 4002 of washing and drying robots 4000a-n shared by two or more sets of automated intake robots 2000a-b and dirty laundry separating and sorting robots 3000a-b and two or more sets of clean laundry separating robots 5000a-b, repositioning robots 6000a-b,

folding robots **7000a-b**, and packing robots **8000a-b**. Additionally, two or more of the robots can be combined in a single module in alternate implementations. In implementations, one or more of the robots in the process line **100a-c** are configured to communicate over wired connections or wireless communication protocols. For example, in implementations, one or more robots in the process line **100a-c** can communicate with another one or more robots in the process line **100a-c** over a wired BUS, LAN, WLAN, 4G, 5G, LTE, Ethernet, BLUETOOTH, or other IEEE 801.11 standard.

Referring to FIG. 4, an example of a system **200** of operatively connected robots is shown. FIG. 4 depicts a schematic implementation of a portion of an autonomous robotic process line **100, 100a-c**. A dirty laundry separating and sorting robot **3000** is in operative communication with an automated intake robot **2000** configured to provide a plurality of dirty laundry items from a single customer (e.g., one household) to the dirty laundry separating and sorting robot **3000**. The dirty laundry separating and sorting robot **3000** is configured to provide intelligently sorted and batched loads of dirty deformable laundry articles to the washing and drying robot **4000** for effective and efficient washing and drying. The washing and drying robot **4000** is in operative communication with a clean laundry separating robot **5000** and outputs a load of clean laundry for separation by the clean laundry separating robot **5000**. Each robot **2000, 3000, 4000** includes a controller **3005, 3005, 4005** configured to operate the associated robot and the one or more controllers prompt intermediary wheel robots, conveyors, and/or carriers to transfer the one or more deformable articles **12** between sequential robots in the process line **100, 100a-c**.

For example, in implementations, the autonomous dirty laundry separating and sorting robot **3000** includes a controller **3005**. The controller **3005** includes a processor **3015** in communication with a memory **3010**, a network interface **3020**, and a sensor interface **3025**. The processor **3015** can be a single microprocessor, multiple microprocessors, a many-core processor, a microcontroller, and/or any other general purpose computing system that can be configured by software and/or firmware. In implementations, the memory **3010** contains any of a variety of software applications, data structures, files and/or databases. In one implementation, the controller **3005** includes dedicated hardware, such as single-board computers, application specific integrated circuits (ASICs), and field programmable gate arrays (FPGAs).

A network interface **3020** is configured to couple the controller **3005** to a network **230**. The network **230** may include both private networks, such as local area networks, and public networks, such as the Internet. It should be noted that, in some examples, the network **230** may include one or more intermediate devices involved in the routing of packets from one endpoint to another. In implementations, the network interface **3020** is coupled to the network **230** via a networking device, such as a bridge, router, or hub. In other implementations, the network **230** may involve only two endpoints that each have a network connection directly with the other. In implementations, the network interface **3020** supports a variety of standards and protocols, examples of which include USB (via, for example, a dongle to a computer), TCP/IP, Ethernet, Wireless Ethernet, BLUETOOTH, ZigBee, M-Bus, CAN-bus, IP, IPV6, UDP, DTN, HTTP, FTP, SNMP, CDMA, NMEA and GSM. To ensure data transfer is secure, in some examples, the controller **3005** can transmit data via the network interface **3020** using a variety of security measures including, for example, TLS, SSL or

VPN. In implementations, the network interface **3020** includes both a physical interface configured for wireless communication and a physical interface configured for wired communication. According to various embodiments, the network interface **3020** enables communication between the controller **3005** of the dirty laundry separating and sorting robot **3000** and at least one of the plurality of robots **2000, 4000, 5000, 6000, 7000, 8000, 9000** of the process line **100, 100a-c**.

Additionally or alternatively, the network interface **3020** is configured to facilitate the communication of information between the processor **3015** and one or more other devices or entities over the network **230**. For example, in implementations, the network interface **3020** is configured to communicate with a remote computing device such as a computing terminal **205**, database **235**, server **240**, smart-phone **245**, and server farm **250**. In implementations, the network interface **3020** can include communications circuitry for at least one of receiving data from a database **235** and transmitting data to a remote server **240, 250**. In some implementations, the network interface **3020** can communicate with a remote server over any of the wired protocols previously described, including a WI-FI communications link based on the IEEE 802.11 standard.

In some examples in accordance with FIG. 4, the network **230** may include one or more communication networks through which the various autonomous robots and computing devices illustrated in FIG. 4 may send, receive, and/or exchange data. In various implementations, the network **230** may include a cellular communication network and/or a computer network. In some examples, the network **230** includes and supports wireless network and/or wired connections. For instance, in these examples, the network **230** may support one or more networking standards such as GSM, CMDA, USB, BLUETOOTH®, CAN, ZigBee®, Wireless Ethernet, Ethernet, and TCP/IP, among others. In implementations, the network **230** can implement broadband cellular technology (e.g., 2.5 G, 2.75 G, 3 G, 4 G, 5 G cellular standards) and/or Long-Term Evolution (LTE) technology or GSM/EDGE and UMTS/HSPA technologies for high-speed wireless communication.

Although the controller **3005** is described herein in particular, one or more of the plurality of robots **2000, 4000, 5000, 6000, 7000, 8000, 9000** of the process line **100** includes similar components having similar functionality.

Turning to FIG. 5, a schematic of an implementation of an autonomous separating and sorting system **400** is shown. The system **400** includes one or more of the features and devices described with regard to the embodiments of FIGS. 1-4. In implementations, the separating and sorting system **400** comprises a plurality of interactive autonomous robotic devices. In implementations the system **400** comprises a separating and sorting device **3000** comprising at least three arms and a controller **3005**, an elevator **3350** for raising a box **3500** of dirty articles to a height above the separating and sorting robot **3000**, a box tipping assembly **3400** for receiving the box **3500** of dirty articles **12** from the elevator and overturning the bin into the separating and sorting robot **3000**, and a load constructor **3200** for collecting sorted and/or batched dirty laundry articles exiting the separating and sorting robot **3000**. In implementations, the controller **3005** is in wired or wireless operative communication with processors and drives of all of the foregoing. Each autonomous device of the implementation of the system **400** of FIG. 5 will subsequently be described with regard to implementations.

## 23

Turning now to FIGS. 6-11, an implementation of an autonomous sorting device **3000** (also alternatively referred to hereinafter as the “device,” “robotic device,” and “separating and sorting robot”) for separating individual dirty laundry articles of a plurality of deformable laundry articles and sorting the individual deformable laundry article into bins for washing. The plurality of deformable articles comprise one or more loads of dirty household laundry. Because the one or more loads of dirty household laundry can comprise two or more article types of at least one of different sizes, different shapes, different colors, and different fabrics, the autonomous sorting device **3000** is configured to separate each article from a pile, a bin, and/or a tangled clump of dirty laundry articles and place each separated article **12** in a specific group of articles with matching washing and drying requirements. As will be described subsequently with regard to implementations, the parameters for specific groupings can be at least one of preset, dynamically determined, and requested by a customer. The autonomous sorting device **3000** thereby autonomously separates and sorts an unsorted mass of dirty laundry into batches of dirty laundry articles for washing and drying. For example, the device **3000** can separate colored articles from white articles for separate batching, washing and drying, and the device **3000** can separate and batch towels for separate washing and drying. For example, the device **3000** can separate and batch delicate articles for washing and drying together or as individual articles, and the device **3000** can identify and batch one or more stained articles requiring individualized stain treatment.

In implementations, the device **3000** includes an enclosed channel **3100** comprising a plurality of sequential work volumes **3105a-d** and a stationary floor **3110** extending between an inlet end “I” and an outlet end “O” of the enclosed channel **3100**. In implementations, the stationary floor **3110** comprises a substantially level surface extending from the inlet end I to the outlet end O. Additionally or alternatively, the stationary floor **3110** comprises a substantially continuous surface extending throughout all of the plurality of sequential work volumes **3105a-d**. In implementations, the enclosed channel **3100** is raised above a ground floor and/or mezzanine platform. In implementations, the enclosed channel **3100** comprises the floor **3110**, a ceiling **3111**, and four walls **3112a-d**. (For illustrative purposes, the floor **3110**, ceiling **3111** and four walls **3112a-d** are shown as transparent in FIGS. 10-11.) As described later with regard to implementations of autonomously introducing a plurality of deformable laundry articles **12** into the enclosed channel **3100**, a portion **3110a** of the stationary floor **3110** within a first work volume **3105a** of the plurality of sequential work volumes **3105a-d** is configured to receive thereon the plurality of deformable articles **12a-n** adjacent the inlet end I. In implementations, the device **3000** includes a plurality of arms **3115a-c** disposed in series along the enclosed channel **3100**, each one of the plurality of arms **3115a-c** comprising an actuatable terminal gripper **3120a-d** configured to selectively grasp at least one of the plurality of deformable articles **12a-n** and at least one drive motor **3125a-c** configured to at least one of rotate, tilt, extend, and retract the terminal gripper **3120a-c**, each of the plurality of arms **3115a-d** associated with a corresponding one of the plurality of sequential work volumes **3105a-d**.

The device **3000** includes at least one selectively sealed inlet orifice **3130**, **3130a-b** and an outlet orifice **3135**. Additionally or alternatively, the outlet orifice **3135** is selectively sealed by an actuatable door or covering. Additionally or alternatively, the outlet orifice **3135** is selectively sealed

## 24

by an air curtain in operable communication with the controller **3005**. The at least one inlet orifice **3130**, **3130a-b** is disposed in at least one of a wall or ceiling of the enclosed channel **3100**, and the plurality of deformable articles **12a-n** are received into the enclosed channel **3100** through the inlet orifice **3130**, **3130a-b**. The outlet orifice **3135** is disposed adjacent the outlet end O of the enclosed channel **3100** in at least one of a wall **3112a-d** of the enclosed channel and the stationary floor **3110**. Each one of the plurality of deformable articles **12a-n** exits the enclosed channel **3100** through the outlet orifice **3135**. Selectively sealing the at least one inlet orifice **3130**, **3130a-b** and, in implementations, the outlet orifice **3135**, enables containment of loose personal items and other detritus and debris that might accompany an individual household’s laundry without contaminating other devices and systems in the process line **100**. Additionally, selectively sealing the inlet orifice **3130**, **3130a-b** and, in implementations, the outlet orifice **3135**, enables effective cleaning and disinfecting of the enclosed channel **3100**, as will be described subsequently with regard to implementations.

As shown in FIGS. 10-11, the device **3000** comprises at least one sensor **3140a-d** disposed at least one of on, adjacent to, and within each one of the plurality of sequential work volumes **3105a-d**. In implementations, the at least one sensor **3140a-d** can include one or more cameras disposed at least one of on, adjacent to, and within each of the sequential work volumes. In implementations, adjacent to includes the at least one sensor being disposed external to a transparent wall or window disposed in a wall **3112a-d**, floor **3110**, and/or ceiling **3111** of the enclosed channel **3100**. For example, in implementations, the at least one sensor **3140a-d** comprises one or more cameras adhered to or positioned adjacent plexiglass walls or windows with a field of view trained on the interior of the channel **3100**. In implementations, the at least one sensor is a camera, and the camera is calibrated to the floor **3110** of the enclosed channel and one or more of the plurality of arms **3115a-d**. The at least one sensor **3140a-d** is configured to detect at least one of the plurality of deformable articles **12a-n** disposed within an associated one of the plurality of sequential work volumes, and output a signal indicative of at least one of the presence and location of the at least one of the plurality of deformable articles **12a-n** relative to the terminal gripper **3120a-c** of the one of the plurality of sequential work volumes **3105a-d**. In implementations, at least one camera **3140d** is disposed adjacent the outlet end O and has a field of view encompassing the outlet orifice **3135** for detecting passage of an article **12** therethrough.

In implementations, the at least one sensor **3140a-d** is a single camera comprising a field of view encompassing the entire floor **3110** of the enclosed channel **3100**. In implementations, the at least one sensor **3140a-d** comprises two cameras comprising adjacent fields of view collectively encompassing the entire floor **3110** of the enclosed channel **3100**. In implementations, the at least one sensor **3140a-d** is three or more cameras comprising adjacent field of views collectively encompassing the entire floor **3110** of the enclosed channel **3100**.

The device **3000** comprises a controller, such as controller **3005**, that is in operable communication with the at least one drive motor **3125a-c**, an actuator **3174a-c** of each of the plurality of terminal grippers **3120**, and the at least one sensor **3140a-d** of each one of the plurality of sequential work volumes **3105a-d**. As will be described subsequently with regard to implementations, the controller **3005** is con-

figured to orchestrate movements of the plurality of arms **3115a-c** within the enclosed channel **3100** and actuation of the associated terminal grippers **3120a-c** to grasp, hoist, and move an initially grasped one or more of the plurality of deformable articles **12a-n** down the series of arms **3115a-b** such that a single article **12n** is grasped by an arm **3115c** closest to the exit orifice **3135**. The controller **3005** is configured to receive a signal from the at least one sensor **3140a-c** in an associated one of the plurality of sequential work volumes **3105a-c** indicative of at least one of the plurality of deformable articles **12a-n** being disposed within the associated one of the plurality of sequential work volumes **3105a-c**. The controller **3005** is configured to determine a location of the at least one of the plurality of deformable articles **12a-n** on the stationary floor **3110** relative to the associated arm **3115a-c**, instruct the at least one drive motor **3125a-c** to position the terminal gripper **3120a-c** of the associated arm **3115a-c** at the determined location to grasp the at least one of the plurality of deformable articles **12a-n**, and instruct an actuator **3174a-c** of the terminal gripper **3120a-c** of the associated arm **3115a-c** to close on and grasp the at least one of the plurality of deformable articles **12a-n**. The controller **3005** is configured to instruct the at least one drive motor **3125a-c** to raise the closed terminal gripper **3120a-c** of the associated arm **3115a-c** and the grasped at least one of the plurality of deformable articles **12a-n** to a hoist height above the stationary floor, and rotate toward the outlet end O into an adjacent work volume **3115a-d**. The controller **3005** is configured to instruct the actuator of the terminal gripper to open the gripper to release the at least one of the plurality of deformable articles **12a-n** in the adjacent work volume, and receive a signal from at least one sensor **3140a-d** in the adjacent work volume of the plurality of sequential work volumes **3105a-d**. The controller **3005** is configured to determine, based on the received signal, at least one of one or more of the plurality of deformable articles **12a-n** being present on the stationary floor **3110**, none of the plurality of deformable articles **12a-n** are present on the stationary floor **3110**, and one of the plurality of deformable laundry articles **12a-n** exited the enclosed channel through the outlet orifice **3135**.

In implementations, such as those of FIGS. 6-9, the plurality of sequential work volumes **3105a-d** comprises three or more work volumes, and each of the three or more arms are associated with one of the three or more work volumes. In implementations, the outlet orifice **3135** is disposed in a last work volume **3105d** of the plurality of sequential work volumes **3105a-d**, which is adjacent the outlet end O of the enclosed channel **3100**. In implementations, the outlet orifice **3135** is disposed in the stationary floor **3110** within or adjacent to a last of the plurality of sequential work volumes **3105a-c** and, in implementations, is disposed in a terminal work volume **3135d** that is shorter in length than the preceding work volumes **3105a-b**. In implementations, the number of work volumes comprising the plurality of sequential work volumes **3105a-d** is one greater than the number of the plurality of arms **3115a-c** and each of the plurality of arms **3115a-c** is associated with a work volume directly adjacent at least one other work volume associated with one of the plurality of arms **3115a-c**. For example, in FIGS. 6-11, each one of three arms **3115a-c** is associated with a corresponding one of three sequential work volumes **3105a-c** and a fourth work volume **3105d** with no associated arm follows the third work volume **3105c**. In implementations, an outlet-facing end of each of the three or more work volumes overlaps with an inlet-

facing end of an adjacent sequential one of the three or more work volumes such that each arm of the plurality of arms **3115a-c** is configured to extend into one or more adjacent work volumes of the plurality of sequential work volumes **3105a-c**.

If the controller **3005** determines one or more of the plurality of deformable articles **12a-n** is present on the stationary floor **3110** in the adjacent work volume into which the one or more articles was dropped, the controller **3005** is further configured to iteratively perform one or more grabs, rotations, and drops down the line of sequential arms **3115a-c** and work volumes **3105a-c**. In implementations, upon determining the presence of one or more of the plurality of deformable articles **12a-n**, the controller **3005** is configured to determine a location of the at least one of the plurality of deformable articles **12a-n** on the stationary floor **3110** relative to an arm associated with the adjacent work volume, and instruct the at least one drive motor **3125a-c** of the arm associated with the adjacent work volume to position the terminal gripper of the arm associated with the adjacent work volume at the determined location to grasp the at least one of the plurality of deformable articles **12a-n**.

As will be described subsequently with regard to schematic implementations, the controller **3005** is configured to instruct an actuator **3174a-c** of the terminal gripper **3120** of the arm **3115** associated with the adjacent work volume **3105** to close on the at least one of the plurality of deformable articles **12a-n**, and instruct the at least one drive **3125a-c** to raise the closed terminal gripper of the arm associated with the adjacent work volume and the grasped at least one of the plurality of deformable articles to a hoist height H1 above the stationary floor, and move the gripper **3120** (e.g., at least one of pan, tilt, and extend, e.g., rotate) toward the outlet end O into the next sequential adjacent work volume of the three or more work volumes **3115a-c**. The controller **3005** is configured to instruct the actuator of the terminal gripper to open the gripper to release the at least one of the plurality of deformable articles **12a-n** in the next sequential adjacent work volume down the line toward the outlet end O of the enclosed channel **3100**. As in the previous iteration, the controller **3005** is configured to receive a signal from at least one sensor **3140a-n** in the next sequential adjacent work volume of the plurality of sequential work volumes **3115a-c**, and determine, based on the received signal, at least one of one or more of the plurality of deformable articles **12a-n** being present on the stationary floor **3110**, none of the plurality of deformable articles **12a-n** are present on the stationary floor **3110**, and one of the plurality of deformable articles **12a-n** exited the enclosed channel **3100** through the outlet orifice **3135**.

Alternatively, in implementations, the rather than an engaged gripper releasing each article **12** on the floor **3110** of an adjacent work volume **3105** following a hoist, the gripper **3120** of an available arm **3115** in a receiving work volume **3105** can grip an edge of the article **12** (e.g., a lowest hanging point), hoist the gripped edge to the hoist height and the longest engaged gripper can release the article **12**.

In implementations, the controller **3005** is configured to stop iterating when each one of the plurality of deformable articles **12a-n** in a load of dirty articles exits the enclosed channel through the outlet orifice **3135** as a solitary deformable article and no deformable articles remain in the enclosed channel **3100**.

In implementations, as will be subsequently described with regard to an illustrative embodiment, the controller **3005** is further configured to instruct two or more of the plurality of arms **3115a-c** to operate simultaneously within



each respective one of the plurality of sequential work volumes **3105a-c**. In implementations, terminal grippers **3120a-c** of the two or more of the plurality of arms **3115a-c** operating simultaneously are configured to simultaneously grasp at least one of the plurality of deformable articles **12a-b**. For example, to determine an article is a large sized item, two or more arms of the plurality of arms **3115a-c** can simultaneously grasp the article and rotate apart to spread the article. The controller **3005** can be configured to estimate a size of the article **12** based on a distance separating the engaged terminal grippers **3120a-c** once tension is detected in the spread article. Tension can be detected, for example, by one or more sensors in communication the controller **3005** for detecting resistance to movement or by monitoring a motor current of the at least one drive motor **3125a-c** of each arm engaged with the article.

As previously described with regard to FIGS. **10-11**, the device **3000** comprises at least one sensor **3140a-d**, **3145a-c**, **3147a-c** disposed at least one of on, adjacent to, and within each one of the plurality of sequential work volumes **3105a-d**. In examples, the at least one sensor of each work volume of the plurality of work volumes **3105a-d** is configured to at least one of detect one of one or more features and capture one or more images of the at least one of the plurality of deformable articles **12a-n** disposed in at least one work volume **3105** of the enclosed channel **3100**. In implementations, the at least one sensor **3140a-d**, **3145a-c**, **3147a-c** comprises at least one of a 3-D camera, an IR sensor, a 2-D camera, LIDAR, LADAR, a sonar proximity sensor, an ultrasonic ranging sensor, a radar sensor (e.g., including Doppler radar and/or millimeter-wave radar), and a pair of stereo depth cameras. In implementations, at least one sensor outputs to the controller **3005** at least one of a depth map, RGB images, and IR images. In implementations the at least one sensor **3140a-c**, **3145a-c**, **3147a-c** comprises a REALSENSE camera configured to output at least one of a depth map, RGB images, and IR images. In implementations, the at least one sensor **3140a-d**, **3145a-c**, **3147a-c** can be configured to output 3-D image data to the controller **3005**. Additionally or alternatively, in implementations, the at least one sensor **3140a-d**, **3145a-c**, **3147a-c** can be configured to output one or more 2-D images to the controller **3005**. As previously described, in implementations, the at least one sensor **3140a-d**, **3145a-c**, **3147a-c** comprises a camera, and the camera is calibrated to the floor **3110** of the enclosed channel **3100** and has a field of view encompassing one or more of the plurality of arms **3115a-c**.

In implementations, the at least one sensor **3140a-d**, **3145a-c**, **3147a-c** is positioned at least one of on, adjacent to, and within an associated one of the plurality of work volumes **3105a-c** such that the at least one sensor **3140a-d**, **3145a-c**, **3147a-c** has a field of view encompassing the stationary floor **3110** within the associated one of the plurality of work volumes **3105a-d**. In implementations, the at least one sensor **3140a-d**, **3145a-c**, **3147a-c** comprises a field of view (FOV) encompassing the outer perimeter reachable by an associated one of the plurality of arms **3115a-c**. In implementations, as shown in FIGS. **10-13**, the at least one sensor **3140a-d**, **3145a-c**, **3147a-c** is disposed outside the enclosed channel **3100**, above each of the plurality of sequential work volumes **3105a-c**. As shown in FIG. **12** depicting a portion of the enclosed channel **3100** comprising a first work volume **3105a**, the at least one sensor **3140a** can be disposed adjacent a transparent window **3141a** in a ceiling **3111** of the enclosed channel **3100** and comprises a field of view encompassing the stationary floor **3110** within the associated work volume. Additionally or

alternatively, as shown by way of example in FIG. **12**, the at least one sensor can include at least one of at least one upwardly angled sensor **3145a** and at least one transverse sensor **3147a** disposed at least one of on, adjacent to, and within an associated work volume **3105a**. The at least one upwardly angled sensor **3145a** comprises a field of view encompassing the work volume above the floor **3110** and is configured to detect an article **12** suspended by an associated arm **3115a-c** above the floor **3110**. In implementations, as shown FIGS. **12** and **13**, the at least one upwardly angled sensor **3145a** and at least one transverse sensor **3147a** are disposed outside the enclosed channel **3100**, adjacent each of the plurality of sequential work volumes **3105a-c**. In implementations, the at least one upwardly angled sensor **3145a** and at least one transverse sensor **3147a** can be disposed respectively adjacent a transparent window **3146a** on an arm side of the enclosed channel and a transparent window **3148a** on a side wall opposite the arm wall. Additionally or alternatively, in implementations, one or more of the at least one transverse sensor **3147a** and at least one upwardly angled sensor **3145a** can be disposed respectively adjacent a transparent window on an arm side of the enclosed channel and a transparent window on a side wall opposite the arm wall. Although the one or more sensors **3140a**, **3145a**, **3147a** are described with regard to the first work volume **3105a**, in implementations, each work volume **3105a-d** of the enclosed channel **3100** can comprise one or more of any of the sensors herein described by way of example with reference the first work volume **3105a**.

As shown in the schematic end view of a working volume **3105a** in FIG. **13** and the simplified end view showing only the floor **3110** of the enclosed channel **3100** in FIG. **14**, in implementations of the device **3000**, the at least one sensor comprises at least one sensor **3140a** at the ceiling aimed substantially downward at the stationary floor **3110**, an upward angled sensor **3145a** and a transverse sensor **3147** such that the overlapping fields of view (FOVs)  $\phi 1$ - $\phi 3$  cover the entirety of the work volume. Such implementations are particularly advantageous for determining whether and where any one of the plurality of deformable articles **12a-n** remains in the enclosed channel **3100** prior to concluding the separating and sorting process on the plurality of deformable articles **12a-n** and determining the channel **3100** is dormant and ready to receive a subsequent load of dirty laundry into the enclosed channel for separating and sorting. Alternatively, in implementations, a single sensor of the one or more sensors **3140a**, **3145a**, **3147a** comprises a field of view configured to detect the entirety of one or more work volumes **3105a-c** of the enclosed channel **3100**.

In implementations, as shown in FIG. **14**, determining a location of the at least one of the plurality of deformable articles **12a-n** on the stationary floor further comprises determining one or more grip points **15a-15c** on the at least one of the plurality of deformable articles **12a-n** at which the gripper **3120a** will close on the article **12a**. In implementations, the one or more grip points **15a-15c** are disposed on a high point (e.g., grip point **15a**) of the at least one deformable article **12a** of the plurality of deformable articles **12a-n**. The high point can be a highest point of one or more highest points on the article **12a**, the one or more highest points being raised higher than other points on the article **12a** relative to the planar surface of the floor **3110** beneath the article **12**. Additionally or alternatively, in implementations, one or more grip points **15b-c** are disposed on an edge of the at least one of the plurality of deformable articles **12a-n** as determined by the controller **3005** based on signals received from the one or more sensors **3140**, **3145**, **3147**. In

29

implementations, as will be subsequently described with regard to embodiments, the controller **3005** is configured to receive or compute a mask of the article **12a** to determine the edges of the article **12** (e.g., a continuous outline traced in 2D around the outer periphery of the article **12a** on the floor **3110** of the channel **3100**) and the one or more grip points **12b-c** disposed on the edge.

As previously described with regard to in implementations, the at least one sensor **3140a-c** is a camera disposed at, on, or adjacent the ceiling **3111** and/or walls **3112a-d** of the enclosed channel **3100**. The camera is calibrated to the distance of the stationary floor **3110** and configured to detect a prominence of a deformable article **12** disposed on the floor **3110**. In implementations, as shown in FIGS. **10-11** and **14**, the device **3000** further comprises one or more light sources **3150a-c** in operable communication with the controller **3005**. The one or more light sources **3150a-c** can comprise at least one of adjustable brightness, intensity, and color. The one or more light sources **3150a-c** are configured to adjust lighting within the enclosed channel **3100** for improving perception by the at least one sensor comprising at least one of the at least one sensor **3140a-c** disposed at, on, or adjacent the ceiling, an upward angled sensor **3145a-c** disposed at, or adjacent on of the walls **3112a-d**, and a transverse sensor **3147a-c** disposed at, or adjacent on of the walls **3112a-d** as previously described with regard to implementations. In implementations, one or more of the one or more light sources **3150a-c** can be aimed directly or indirectly at the floor **3110** from above or aside the floor **3110**. In implementations, the one or more light sources **3150a-c** are disposed adjacent at least one of the ceiling **3111**, one or more walls **3112a-d**, and the floor **3110** at least one of within the channel **3100** and external to the channel **3100** and adjacent one or more transparent or diffusive light permitting windows, such as one or more plexiglass windows sealed within the ceiling, walls, and/or floor such that clothing, dirt and debris, loose items, and cleaning fluid do not escape the channel **3100**.

Turning now to FIGS. **15A-17B**, a series of partial views of the device **3000** are shown for exemplification. A floor **3110** of an enclosed channel is depicted along with a plurality of arms **3115a-c** as previously described and boundaries of associated work volumes **3105a-b** projected on the floor **3110**. As previously described, the controller **3005** is configured to orchestrate movements of the plurality of arms **3115a-c** within the enclosed channel **3100** and actuate the associated terminal grippers **3120a-c** to grasp, hoist, and release which actuating the at least one motor **3125a-c** of each arm **3115a-c** to pan, tilt and extend the arm.

In implementations, as shown in FIG. **15A**, the controller **3005** is configured to receive a signal from the at least one sensor (e.g., a camera **3140a**, **3145a**, **3147a**) disposed at or adjacent a first work volume **3105a**. The signal is indicative of the at least one sensor detecting at least one article **12a** of a plurality of deformable articles **12a-n** being disposed within the first work volumes **3105a**. Because the first work volume **3105a** is configured to receive a load of dirty laundry, the at least one article **12a** is, in most instances, a mass of a plurality of deformable articles **12a-n**, when “n” indicates the maximum number of separate articles in a load of laundry. The plurality of deformable articles **12a-n** can be, for example, a pile of non-uniform dirty laundry and the articles comprising the pile of dirty laundry can be overlapped, entangled, and otherwise stuck together or piled atop one another. The controller **3005** is configured to determine a location of the at least one of the plurality of deformable articles **12a-n** on the stationary floor **3110** relative to the

30

associated arm **3115a** (e.g., the first arm **3115a** of the plurality of arms **3115a-c**) of the first work volume **3105a**.

In implementations, the controller **3005** is configured to aim the gripper **3120a** of the first arm **3115a** at the center of the area on the floor **3110** occupied by the plurality of deformable articles **12a-n**. Additionally or alternatively, as described with regard to FIG. **14**, the controller **3005** is configured to aim the gripper **3120a** at one of one or more highest points **15a** of the plurality of deformable articles **12a-n**. Additionally or alternatively, the controller **3005** is configured to determine a mask (e.g., mask **3800** of FIG. **46**) an article **12** or the plurality of deformable articles **12a-n** and edge points as previously described with regard to implementations, and instruct the gripper to aim to engage an article **12** at one of the determined one or more edge points **15b-c**. In implementations, the controller **3005** is configured to instruct the gripper **3120** to aim to engage the article at one of the determined one or more edge points **15b-c** that is closest to the outlet end **O**. In implementations, the controller **3005** is configured to determine a mask **3800** of an article **12a** or a plurality of articles **12a-n** disposed on the floor **3110**, randomly select a point **15a** within the area of the mask **3800**, receive a depth signal from the one or more sensors (e.g., sensors **3140a-c**, **3145a-c**, **3147a-c**), and instruct a gripper **3120** to grab the article **12** at the depth sensed at the selected grip point **15a** even if that is not the highest point on the article **12**.

As shown in FIG. **15B**, the controller **3005** instructs at least one drive **3125a-c** to position the terminal gripper **3120a** of the first arm **3115a** at the determined location to grasp the at least one article **12a** of the plurality of deformable articles **12a-n** by at least one of rotating, panning, and tilting the arm **3115a** and the associated terminal gripper **3120a** to the target location. In implementations, the controller **3005** receives a signal from the one or more sensors **3140a-c**, **3145a-c**, **3147a-c**, determines a depth location of the target grip point **15**, and determines a target height to which the arm **3115** will move the gripper, the target height being short distance (e.g., 1 cm-3 cm) directly above the target grip point **15**. The arm **3115** then moves the gripper **3120** to the target height above the target grip point **15**, positioning the joint at the base of the spread gripper fingers **3107a-b** (FIGS. **39A-41A**) adjacent the article **12** so that the fingers of the gripper **3120** do not push the article **12** away and out of reach. In implementations, the controller **3005** is configured to thus position the gripper so that the fingers **3107a-b** of the gripper **3120** close on the target grip point **15** as the arm **3115** is lifting the article **12** off the floor **3110**.

With the gripper **3120** positioned at least one of on or directly above the location of the target grip point **15**, the controller **3005** instructs an actuator **3174a** of the terminal gripper **3120a** to close the gripper **3120a** on the at least one article **12a** of the plurality of deformable articles **12a-n**. Additionally or alternatively, in implementations, after selecting the target point **15**, the controller **3005** is configured to instruct the one or more drive motors **3125a-c** to transit the gripper **3120** to a target location above the determined grip point, then slowly move down at a fraction of the transit speed (e.g. one half, one third, one quarter) in arriving at the target location. The controller **3005** instructs the at least one drive motor **3125a-c** to press the gripper **3120** into the article **12** and then retract to a distance at or around 2 cm above the target location grip point while closing the fingers **3107a-b** of the gripper **3120** around the grip point of the article **12**. In this way, the gripper **3120** is able to grasp small articles successfully, articles such as baby socks and children’s gloves, for example, without

31

driving into them at full speed and potentially pushing them out of reach of the gripper fingers 3107a-b.

The controller 3005 is configured to instruct the at least one drive 3125a-c to raise the closed terminal gripper 3120a and the grasped at least one 12a of the plurality of deformable articles 12a-n to a hoist height H1 above the stationary floor 3110, leaving behind articles 12b-n in the received load, where "n" represents the maximum number of separable deformable articles in the received load of deformable laundry articles. As will subsequently be described with regard to implementations, the first gripper 3120a nearest the inlet end I can grasp more than one deformable article 12a-n from the pile of dirty laundry to hand off to the next arm 3115b in an adjacent work volume 3105b. As will be described in detail, the plurality of arms 3115a-c operate in sequence to grasp and release articles down the length of the channel 3100 such that by the third grasp by the third arm 3115c, the more than one initially grasped deformable articles are separated and a single article 12a is held aloft by the final arm 3115c adjacent the outlet O.

In implementations, the device 3000 can include one or more weight sensors disposed each of the plurality of arms 3115s-c, the one or more weight sensor being in operative communication with the controller 3005 and being configured to continuously detect a rate of change as each one of the plurality of deformable laundry articles is raised. The controller 3005 can then determine that one of the plurality of deformable laundry articles is raised to a hoist height when the one or more weight sensors detect an unchanging rate of change of measured weight because the article is lifted completely off the floor 3110 and is no longer supported by the floor 3110, therefore imparting a maximum downward force on the engaged arm 3115a. Additionally or alternatively, the at least one sensor of at least one of a downward angled sensor 3140a-c, a transversely angled sensor 3145a-c (e.g., having a field of view aimed across the channel from one side wall 3112c-d to another), and an upwardly angled sensor 3147a-c, can detect a position of the terminal gripper above the floor 3110 and output a signal to the controller indicative of this height position. Upon receiving the signal, the controller 3005 can then determine that the gripper 3120a is at a hoist height conducive for moving the article into an adjacent work volume 3105b for dropping there. Additionally or alternatively, one or more encoders (e.g., motor encoders 3157a-c, a'-c', a"-c", FIG. 5) outputs a signal to the controller 3005, and the controller 3005 determines a hoist height of the gripper 3120 engaged with the article 12 by dynamically processing (e.g., processing the one or more encoders signals as the one or more motors 3125a-c are moving the arm 3115) the signal with a calibrated kinematics routine. In implementations, the hoist height is pre-set, and the controller 3005 uses calibrated kinematics to determine when the gripper reaches the pre-set hoist height. Additionally or alternatively, in implementations the at least one sensor 3140a-c, 3145a-c, 3147 a-c is configured to detect a gap between the hoisted article and the floor 3110, and output a signal to the controller 3005 for dynamic processing to determine when an article 12 is hoisted to a height at which a detectable gap (e.g., a region from which the detectable article is no longer sensed across the width of the channel 3100) appears between the hoisted article and the floor 3110. In implementations, the at least one sensor 3147a-c comprises a transverse field of view for dynamically detecting the appearance of a gap beneath the article 12 and above the floor 3110.

As shown in FIG. 16A, the controller 3005 instructs the at least one drive motor 3125a-c to at least pan the arm

32

3115a, gripper 3120a, and hoisted article 12a in the direction D toward the outlet end O of the channel 3100 and into an adjacent work volume 3105b. Additional, the controller 3005 can tilt and extend the first arm 3115a such that the terminal gripper 3120a is positioned within the second work volume 3105b accessible by the second arm 3115b. As shown in FIG. 16B, the controller 3005 is configured to instruct the actuator 3174b of the terminal gripper 3120a to open and release the article 12a in the adjacent work volume 3105b. The controller 3005 receives a signal from at least one sensor (of at least one of a downward angled sensor 3140b, a transversely angled sensor 3145b, and an upwardly angled sensor 3147b) in the adjacent work volume 3105b and determines, based on the received signal, that the at least one deformable article 12a is present on the stationary floor 3110. Similar to the first arm 3115a, the second arm 3115b is configured to grasp the deformable article 12a from the stationary floor 3110 within the associated second work volume 3105b, rotate in the direction D toward the outlet end O of the channel 3100 and release the deformable article in the third work volume 3105c, as shown in FIG. 17A.

In implementations, the controller 3005 is configured to determine whether a terminal gripper 3120a-c missed grasping the article prior to hoisting to the hoist height H1. For example, after the first arm 3115a has hoisted, rotated, and opened the terminal gripper 3120a in a second work volume 3105b, the controller 3005 of the device 3000 can determine that the article is not present on the floor 3110 within the second work volume based on one or more sensor signals from the at least one sensor 3140a-c. The controller 3005 can then at least one of query and receive a signal from the at least one sensor 3140a in the first work volume 3105a and determine a location of the deformable article on the floor 3110 within the first work volume 3105a. The controller 3005 can then repeat the instructions of positioning the terminal gripper 3120a of the first arm 3115a at the determined location to grasp the at least one article 12a of the plurality of deformable articles 12a-n, grasping, raising, rotating, and releasing the article in the second work volume 3105b.

In implementations, as will be described subsequently with regard to the method of operation, the controller 3005 can execute a miss recovery routine. In implementations, the miss recovery routine comprises moving the target grip point 15 inward from an edge by a distance in a range of between about 10-20 mm (e.g., 10 mm, 11 mm, 12 mm, 13 mm, 14 mm, 15 mm, 16 mm, 17 mm, 18 mm, 19 mm, 20 mm) in a direction toward the inlet end I with each subsequent attempt after a missed grab. Additionally or alternatively, in implementations, the controller 3005 can determine a center of mass of the mask of the at least one article 12a on the floor 3110 and move the targeted grip point 15 toward the center of mass with each subsequent attempt after a missed grab. Alternatively, in implementations, the controller 3005 is configured to move the target grip point 15 to some other location within the area of the garment mask (e.g., mask 3800).

In implementations, the controller 3005 selects the alternate grip point locations randomly, or by iterating attempted grasps at alternate locations in a deterministic manner. This ensures that the gripper 3120 will find a graspable portion of the article 12, accounting for any spacing between extensions and the core of a garment, such as between sleeves and the torso portions of a shirt, which may place a center of mass in an open location not occupied by the article 12. Additionally or alternatively, in implementations, the controller 3005 is configured to create a bounding box 3805

around the mask **3800** of the article **12** as shown in FIG. **46**, the bounding box comprising a length **LB** and a width **WB** that places the mask **3800** inside the bounding box **3805**. The controller **3005** is configured to choose a random point as the target grip point **15** based on the length **LB** and width **WB** of the bounding box, determine whether the grip point **15** is within the mask (e.g., grip point **15b**) and not just within the bounding box (e.g., **15a**), and instruct a gripper **3120** to grasp the grip point **15b** within the mask area corresponding to the location of the article **12**. If the grip point was not within the mask **3800**, the controller **3005** randomly selects a new target grip point with the bounding box **3805** and iteratively continues randomly selecting target grip points until a target point is within both the bounding box **3805** and the mask **3800**. The randomness of determining a grip point **15** within the bounding box **3805** accounts for the difference in size between an end effector in software path planning (e.g., a single point) and the volume of the gripper **3120**, which is a 3D element and not a single point, and results in successful grabs of the article **12** regardless of article size. This enables a gripper **3120** to grab very small items such as baby socks, for example. By comparison, targeting a center of mass could result in the joint at the base of the fingers of the gripper **3120** touching the floor **3110** of the channel **3100** and not reaching the article, even though the center of the gripper **3120** was directly above the given target point, such as an edge point of the small article or a point moved inward from an edge point toward a center of mass.

Additionally or alternatively, in implementations, after selecting the target grip point within the bounding box, the controller **3005** is configured to instruct the one or more drive motors **3125a-c** to transit the gripper **3120** to a target location above the determined grip point, then slowly move down at a fraction of the transit speed in arriving at the target location. The controller **3005** instructs the at least one drive motor **3125a-c** to press the gripper **3120** into the article and then retract to a distance at or around 2 cm while closing the fingers **3107a-b** of the gripper **3120** around the grip point of the article. In this way, the gripper **3120** is able to grasp small articles successfully, articles such as baby socks and children's gloves, for example, without driving into them and potentially pushing them out of reach.

Each of the subsequent arms in the plurality of sequential arms **3115a-c** similarly performs a grasp, rotation, and drop down the line of sequential arms **3115a-c** and work volumes **3105a-c** from the inlet end **I** to the outlet end **O** of the channel **3100**. By performing sequential grasps, rotations, and drops the device **3000** increases the likelihood that each subsequent grasp will result in the terminal gripper **3120** of an arm **3115** retaining only a single article **12** in the final work volume **3105d** for dropping through the outlet orifice **3135**. By separating the load of the plurality of deformable articles **12a-n** into single articles, the device **3000** is able to sort each one of the plurality of deformable articles **12a-n** into a receiving bin **3202** configured to receive a single load of laundry having one or more common characteristics for improved washing and drying. Each article of the plurality of deformable articles **12a-n** can be independently detected by the at least one sensor (at least one of a downward angled sensor **3140a-c**, a transversely angled sensor **3145a-c**, and an upwardly angled sensor **3147a-c**), and the controller **3005** can determine one or more characteristics for batching the article into an associated bin **3202a-n**. As shown in FIG. **17B**, a single article **12a** of the plurality of deformable articles **12a-n** exits the channel **3100** at the outlet orifice **3135** to be received by a bin **3202** therebeneath.

Also as shown in FIG. **17B**, one or more arms of the plurality of arms **3115a-c** can operate simultaneously. For example, a third arm **3115c** can drop an article **12a** through the outlet orifice **3135** into a bin **3202** while a first arm **3115a** is rotating into the second work volume **3105b** with a hoisted one or more articles **12b-c** in its terminal gripper **3120a**, leaving behind the remaining plurality of deformable articles **12d-n** on the floor **3110** at a load intake position. The first arm **3115b** will drop the articles **12b-c** from its terminal gripper **3120a** onto the floor **3110** in the second work volume **3105b** and the terminal gripper **3120b** of the second arm **3115b** is likely to grasp only one of the two deformable articles **12b-c** dropped. Additionally or alternatively, in implementations, the controller **3005** is further configured to drive the at least one drive motor **3125a-c** of an arm **3115** of the plurality of arms **3115a-c** in at least one of alternating side-to-side and alternating up and down motions to shake a grasped deformable article **12** of the plurality of deformable articles at the hoist height **H1**. By shaking the terminal gripper **3120** at the hoist height, the arm **3115** can free any articles that may be stuck together, e.g., statically attracted or entangled. This shaking and/or snapping motion will separate two articles hoisted together when only a single article **12** is grasped. This helps prevent two articles **12** from being delivered to a next work volume **3105b-c** and therefore helps ensure that only a single article **12** is grasped by the gripper **3120c** of the final arm **3115c** in the sequentially placed plurality of arms **3115a-c**.

In implementations, as shown in FIG. **18**, the controller **3005** is further configured to determine whether a work volume is clear of any articles before an arm drops another article into that work volume. For example, an article **12b** can remain in the third work volume **3105c** while a second arm **3115b** waits for the third arm **3115c** to finish cleaning the third work volume **3105c** before releasing another article **12c** into the third work volume **3105c**. This prevents piling up more than one article in the third work volume **3105c** and further ensures that only a single, separated article will be released through the outlet orifice **3135**. Table 1 describes an implementation of a decision matrix executed by the controller **3005** based on sensor input for determining whether a work volume **3105**, **3105a-c** is clear of any articles **12**, **12a-n** before dropping another article into that work volume:

TABLE 1

Population count at and in contact with gripper above floor	Floor mask	Work volume floor available to receive new article?	Meaning
Article detected	Empty	Yes	Grab successful
Article detected	Article detected	No	Maybe multiple articles grabbed, maybe large article grabbed
Empty	Empty	Yes	Grab successful, small article
Empty	Article detected	No	Missed grab/dropped article, or successful small article grab but multiple articles on floor 3110

In this implementation, after an arm performs an article **12** hoist, the controller **3005** will evaluate a population count of an output sensor signal (e.g., one or more sensors **3140a-c**, **3145a-c**, **3147a-c**) to determine whether an article is

detected in an area under the engaged arm **3115**. In implementations, the population count comprises the number of points in a point cloud, and the points comprise at least one of points that have been voxelized and points that have not been voxelized. Alternatively, in implementations, determining a population count indicative of a successful hoist comprises the controller **3005** identifying correlated points between 3D points in a depth map with RGB pixels in an RGB image of the hoisted article based on the output signal of one or more sensors (e.g., one or more sensors **3140a-c**, **3145a-c**, **3147a-c**). This implementation of determining population count can also be used by the controller **3005** for classifying an article at the last hoist above the outlet orifice **3135** before dropping the article into a bin based on at least one of a detected article size and color.

If the population count is detected as large (e.g., at or above a threshold value indicative of an article **12** being detected), the controller **3005** determines that the arm **3115** and gripper **3120** grabbed and hoisted at least one article **12**. If the population count is below a threshold value, the controller **3005** determines that the grab missed grasping an article, in which case the article is still on the floor **3110**, or the article wasn't missed but is smaller than a threshold population count, e.g., a sock. The controller **3005** determines whether an article is on the floor by evaluation the mask **3800**. If the mask processing indicates an empty floor, the controller **3005** determines the grab was successful and the article **12** in the gripper **3120** is small, therefore the floor beneath that arm is available for receiving a new article. If the controller **3005** analyzes the mask and determines the floor is not empty (e.g., an article **12** is detected on the floor **3110**), the controller **3005** determines the floor **3110** is not available for receiving another article. In this instance when an article is detected in the gripper and on the floor **3110**, either more than one article **12a-n** had been deposited on the floor **3110** in the work volume **3105** and one article was hoisted and another left behind on the floor **3110**, or the article in the hoisted gripper is large and extends down onto the floor **3110**.

If the population count is below a threshold value and the floor mask does not indicate an article being present on the floor **3110**, the floor **3110** is available to receive an article. This condition can indicate that the grab was successful, and the item hoisted is small (e.g., below a population count threshold). If the population count is below a threshold value and the floor mask indicates an article being present on the floor **3110**, the work volume is not available for receiving another article. This condition indicates either a missed or dropped article or that a small item was successfully grabbed but another article remains on the floor **3110**.

Additionally or alternatively to the above described conditions, in implementations, the controller **3005** is configured to account for shadows. For example, if an article is supposedly detected on the floor **3110** of the work volume **3105a** of a hoisted arm **3115a**, but the arm **3115b** corresponding to the next sequential work volume **3105b** is stowed, the controller **3005** determines the detected article is a shadow of the hoisted article **12** the engaged arm **3115** is waiting to move to the adjacent work volume **3105b**. The controller **3005** can assume this is a shadow and not an article because the arm **3115** for the adjacent work volume **3105b** would have tried to pick up the article **12** and would be in a hoisted position.

In implementations, the controller **3005** is configured to stop iterating the sequential grasps, hoists, rotations, and drops when each one of the plurality of deformable articles **12a-n** exits the enclosed channel **3100** through the outlet

orifice **3135** as a solitary deformable article and no deformable articles remain in the enclosed channel **3100** as detected by the one or more sensors (e.g., at least one of one or more downward angled sensors **3140a-c**, one or more transversely angled sensors **3145a-c**, and one or more upwardly angled sensors **3147a-c**). As will be subsequently described, the controller **3005** is configured to determine that the enclosed channel **3100** is clear of any deformable articles before accepting a new load of dirty laundry (e.g., a new pile of deformable articles **12a'-n'**) onto the stationary floor **3110** adjacent the intake end I.

Although the above implementations describe each of the plurality of arms **3115a-c** rotating a grasped article **12** into an adjacent work volume and the associated terminal gripper **3120a-c** releasing the article onto the floor **3110** in the adjacent work volume, additionally or alternatively, in implementations, one or more of the terminal grippers **3120a-c** of the plurality of arms **3115a-c** can simultaneously grasp at least one article **12a** of the plurality of deformable articles **12a-n** at a hoist height H1 without releasing the article onto the floor **3110** so that the article **12a** is spread out. For example, as shown in FIGS. 19-21, the controller **3005** can determine one or more grip points **15a-f** on a deformable article **12a** hoisted by a second arm **3115b**. In implementations, the one or more grip points **15a** are disposed on an edge **16** of the deformable article **12a**. The controller **3005** can instruct a terminal gripper **3120c** of a third arm **3115c** in a work volume **3105c** adjacent the second work volume **3105b** to grip one of the one or more grip points **15a-f**. For example, the terminal gripper **3120c** of the third arm **3115c** can grip the lowest grip point **15d** on the article **12** as shown in FIG. 19. As shown in FIG. 20, the third arm **3115c** can then raise the grasped grip point **15d** of the article **12a** to the hoist height H1 while the terminal gripper **3120b** of the second arm **3115b** is still engaged with the article **12a** at the hoist height H1.

As shown in FIG. 21, one or more of the engaged second arm **3115b** and engaged third arm **3115c** can rotate away from the other to spread the article **12a** to an uncrumpled state, stopping for example when a resistance sensor in communication with the controller **3005** detects resistance indicative of the article **12a** being spread. The second terminal gripper **3120b** can then release the article **12a** leaving only the third gripper **3120c** holding the article **12a** at the hoist height H1. In this way, the plurality of grippers **3115a-c** continually pass the article **12** between mid-air grasps and by the final grasp, the article is a single article ready for exiting and sorting into a collection bin **3202** for washing. Additionally, in implementations, the controller **3005** can determine whether an article is a large sized item while two or more arms of the plurality of arms **3115a-c** simultaneously grasp the article and rotate apart to spread the article to at least a threshold length. The controller **3005** can be configured to estimate a size of the article **12a** based on a distance W separating the engaged terminal grippers **3120a-c** once tension is detected in the spread article **12a**. Tension can be detected, for example, by one or more sensors in communication the controller **3005** for detecting resistance to movement or by monitoring a motor current of the at least one drive motor **3125a-c** of each arm engaged with the article **12a**. The controller **3005** can access a memory **3010**, **210**, **235**, **240**, **250** in wired or wireless communication with the controller **3005**, for example via a communication network **230**, and cross reference the determined distance W with a database of article size classifications. The determination of a size classification can inform

which collection bin **3002** will receive the article **12a**, as will be described subsequently with regard to implementations.

Although FIGS. **14-22** show the plurality of arms **3115a-c** and floor **3110** of the channel **3100** absent the remaining enclosure walls **3112a-d** for exemplary purposes, in implementations, the enclosed channel **3100** is fully enclosed on all sides including at the inlet end **I** and outlet end **O**. Additionally, in implementations, as shown in FIGS. **6-7**, a lower portion **3113** of the channel side wall along the arms (e.g., arm wall **3112c** of FIG. **6**) can be angled inward toward the lower edge meeting the floor **3110** such that any of the plurality of deformable articles **12a-n** falling too close to the arm wall **3112c** during a drop will slide down under the force of gravity onto the floor **3110**, within reach of one or more of the plurality of arms **3115a-c**. Also as will be subsequently described in further detail with regard to implementations, the inlet orifice **3130a-b** and outlet orifice **3135** each comprise an actuated covering for selectively exposing and sealing each of the orifices, the controller **3005** being in operative communication with the actuator of each covering for sealing and uncovering the openings of the enclosed channel **3100** only when required to receive a load of deformable articles **12a-n** through the inlet orifice **3130a-b** into the channel **3100** and to allow a separated one of the deformable articles **12** to exit the channel **3100** through the exit orifice **3135**. By selectively sealing and uncovering the openings **3140a-b**, **3135**, the device **3000** contains the dirty load of deformable articles **12a-n** and any loose items (e.g., buttons, hair ties, pocket change, pens) dirt, debris, and other biological matter that may be on the deformable articles **12a-n**. This prevents the loss of personal items and the spread of dirt, debris, and potentially harmful matter from spreading throughout the process line **100**, particularly to clean loads of deformable articles being processed by other robots of the process line **100**. The channel **3100** can be autonomously sealed for autonomous cleaning and sanitization between loads of laundry and any loose articles can be autonomously collected for return to the customer in one or more customer containers or boxes.

Turning to FIGS. **23-24C**, in implementations, the inlet orifice **3130a** is disposed in a ceiling **3111** of the enclosed channel, adjacent the inlet end **I** such that a plurality of deformable articles **12a-n** received therethrough lands upon the floor **3110** of the channel adjacent a first arm of a plurality of arms **3115a-c** disposed sequentially along the length of the channel **3100**. The inlet orifice **3130a** is selectively sealed by a slidable door **3131** configured to be drawn away from the inlet orifice **3130a** when a load of deformable articles is ready for placement into the enclosed channel **3100**. In implementations, the door **3131** comprises one or more pair of rollers **3305a-b**, **3307a-b**, **3308a-b** configured to slide along a pair of rails **3310a-b** disposed therebetween such that the door **3131** moves up and back at a slight incline in the direction of arrow **S**. In implementations, the rollers **3305a-b**, **3307a-b**, **3308a-b** are spring loaded bearing rollers, and the pair of rails **3310a-b** are mounted astride the inlet orifice **3130a**. For example, in implementations, the door **3131** can raise up in a range of about 10-15 mm. In implementations, the door **3131** is mounted on one end to a spring loaded hinge **3315** that pulls the door **3131** up an inclined pair of rails **3310a-b** having a total rise of about 12 mm. Implementations of the door **3131** being a sliding door provides the benefits of a fast opening and closure to minimize the time the inlet orifice **3130a** is exposed. This prevents exposing other robots in the process line **100**, **100a-c** to potential dirt, debris, biohazardous

substances, and other contaminants and detritus that might escape from a sealed box of one or more dirty articles **12**, **12a-n**.

In implementations, the sliding trap door **3131** is actuated by a drive motor **3320** in operable communication with the controller **3005** for selectively sealing and exposing the inlet orifice **3130a** on demand. The drive motor **3320** can be configured to rotate a movable track **3325** to which the spring loaded hinge **3315** is attached. In implementations, the drive motor **3320** can be a low profile linear drive that enables the trapdoor assembly **3300** to have a low profile atop the enclosed channel **3100**. As will be subsequently described, the low profile enables a box tipping assembly **3400** to be mounted in close proximity with the inlet orifice **3130a** thereby minimizing or eliminating exposure of the box contents (e.g., one or more dirty articles **12**, **12a-n**) to the exterior and surrounding environment external to the enclosed channel **3100**. This prevents the load of one or more deformable articles **12**, **12a-n** therein and any dirt, detritus, debris, and/or biological matter from falling outside the enclosed channel **3100**. As will be described subsequently with regard to implementations, the box tipping assembly is designed to avoid contamination of the process line **100** at large and the exterior of the enclosed channel **3100** in particular by dirty laundry (e.g., one or more dirty articles **12**, **12a-n**). Only the cleanable interior surfaces of the enclosed channel **3100** are touched by dirty laundry released from a customer box.

As shown in FIGS. **25-27**, upon alignment of a sealed box **3500** containing the plurality deformable articles above the inlet orifice **3130a**, the controller **3005** actuates the inlet door **3131** to reveal the inlet orifice **3130a** before emptying the contents of the aligned box **3500** into the enclosed channel **3100**. In implementations, a box **3500** containing a plurality of dirty deformable articles **12a-n** from a single customer (e.g., household) is autonomously queued to a first position **A** adjacent the inlet orifice **3130a**, for example on a conveyor and/or flow rack **3405**. When the enclosed channel **3100** is ready to being a separation and sorting processing, the controller **3005** instructs a pair of rotatable clamps **3410a-b** to engage the box **3500**. The box **3500** then moves along a pair of rails **3415a-b** in a direction from the first position **A** to the second position **B** (as indicated by arrow **T**) directly above the inlet orifice **3130**. In implementations, the controller **3005** is configured to simultaneously instruct a drive to advance the box **3500** to the second position **B** while opening the door **3131** to expose the orifice **3130a**. Alternatively, the controller **3005** instructs a conveyor drive **3445** (FIG. **5**) to advance the box **3500** to the second position **B** and instructs the drive motor **3320** of the trap door **3131** to open the door **3131** once the box **3500** is positioned above the door **3131**. In implementations, as shown in FIGS. **25-27**, the box tipping assembly **3400** comprises a cam follower and bidirectional gear engagement assembly **3420** configured to rotate the box **3500** to an inverted position for dropping the plurality of deformable articles onto the stationary floor **3110** of the enclosed channel **3100**. In implementations, the gear engages a rack for rotating the box **3500** such that a lid **3505** flips open into the orifice **3130a** and contents fall into the enclosed channel **3100**. In implementations, the lid **3505** is a hinged lid configured to open into the inlet orifice **3130a** upon rotation of the box **3500** to an inverted position. In implementations, the box **3500** is rotated with the lid **3505** hinged at the leading edge of rotation such that the lid **3505** blocks any deformable articles from falling anywhere other than into the inlet orifice **3130a**.

Turning to the system schematic of FIG. 5, the box tipping assembly 3400 comprises a processor 4705 in wired or wireless communication with the controller 4005 via a network interface 4735. The box tipping assembly 3400 comprises a driven conveyor 3405 driven by a conveyor drive 3345 in operable communication with a reversible conveyor motor (not shown). The driven conveyor 3405 is configured to receive a full box 3500 into the box tipping assembly 3400 and eject the righted box 3500 once emptied. In implementations, the driven conveyor 3405 further comprises an incremental shaft encoder 3455 on the conveyor motor configured to rotate the driven conveyor 3405 by a measurable amount to move a box 3500 into a clamping position, position B. Additionally or alternatively, the conveyor 3405 comprises at least one position sensor 3450 configured to detect a position of a box 3500 within the box tipping assembly 3400 and transmit a signal to the processor 3430 of the box tipping assembly 3400 to actuate the pair of rotatable clamps 3410a-b to retain the box 3500 for tipping. In implementations, the position sensor 3450 comprises at least one of one or more non-contacting electromagnetic switches (e.g., Hall effect sensors), one or more mechanical limit switches, one or more photoelectric proximity switches (e.g., break beams), one or more inductive sensors, and one or more time of flight distance sensors configured to detect the presence of the position of the clamped box 3500 along the pair of rails 3415a-b and output a signal to the conveyor drive 3445 to stop moving the conveyor 3405. The box tipping assembly 3400 further comprises a tipper drive 3440 in operable communication with a tipper motor configured to rotate at least one of the pair of rotatable clamps 3410a-b to invert a box 3500 clamped therein. In implementations an incremental shaft encoder is disposed on the drive motor shaft of the tipper motor for detecting a rotational position of the pair of rotatable clamps 3410a-b. Additionally, in implementations, the box tipping assembly 3400 comprises one or more limit switches configured to detect at least one of the pair of rotatable clamps 3410a-b being upturned and the pair of rotatable clamps 3410a-b being inverted.

Additionally, in implementations, as shown in FIG. 28 an elevator 3350 can raise a closed and/or sealed box 3500 to a conveyor and/or flow rack 3405 of the box tipping assembly 3400 and transfer the box 3500 to the box tipping assembly 3400 for emptying into the enclosed channel 3100. As shown in FIGS. 5 and 28, in implementations, the elevator 3350 is disposed adjacent the enclosed channel 3100 and comprises one or more load sensors 3359, such as one or more undermounted loadcells, for detecting a box 3500 received thereon for elevating to the inlet orifice 3130a. In implementations, the elevator 3350 comprises a driven roller conveyor 3380 for receiving the box 3500 thereon from the separating and sorting robot 3000. The roller conveyor 3380 is movably attached to one or more vertical risers 3390a-b and driven up and down the vertical risers by a drive motor 3385 and puller system 3392 that includes a counterweight 3394.

As shown in the system schematic of FIG. 5, in implementations, the elevator 3350 comprises a processor 3355 in wired or wireless communication with the controller 4005 via a network interface 3370. The elevator 3350 comprises an elevator drive 4415 in operable communication with a pulley system drive motor 4465 and a conveyor drive 3365 in operable communication with a reversible conveyor motor 3385 configured to receive a full box 3500 for elevating and an emptied box 3500 for lowering. In implementations, the elevator 3350 further comprises a load sensor 3359 for detecting the presence of a box 3500 on the

conveyor 3380 and a position sensor configured to detect alignment of the conveyor 3380 with the conveyor and/or flow rack 3405 of the box tipping assembly 3400. Additionally or alternatively, the conveyor 3380 comprises at least one position sensor 3375 configured to detect a position of a box 3500 on the conveyor 3380 and transmit a signal to the processor 3355 of the elevator 3350 to actuate the drive motor 3385 to raise the box 3500 for transferring to the box tipping assembly 3400. In implementations, the position sensor 3375 comprises at least one of one or more non-contacting electromagnetic switches (e.g., Hall effect sensors), one or more mechanical limit switches, one or more photoelectric proximity switches (e.g., break beams), one or more inductive sensors, and one or more time of flight distance sensors configured to detect the presence of the position of the clamped box 3500 along the conveyor 3380 as the box 3500 is being received thereon and output a signal to the conveyor drive 3367 to stop moving the conveyor 3380.

Although the inlet orifice 3130a is describe as a selectively exposed orifice in the ceiling 3111 of the enclosed channel 3100 configured to receive a plurality of deformable articles from a box 3500 disposed above the orifice 3130a, other intake assemblies and methods are contemplated. As shown in FIGS. 29A-E, alternate methods of introducing a plurality of deformable articles 12a-n into the enclosed channel 3100 comprises sucking the close in through a flexible tube 3425 in communication with a vacuum 3430 (FIG. 29A), and inserting the box 3500 into the enclosed channel 3100 through a side opening 3130b (see FIG. 7) and pulling the deformable articles from the box 3500. For example, FIG. 28B shows a box 3500 inserted into the enclosed channel 3100 and opened to a lay-flat stay, exposing the one or more deformable articles 12a-n within the channel 3100 only once the inlet orifice is sealed, thereby containing all dirt and other potential contaminants within the washable channel 3100. In implementations, as shown in FIG. 29C, instead of having side walls the unfold to lay flat, a box 3500 comprises a removable or hinged lid and a gripper 3435 of an extendable arm is lowered into the box to remove one or more deformable articles therein once the box is received within the enclosed channel 3100. In implementations, as depicted in FIG. 29D, a sliding drawer or extendable conveyor tongue can deliver a box 3500 through a side orifice 3130a into the channel 3100. In implementations, as shown in FIG. 29E, a wall in which the orifice 3130a is disposed comprises an angled base for slidably receiving a box 3500 thereon in a tipped orientation for easy accessibility by an arm 3115a in the first work volume of the enclosed channel 3100.

In implementations as shown in FIGS. 30A-C and 31, the box tipping assembly 3400' comprises a framed tumbler 3467 positioned above an inlet orifice 3130b in the ceiling of the channel 3100. After clamping the box 3500 within the tumbler, a drive motor 3468 of the tumbler 3467 can rotate the clamped box 3500 on command from the controller 3005 to invert the box 3500 and dump the one or more deformable articles 12a-n through the frame 3465 and into the inlet orifice 3130a of the channel 3100. As described previously with regard to implementations, the box 3500 can be sealed with a selectively removable lid, such as a hinged lid (not shown) that opens under gravitational force as the box 3500 is inverted. In implementations, the box tipping assembly 3400' comprises a frame 3465 and suspension elements 3470a-d, 3470a'-d' disposed thereon configured to rotatably engage a tumbler 3467 configured to receive a box 3500 containing one or more deformable articles 12a-n. In imple-



mentations, the device **3000** comprises an autonomous conveyor (not shown) configured to transit the box **3500** from a rack or storage area to at least one of the box tipping assembly **3400'** and, as shown in FIG. 28, an elevator **3350** configured to receive the box **3500** and raise the box **3500** to a height of the box tipping assembly **3400'** for conveyance into the tumbler **3467**.

As shown in the exploded view of FIG. 32, in implementations, the tumbler **3467** further comprises a conveyor **3475** on which the box **3500** slides into the tumbler **3467** to be held by one or more selectively actuated clamps **3477**. In implementations the one or more selectively actuated clamps **3477** comprise a pneumatically operated clamp in operable communication with the controller **3005**. In implementations, the conveyor **3475** comprises a plurality of driven rollers **3476**. As shown in sequential depiction in FIGS. 30A-C, with the box **3500** clamped into the tumbler **3467**, the controller **3005** rotates the tumbler **3467** seated on a plurality of guide wheels **3472a-d**, **3472a'-d'** affixed to the suspension elements **3470a-d**, **3470a'-d'** thereby flipping the box **3500** upside down with its opening facing the inlet orifice **3130a'** therebeneath. Once the controller **3005** receives a signal that a selectively removable cover of the inlet orifice **3130a** is removed thereby exposing the orifice **3130a**, the controller **3005** signals the box tipping assembly **3400'** to rotate and drop the one or more deformable articles **12a-n** from the box **3500** through the orifice **3130**. The tumbler **3467**, frame **3465**, and suspension elements **3470a-d**, **3470a'-d'** are designed so that deformable articles **12** being tipped from the box in do not touch any of the tumbler **3467**, frame **3465**, and suspension elements **3470a-d**, **3470a'-d'** thereby avoiding being caught in these structural and moving components and avoiding potential contamination and subsequent cleaning requirements.

As described previously with regard to implementations, as shown in the system schematic of FIG. 5 and FIGS. 30A-31, the box tipping assembly **3400'** comprises a processor **3430** in wired or wireless communication with the controller **3005** via a network interface **3437**. The box tipping assembly **3400'** comprises a conveyor drive **3445** in operable communication with a reversible conveyor motor **3468** configured to receive a full box **3500** into the tumbler **3467** and eject the box **3500** once emptied. In implementations, the conveyor **3475** further comprises an incremental shaft encoder **3474** on the conveyor motor **3473** configured to rotate the conveyor rollers **3476** by a measurable amount to move a box **3500** into a clamping positioning within the tumbler **3467**. Additionally or alternatively, the conveyor **3475** comprises at least one position sensor **3450** configured to detect a position of a box **3500** within the tumbler **3467** and transmit a signal to the processor **3430** of the box tipping assembly **3400'** to actuate the clamp **3477** to retain the box **3500** for tipping. In implementations, the position sensor **3450** comprises at least one of one or more non-contacting electromagnetic switches (e.g., Hall effect sensors), one or more mechanical limit switches, one or more photoelectric proximity switches (e.g., break beams), and one or more inductive sensors, and output a signal to the drive motor **3437** to stop moving the rollers **3476**. The box tipping assembly **3400'** further comprises a tipper drive **3440** in operable communication with a tumbler motor **3468** configured to rotate the tumbler **3467** to invert a box **3500** clamped therein. In implementations an incremental shaft encoder **3455** is disposed on the drive motor shaft of the tumbler motor **3468** for detecting a rotational position of the tumbler **3467**. Additionally, in implementations, the box tipping assembly **3400'** comprises one or more limit

switches configured to detect at least one of the tumbler **3467** being upturned and the tumbler **3467** being inverted.

Turning now to the outlet end O of the enclosed channel, the outlet orifice **3135** is configured to receive individually sorted articles therethrough for batching into sorted loads of laundry for washing. In implementations, such as that of FIG. 17B, the device **3000** comprises an actuated outlet door **3137** in operable communication with the controller **3005**. In implementations, the outlet door **3137** can be similar in design and function to the inlet orifice door **3131**. In implementations, the outlet door can be a hinged door. In implementations, the outlet door comprises a two-piece trap door. The controller **3005** can be configured to receive a signal from the at least one sensor **3140a-c** indicative of the presence of a deformable article **12** positioned over the outlet orifice **3135** and actuate the outlet door **3137** to expose the outlet orifice **3135** on demand. By actuating the door **3137** on a just-in-time basis, the controller **3005** maintains the containment of any dirt, debris, and biological matter within the enclosed channel **3100** by minimizing the amount of time the orifice **3135** is exposed, thereby exposing the external environment to the contents of the channel **3100**.

In implementations, as shown in FIG. 18, the controller **3005** is further configured to determine whether a work volume **3105a-d** is clear of any articles **12** before an arm **3115** drops another article **12** into that work volume. For example, an article **12b** can remain in the third work volume **3105c** while a second arm **3115b** waits for the third arm **3115c** to finish cleaning the third work volume **3105c** before releasing another article **12c** into the third work volume **3105c**. The article **12b** remaining in the third work volume **3105** is detected by the one or more sensors, e.g., at least one of a downward angled sensor **3140a-c**, a transversely angled sensor **3145a-c**, and an upwardly angled sensor **3147a-c** as previously described with regard to implementations.

As previously described, in implementations, such as shown in FIGS. 10-11, the enclosed channel **3100** is raised above a floor **10** or platform. For example, the enclosed channel **3100** can be supported by a plurality of legs **17a-f** disposed on and, in some implementations, anchored to the floor **10** or platform. In implementations, one or more sorting bins **3202a-e** (also referred to herein as "bin" or "bins") are configured to be disposed beneath the stationary floor **3110** of the channel **3100** to receive the separated and sorted each one of the plurality of deformable articles **12a-n** associated with a single household's load of dirty laundry. The one or more sorting bins **3202a-e** are disposed beneath the exit orifice for receiving each one of the plurality of deformable articles exiting the enclosed channel **3100** individually and, in implementations, collecting a sorted and batched load of deformable articles for washing and drying collectively. In implementations, the one or more sorting bins **3202a-e** are disposed on a carousel **3200**, or load constructor, for rotating an appropriate one of the one or more sorting bins **3202a-e** beneath the outlet orifice **3135**. Each of the one or more bins **3202a-e** is configured to receive one or more of the plurality of deformable articles **12a-n** having one or more characteristics associated with at least one of the one or more bins **3202a-e** so that items having compatible and/or matching characteristics are aggregated into one or more associated bins. In implementations, the one or more characteristics comprise at least one of color, size, and fabric heat tolerance.

The autonomous separating and sorting robot **3000** is configured to provide the at least one deformable article **12** to one or more washing and drying devices **4000**, and in implementations the autonomous separating and sorting



robot **3000** comprises sensors configured to determine one or more characteristics of the at least one deformable article **12**. The one or more characteristics can be, for example, material composition, fabric finish, load weight, color, size, volume, article type, and degree of dirtiness. In implementations, the autonomous separating and sorting robot **3000** communicates these characteristics to the controller **4005** of the one or more washing and drying devices **400** for determining parameters for a washing and drying cycle, parameters such as wash cycle temperature, cleaning and rinse agent amounts and concentrations, wash cycle duration (e.g., one or more soak and agitation cycles), number and duration of rinse cycles, soak cycle duration, washing cycle agitation speed (e.g., for delicate, normal, and heavy loads), maximum spin speed during fluid (e.g., water and/or chemicals) extraction, wash detergent selection and concentration, number of rinse cycles, drying air temperature, drying airflow rate, and a minimum size device **4000** in a cluster **4002** for receiving each load of at least one deformable article **12**. Additionally or alternatively, in implementations, the autonomous separating and sorting robot **3000** is configured to estimate cycle duration and wash water requirements (e.g., for plant load balancing purposes across one or more clusters **4002**).

In implementations, the wash parameters associated with the identified one or more characteristics are stored in a memory in communication with the controller **3005**. The memory can be a memory **3010** of the separating and sorting device **3000** and additionally or alternatively can be a memory storage or database **235**, **250**, **240** in remote communication with the controller **3005** via the communication network **230**. Because each load of household laundry contains articles of various types, sizes, materials, stains, and related wash requirements, each load may comprise more than one associated wash parameter. The wash parameters can be stored in a look up table cross referenced with one or more characteristics along with a default hierarchy for selecting washing and drying parameters based on two or more characteristics. For example, water temperature and agitation cycle duration associated with material type can trump parameters associated with load volume or weight. For example, a large load of laundry comprising several heavy cotton towels can be washed on warm water with vigorous agitation while a large load of thing cotton undergarments can be washed at more slow, gentle agitation speeds. The controller **3005** thus can be configured to determine wash parameters for each individual load of laundry based on the characteristics of the one or more deformable articles **12** in each individual load and communicate at least one of the one or more characteristics and washing and drying parameters associated with a bin **3202** to the one or more washing and drying devices **4000** receiving the bin **3202**. Additionally or alternatively to the autonomous separating and sorting robot **3000** determining one or more characteristics of the at least one deformable article **12** for cross referencing with associated wash parameters, the wash parameters can be communicated to and received by a remote terminal **205** in communication with the communication network **230**. A user of the remote terminal, e.g., the customer owning the one or more deformable articles, can provide predetermined wash parameters associated with a tagged (e.g., RFID label, bar code, QR code, etc.) container of dirty laundry articles **12a-n** on an input screen of the remote terminal **205** or handheld device **245**, and the provided predetermined parameters can be communicated to and stored in the memory **4010**, **235**, **240**, **255** in communication with the controller **3005**.

Because the one or more characteristics can include at least one of load size, fabric type, fabric finishes, wash cycle temperature, and article type (e.g., thick, water retaining items such as towels and jeans and thinner fabric items such as t-shirts and underwear), in implementations, at least one of the controller **4005** of the washing and drying device **4000** and remote terminal **205** determines optimum conditions for airflow, air temperature, and drying duration based on the load characteristics detected by the separating and sorting robot **3000**. For example, the load characteristics can comprise two or more of the following load characteristics: the size of the load of laundry articles **12a-n** relative to a size of a drum of a washing and drying robot **4000a-n**, the fiber composition and fabric type (e.g., weave/knit type and looseness, length of fibers (staple) from which the fiber/yarn is spun, spin quality of the fiber/yarn, fuzziness, etc.) of one or more articles **12** in the load, fabric finishes of one or more articles **12** in the load, wash cycle temperature, and article type and thickness. The two or more load characteristics can be determined by the dirty laundry separating and sorting robot **3000** and communicated to the controller **4005** of the washing and drying robot **4000** and/or the remote terminal **205** by a controller **3305** of the dirty laundry separating and sorting robot **3000** via a wired or wireless network **230**.

Turning to the system schematic of FIG. 5, as previously described, the controller **3005** is configured to determine based on receiving a signal from the at least one sensor **3140**, **3145**, **3147** disposed within each of the plurality of sequential work volumes **3105a-d** that none of the plurality of deformable articles **12**, **12a-n** remain on the stationary floor **3110** in any of the plurality of sequential work volumes in the enclosed channel **3100**. Upon determining that none of the plurality of deformable articles **12**, **12a-n** remain on the stationary floor **3110** in any of the plurality of sequential work volumes **3105a-d**, at least one of the controller **3005** and a load constructor processor **3221** is further configured to instruct at conveyor drive **3222** of the load constructor **3200** to transit the one or more bins **3202a-e** of the sorted plurality of deformable articles **12**, **12a-n** to one or more autonomous combination washing and drying machines **4000**.

The one or more deformable articles **12**, **12a-n** in a common bin **3202a-e** are routed to a single washing and drying device **4000**. In implementations, more than one bin **3202a-e** can be routed to a single washing and drying device **4000** if the characteristics of the deformable articles therein are matching and/or compatible for washing together and without exceeding a load capacity of a washing and drying device **4000**, as will be described subsequently with regard to implementations of load construction parameters. In implementations, the device **3000** comprises at least one fill sensor in communication with the controller **3005**, and the at least one fill sensor is configured to detect an occupied volume of the one or more bins. In implementations, the fill sensor is an optical sensor focused on a minimum threshold fill line and a maximum threshold fill line disposed on an interior surface of one of the one or more bins **3202a-e** positioned beneath the exit orifice. The optical fill sensor can be configured to detect whether the of one or more of the plurality of deformable articles received in the one of the one or more bins reaches or surpasses the minimum threshold fill line. In implementations, the maximum threshold fill line comprises a top edge of the one of the one or more bins **3202a-e**. Additionally or alternatively, the fill sensor is configured to output a signal indicative of the occupied volume of the one of the one or more bins being with a threshold range between the minimum threshold fill line and

maximum threshold fill line. Upon determining an occupied volume of the one of the one or more bins is within a threshold range indicative of being filled, the controller **3005** is further configured to instruct the load constructor **3200** to unload the filled one of the one or more bins **3202a-e** containing the sorted plurality of deformable articles **12a-n** to the autonomous combination washing and drying device **4000**. In implementations, a filled volume of all deformable articles in a single bin **3202** should be less than a washing and drying device capacity. For example, the washing and drying device capacity can be in a range of between about  $0.10\text{ m}^3$  to  $0.20\text{ m}^3$ . In implementations, the washing and drying device capacity can be at or about  $0.17\text{ m}^3$ . In implementations, the controller **3005** is configured to determine whether additional items can be added to a collection bin **3202**. The controller **3005** can determine whether a deformable article **12** fits into the available bin based on a size estimate and previous bin fill level. For example, the controller **3005** can be configured to stop loading a bin **3202** that is in a range of between about one half to three quarters full.

Additionally or alternatively, as shown in FIGS. **10-11** and FIGS. **51A-B**, the fill sensor is a weight sensor (e.g. a scale or loadcell **3215**) disposed beneath the one of the one or more bins **3202a-e** positioned beneath the exit orifice **3135**. The scale **3215** is configured to detect whether the weight of the one of the one or more bins **3202a-e** reaches or surpasses the minimum threshold weight indicative of a bin full condition. Because the weight of all articles **12a-n** in a single bin **3202** must weigh less than a washing and drying device **4000** capacity, the controller **3005** is configured to determine whether additional items can be added to a collection bin **3202** based on at least one of weight and volume. The controller **3005** can determine whether a deformable article **12** fits into the available bin based on a weight estimate of the article and the bin weight. For example, in an implementation, the washing and drying device capacity can be about 16 kg, and the controller **3005** can be configured to stop loading a bin **3202** having a current net bin mass of greater than or equal to 14 kg. In implementations, the washing and drying device capacity can be about 16 kg, and the controller **3005** can be configured to not add a heavy item to a bin **3202** having a current net bin mass of greater than or equal to 10 kg. In implementations, a heavy item weighs between about 5-10 kg. In implementations, the controller **3005** is configured to obtain a mass measurement of a deformable article **12** by reading the tilt arm current of a tilt motor **3125b-b"** of the at least one drive motor **3125a-c** required to raise the deformable article **12** to the hoist height **H1**.

In implementations, the fill sensor is configured to output a signal indicative of the bin full condition. Upon receiving the bin full condition output signal, the controller **3005** is further configured to instruct the load constructor **3200** to unload the filled one of the one or more bins **3202a-e** containing the sorted plurality of deformable articles **12a-n** to one or more autonomous combination washing and drying machines **3000**. In implementations, each of the one or more bins **3202a-e** comprises an identification marker **3220a-e** for associating with at least one of a identity of the bin and one or more characteristics of the one or more deformable articles sorted into the each of the one or more bins **3202a-e**.

In implementations, as shown in FIG. **32**, the identification marker **3220a-e** of each bin **3202** of the plurality of bins **3202a-e** comprises a customer ID and at least one of a net weight, a final fill level (e.g., Full,  $\frac{3}{4}$ ,  $\frac{1}{2}$ ,  $\frac{1}{4}$ , and E, where E indicates the contents being below the  $\frac{1}{4}$  fill level), color

(e.g., light or dark) and item size (e.g., large or typical). A controller **4005** in operable communication with the autonomous washing and drying machine **4000** or machines receiving the one or more bins **3202a-e** will use the information associated with the identification marker or markers **3220a-e** to determine how and whether to combine one or more of the bins **3202a-e** in a single washing and drying device **4000**. Additionally or alternatively, the controller **3005** of the device **3000** and/or the controller **4005** of the washing and drying device **4000** can be configured to determine how and whether to combine one or more of the plurality of bins **3202a-e** based on one or more characteristics of the one or more deformable articles **12a-n** disposed in each bin **3202a-e** and associated with the bin marker **3220**. In implementations, the bin marker **3220**, **3220 a-e** comprises a visible marker such as a digital display, an RFID tag, a bar code, or a QR code. Additionally or alternatively, the bin marker **3220** is determined by the controller **3005** and assigned to a bin **3202** based on the bin position on the load constructor **3200**. The bin marker **3220** is a unique pointer passed to a structure in software.

The parameters for determining combining bins can be stored on a local and/or remote memory in wired or wireless communication with a least one controller **3005**, **4005**. To prevent overfilling a washing and drying device **4000**, the parameters can include one or more of the following limitations: ' $\frac{3}{4}$ ' full bins shall not be combined with any other bins, a ' $\frac{1}{2}$ ' full bin may only be combined with a single ' $\frac{3}{4}$ ' full bin, a ' $\frac{3}{4}$ ' full bin may be combined with another ' $\frac{3}{4}$ ' full bin or an 'E' bin, three "E" bins may be combined and a combined weight of all bins must be less than a threshold weight. For example, the threshold weight can be in a range of between about 10-20 kg. In implementations, the threshold weight is at or about 16 kg.

As previously described, in implementations the device **3000** comprises an actuatable load constructor **3200** in operable communication with the controller **3005**. As shown in FIGS. **10-11** and **32**, in implementations, the load constructor **3200** is configured to receive thereon the one or more bins **3202a-e** and rotate the one or more bins **3202a-e** beneath the enclosed channel **3100** to match a characteristic of one of the one or more bins positioned beneath the outlet orifice **3135** with the one or more characteristics of each one of the plurality of deformable articles **12**, **12a-n** exiting the enclosed channel **3100**. In implementations, the load constructor **3200** comprises one or more conveyors **3205**, **3205a-d** for positioning one of the one or more bins **3202a-e** disposed thereon beneath the exit orifice **3135**. In implementations, a central conveyor **3205a** is configured to receive thereon a bin **3202c** for placement beneath the orifice **3135**. In implementations, the conveyors **3205a-d** are configured to move the bins both back and forth in the direction of the channel inlet end I to outlet end O and side to side. In implementations, the conveyor is configured to hold one fewer bin than the number of available conveyor spaces such as a gap **3217** enables free flowing movement of the bins **3202a-e** on the load constructor.

Turning now to FIGS. **48-57**, in implementations the load constructor **3200** comprises 6 conveyors for receiving a maximum of 5 bins **3202a-e** thereon for moving back and forth and side to side to position a particular bin beneath the exit orifice **3135**. The total number of conveyors can scale to any number as long as one conveyor **3205** is left unoccupied for shuffling two or more bins **3202a-e** about the load constructor **3200**. As shown for example in FIG. **52**, in implementation, each conveyor **3205** comprise a plurality of driven rollers **3245a-f** configured to position a bin **3202**

thereon in a first direction and a plurality of pop up transfer roller assemblies **3240a-d** configured to raise a rotating belt **3241** up above a top plane of the driven rollers **3245** to engage a bottom surface of the bin **3202** and transfer the bin **3202** thereon in a direction perpendicular to the first direction. As shown in FIGS. **50** and **52B**, in implementations each rotating belt **3241** is driven by a drive gear **3243** and supported by one or more rollers **3245a-e** for tensioning and retaining the belt **3241** thereon. As shown in FIGS. **49-50** and **52-54**, each of the transfer roller assemblies **3240** is spring loaded to raise the rotating belts **3241** of each pop up transfer roller assembly **3240**, **3240a-d** up higher than the adjacent rollers **3245**, **3245a-f**. As shown in FIGS. **53-54** the pop up transfer roller assemblies **3240a-d** of each conveyor **3205** are mounted on a shared moveable frame **3246** and, in implementations, are geared together for simultaneous rotation of each belt **3241** of the plurality of transfer roller assemblies **3240a-d**.

In implementations, each of the maximum number of bins **3202** can be positioned on the load constructor **3200** at the start of a separating and sorting process for a load of deformable laundry articles **12a-n**. Alternatively, the load constructor processor **3221** can call for the autonomous loading of a bin **3202** onto the load constructor **3200** upon receipt of a signal communicating of a detected condition comprising at least one of a start of a separating and sorting process, the identification of a new article characteristic associated with newly identified washing and drying parameters (e.g., color, fabric type, material thickness, stain identification, etc.) within a load of dirty laundry articles **12a-n**, and detection of a bin full condition of a bin **3202** disposed on the load constructor **3200** prior to completing separating and sorting of a load of deformable laundry articles **12a-n**.

For example, as shown in FIG. **55A**, first bin **3202** labeled with the numeral 1 enters a load position beneath the orifice **3135**. The load position in this example is conveyor **3205b** and the total number of conveyors **3205a-d** is eight. The first article **12a** that enters the first bin **3202** (e.g., numeral 1) sets the bin type. For example, if the first article **12a** is a large, white, thick, terrycloth article such as a towel, the bin characteristic is at least one of large, white, thick, and terrycloth such that any other large, white, thick, terrycloth items subsequently identified by the one or more sensors **3140a-d**, **3145a-d**, **3147a-d** of the enclosed channel **3100** will be deposited also in this bin **3202** until a bin full condition is reached. As shown in FIG. **55B**, when the separating and sorting device **3000** identifies an article of a second type, the first bin (numeral 1) moves to a new conveyor position (e.g., corner conveyor **3205**) and a second bin labeled with numeral 2 is transferred across one or more conveyors **3205c-d** to the load position conveyor **3205** beneath the orifice for receiving the article of a second type. In this way, each bin **3202** of the plurality of bins **3202a-e** contains one or more deformable articles **12a-n** comprising one or more shared characteristics for effective aggregate washing and drying. As shown in FIG. **56A**, in implementations, a bin disposed on the load position conveyor **3205b** can move side to side (arrow S) on one of the driven rollers **3240a-f** and the pop up transfer roller assemblies **3245a-d** and back and forth (arrow BF) on the other of at least one of the driven rollers **3240a-f** and transfer roller assemblies **3245a-d**. As shown in FIG. **56B**, one or more sensors **3140d-g** are positioned about the load constructor **3200** for detecting the at least a level and/or volume of one or more deformable articles **12a-n** contained in each of the one or more bins **3202**, **3202a-n** thereon. In implementations, the

one or more sensors **3140d-g** comprise one or more cameras positioned about the load constructor **3200**.

FIGS. **57A-D** depict a sequence of moves of 5 bins **3202** (labeled 1-5) moving about a load constructor **3200**. Each bin moves one conveyor location at a time, either front to back or side to side. In FIG. **57A**, bin number 2 moves to an open location. In FIG. **57B**, bin number 1 transfers to bin number 2's starting location and bin number 4 transfers to bin number 1's starting location. In FIG. **57C**, bin number 2 moves to bin number 4's starting location and bin number 1 moves to bin number 2's second location, as shown in FIG. **57D**. In implementations, the controller **3005** and/or load constructor processor **3221** is configured to move the bins in a most efficient sequence when a particular bin type is called to the loading position. For example, at least one of the controller and load constructor processor **3221** employs optimized path planning (e.g., DIJKSTRA'S path planning algorithm) for efficient, autonomous reordering of bins **3202a-n** on the load constructor **3200**. Additionally, in implementations, each conveyor **3205** of the plurality of conveyors **3205a-n** comprises one or more position sensors **3228** for detecting a position of a bin **3202** thereon as successfully loaded and approximately centered. For example, in implementations, each conveyor **3205** of the plurality of conveyors **3205a-n** comprises four limit switches, one disposed at each corner of the conveyor **3205**, for detecting the passage of a bin thereacross such that the controller **3005** and/or processor **3221** receiving signals from one or more of the four limit switches can determine a position of the bin **3202** based on which switches of which conveyor(s) detected passage of a transferring bin **3202** thereacross.

As previously described, each of the one or more bins **3202a-e** comprises an identification marker representative of the contents of the bin and linkable with a customer ID. In implementations, the identification marker comprises at least one of a machine-readable serial number, a bar code, a machine-readable QR code, an RFID code, NFC tag, a WIFI enabled tag, a ZIGBEE enabled tag, and an active radio telemetry system. In implementations, the controller **3005** can create a virtual tag in memory associated with a known location of one or more bins based on an initial location and subsequent locations as the one or more bins move through the process line **100**, **100a-c**. In implementations, the controller **3005** is in communication with a memory configured to store at least one relation comprising one of the one or more characteristics associated with the bin, the bin identification marker for each of the one or more bins, and a customer identity shared by the plurality of deformable articles received into the enclosed channel. In implementations, the controller **3005** is in communication with a communication network **230**, and a remote terminal **205** in communication with the communication network is configured to receive a customer input comprising the one or more characteristics associated with the plurality of deformable articles.

Additionally or alternatively, in implementations, at least one sensor (e.g., one or more sensors **3140a-c**, **3145a-c**, **3147a-c**) is configured to detect the one or more characteristics of each one of the plurality of deformable articles **12a-n** and output a signal to the controller **3005** comprising the detected one or more characteristics. In implementations, the at least one sensor comprises at least one of a 3D camera, an IR sensor, a 2-D camera, LIDAR, LADAR, a sonar proximity sensor, an ultrasonic ranging sensor, a radar sensor, a pair of stereo depth cameras, a colorimeter for determining color of an article **12**, and a spectrometer for

determining fiber type of a deformable article **12**. In implementations, the at least one sensor comprises at least one of a colorimeter and spectrometer disposed on or in the fingertips of the gripper fingers **3107a-b** because these points come into close contact with the material of the article **12** for successful evaluation. Additionally or alternatively, the at least one sensor comprises at least one of a colorimeter and spectrometer disposed at least one of in a wall **3112a-d** of the channel **3100** and along the floor **3110** such that an arm **3115** can hold a hoisted article against or immediately proximate the sensor. The one at least one sensor can further detect one or more stains disposed on a deformable article and flag the article in software for delivering to a bin **3202** marked for stain treatment in the washing and drying device **4000**. In implementations, the at least one sensor comprises a camera (e.g., one or more sensors **3140a-c**, **3145a-c**, **3147a-c**) associated with one or more of the plurality of work volumes outputs at least one of depth map, RGB images, and IR images. In implementations, the at least one sensor comprises a camera (e.g., one or more sensors **3140a-c**, **3145a-c**, **3147a-c**) associated with one or more of the plurality of work volumes, the camera being configured to output 3-D image data to the controller **3005**. Additionally or alternatively, the at least one sensor comprises a camera (e.g., one or more sensors **3140a-c**, **3145a-c**, **3147a-c**) associated with one or more of the plurality of work volumes and the camera is configured to output one or more 2-D images to the controller **3005**. As previously described, in implementations, the at least one sensor is a camera, and the camera is calibrated to at least one of the floor of the enclosed channel **3100** and one or more of the plurality of arms **3115a-c**.

In implementations, the controller is configured to determine, based on a comparison of a received output signal of the at least one sensor to data stored in a memory in communication with the controller, at least one of an article type, an article color, an article size, and an article fabric. In implementations, at least one sensor is a 2-D camera, and the data associated with the deformable laundry article is size invariant image data comparable with database images of tagged articles and/or classes of articles.

In implementations, the memory comprises a neural network **300**, and determining the one or more characteristics of each one of the plurality of deformable articles comprises processing the received output signal of the at least one sensor with a neural network classifier. In implementations, as shown in FIG. **33**, the neural network **300** comprises a trained neural network, for example a convolutional neural network that operates quickly on 3D and/or 2D data and is configured to classify images from the 3D and/or 2D camera. In an implementation, the classification comprises generating a descriptor based on the output signal of the at least one sensor **3140a-c**, **3145a-c**, **3147a-c** associated with each one of the plurality of work volumes, and classifying, using the neural network, the output signal based on the descriptor. The neural network is configured to output a probability that the output signal corresponds to a class of the stored data indicative of one or more deformable article types, for example. The classes of trained data in the neural network include data associated with many types of deformable articles. For example, as shown in FIG. **33**, a neural network **300** can be trained with a set of training data **305**. After training, the neural network **300** comprises a set of weights that can be used for neural network inference to determine whether an input **330** (e.g., output signal from the one of the at least one sensors **3140a-c**, **3145a-c**, **3147a-c** in each one of the plurality of sequential work volumes **3105a-d** of the device **3000**) is within one of the trained classes. The classes

of trained data in the neural network include data associated with many types of deformable laundry articles that comprise particular washing characteristics (e.g., size, color, temperature requirements, degree of dirtiness, etc.)

For example, size is a particularly important characteristic of a deformable article because a large item (e.g., a bed sheet, comforter, tablecloth, large bathrobe, etc.) can envelop smaller items, preventing them from being washed or dried effectively. Therefore the controller **3005** will prevent mixing these items in a common (e.g., shared) bin **3202** for washing. The neural network **300**, therefore can be used to determine whether a deformable article in the enclosed channel **3100** is of a large garment class. For example, in implementations such as that of FIG. **21**, the controller **3005** is configured to receive an output signal comprising an image **3142** of a deformable article **12a** engaged with at least one gripper (e.g., two or more grippers **3120b**, **3120c**) at a hoist height **H1**. The controller is configured to determine, based on the output signal, a number of pixels in each of an upper half **3142a** and a lower half **3142b** of the image, and based on the number of pixels in the lower half of the image exceeding a preset threshold that the at least one deformable article **12a** comprises a large sized article. Additionally or alternatively, the controller **3005** can be configured to determine an overall pixel count occupied by the deformable article. Additionally or alternatively, the controller **3005** can be configured to determine a gap height **H2** as previously described with regard to implementations, and, based on the gap height being equal to or less than a threshold distance, determine the deformable article **12a** is of a large size class.

In other implementations, such as that of FIG. **22**, the controller **3005** can determine whether a deformable article is a large item by stitching images together from multiple cameras (e.g., sensors **3140a-c**, **3145a-c**, **3147a-c**), and identifying article size and position relative to the coordinates of the enclosed channel **3100**. The controller **3005** is configured to create a single-image view of the entire floor **3110** of the channel and identify the deformable article **12** against the backdrop of the entire length of the floor **3110**. Because the one or more sensors (e.g., cameras) **3140a-c**, **3145a-c**, **3147a-c** are calibrated into the physical space of the enclosed channel **3100**, the controller **3005** can determine where in physical dimensions of the channel the article begins and ends. For example, as shown in FIG. **22**, the article **12** is a large size article spanning between the second and third work volumes **3105b-c**.

As previously described with regard to implementations, the at least one of the controller **3005** and load constructor processor **3221** can determine a bin full condition based on at least one of a weight and a volume of each of the plurality of loaded bins **3202** on the load constructor **3200**. As previously described with regard to implementations shown in FIGS. **51A-B**, one or more corners of a load position conveyor beneath the outlet orifice **3135** each comprises a loadcell **3215** there beneath. In implementations, each of the loadcells **3215a-d** are in operative communication with at least one of the controller and the load constructor processor **3221** for outputting a signal indicative of a weight of a bin **3202** positioned on the load position conveyor. In implementations, each loadcell **3215** is configured to sense a weight in a range of between about 10 kg to 30 kg. Additionally or alternatively, a bin full condition is detected by one or more sensors configured to detect the height of the contents of a bin. For example, as shown in FIG. **56B**, one or more cameras **4140d-g** disposed about the load constructor detect the height of contents within a bin and whether the

contents have exceeded a threshold bin volume height. In implementations, each camera **4104d-g** can detect a volume of one or more deformable articles in a bin **3202** by breaking the (lengthxwidth) of a bin into discrete “columns”. Because the camera is positioned a set height relative to the load constructor **3200**, a static distance to the bottom of a bin **3202** is known. For each column in a bin, the camera **3140d-g** measures the heights and calculates the volume of each column. At least one of the controller **3005** and load constructor processor **3221** sums the volumes of every column and calculates an approximate filled volume within the bin. Because the bin has a known maximum volume and/or maximum threshold fill volume, the controller **3005** and/or load constructor processor **3221** compares the filled total volume against the maximum volume and/or maximum threshold fill volume and then determine whether the remaining unoccupied volume in a bin can receive an additional one or more articles **12**. As described with regard to implementations, the one or more sensors **3140a-c**, **3145a-c**, **3147a-c** of the enclosed channel and/or one or more sensors of the arm **3115**, gripper **3120** and drive motors **3125a-c** can determine or approximate based on weight the size of a separated article positioned above the outlet orifice **3135**.

Additionally or alternatively, in implementations, the controller **3005** executes a crumple predictor routine for determining a volume of a separated article **12**. The crumple predictor is trained by taking a picture of a suspended article, dropping the articles on the floor **3110** of the channel **3100** and taking a picture of the article on the floor **3110**. The controller **3005** then computes a volume of the article on the floor **3110** from point cloud voxels of the detected article **12**. The crumple predictor can be trained on a plurality of articles comprising a plurality of shapes, sizes, and volumes, and the controller **3005** can store that information in memory **3010** or database for estimating volumes of subsequently separated articles **12** suspended in the channel **3100**.

Because articles **12a-n** can pile in a pyramid during loading, the driven rollers **2145a-d** of the plurality of conveyors **3105a-n** are configured to rotate rapidly in opposite directions to “shake” the bin **3202** thereon and settle the contents therein from a pyramid to a more uniform height across the length and width of the bin **3202**. Additionally or alternatively, the device **3000** comprises one or more plungers for pushing a just loaded article **12** into a bin **3202** and compressing the peak of any pyramid shaped deposited article.

As previously described with regard to implementations, at least one of the controller **3005** and load constructor processor **3221** can intelligently shift bins **3202a-n** on the load constructor **3200** such that the plurality of deformable articles **12a-n** are sorted into one or more bins based on what percent of the load of deformable articles **12a-n** has been separated and sorted and what percent remains. Additionally or alternatively, the load constructor **3200** can fill each bin **3202a-n** to a “bin full” state before starting to fill a second bin of the same type. Alternatively, the load constructor can fill two or more bins of the same article type (e.g., two light article bins), alternating between the two or more bins with each addition of an article of that type. When the separation and sorting process completes, the at least one of the controller **3005** and load constructor processor **3221** determines if the two or more bins of the same article type can be combined into a single washing and drying device **4000** without exceeding a threshold capacity.

As described previously, once the controller **3005** determines that all deformable articles of a plurality of deform-

able articles **12a-n** received into the enclosed channel **3100** from a customer box **3500** are sorted into the one or more bins **3202a-e**, the controller **3005** instructs the load constructor **3200** to convey the remaining bins thereon to one or more washing and drying devices **4000a-n**. The controller **3005** then prepares the enclosed channel **3100** for receiving a next load of one or more deformable articles **12a-n**. In implementations, as shown in FIGS. **6-9** and **34-35**, the device **3000** comprises a retractable cleaner **3600** configured to advance through the enclosed channel **3100** from the inlet end I to the outlet end O while cleaning one or more interior surfaces. In implementations, the retractable cleaner **3600** is configured to form the inlet wall **3112a** of the enclosed channel **3100** in a fully retracted position. In implementations, the retractable cleaner comprises a planar profile contoured and fitted to a cross sectional profile of the enclosed channel **3100**. In implementations, the cross-sectional profile of the enclosed channel is a symmetrical polygon, symmetric about a center line. In implementations, the cross sectional profile of the enclosed channel **3100** is not symmetrical.

In implementations, the retractable cleaner **3600** comprises an actuatable cleaning drive motor in operable communication with the controller **3005**. Upon determining that none of the plurality of deformable articles **12a-n** remain on the stationary floor **3110** in any of the sequential work volumes **3005a-d**, the controller **3005** is configured to instruct the retractable cleaner **3600** to advance from the inlet end I to the outlet end O of the enclosed channel **3100**. In implementations, the drive motor extends a telescoping plunger **3612** or pusher arm disposed on an external face **3616** of the retractable cleaner **3600**. As shown in FIG. **35**, in implementations, the controller **3005** is configured to instruct the plurality of arms **3115a-c** to retract from their associated work volumes prior to the retractable cleaner **3600** advancing through the plurality of work volumes **3105a-d** such that only the terminal gripper **3120a-c** of each of the plurality of arms **3115a-c** remains within an associated work volume of the enclosed channel **3100**. The retractable cleaner **3600** can comprise a slot **3605** configured to pass over and clean the terminal gripper **3120**. Additionally, in implementations, the device **3000** includes a waterproof covering **3117** or seal about the arm **3115**. The waterproof covering **3117** can comprise at least one of a flexible cone and an accordion pleated boot covering the arm and surrounding opening in a sidewall of the channel **3100** through which the arm **3115** extends. By sealing the opening, the waterproof covering **3117** prevents moisture from escaping the channel **3100** during cleaning and contains dirt, debris, biological matter, and any other biohazards and loose items within the enclosed channel **3100** during the separating process and sorting. Because the covering **3117** is flexible, arm movement is unconstrained and because the covering is waterproof, it can withstand the pressure, temperatures, and chemical compositions and cleaning solutions emanating from the retractable cleaner **3600**.

Additionally, in implementations, the device **3000** further comprises one or more UV lights in operable communication with the controller **3005** for cleaning the enclosed channel **3100**. The one or more UV lights are configured to illuminate the one or more sequential work volumes **3105a-d** of the enclosed channel **3100** after the retractable cleaner **3600** advances to the outlet end O and then retracts to the inlet end I. In implementations, the one or more UV lights are disposed on one or more interior surfaces of the enclosed channel **3100**, and the controller **3005** is further configured to instruct the plurality of arms fully extend into

the enclosed channel before the one or more UV lights are illuminated, thereby also cleaning the fully extended arms **3115a-c**. This sanitizes the enclosed channel surfaces and the arms **3115a-c** and associated grippers **3120a-d** between separating and sorting successive loads of one or more dirty deformable articles **12a-n**, thereby preventing the potential introduction of contaminants, pathogens, and other debris and dirty between loads of articles.

Turning back to FIG. **34**, in implementations, the retractable cleaner **3600** further comprises one or more wheels or pairs of wheels **3610a-e** extending from an outer face **3616** (e.g., end wall **3112a**) of the retractable cleaner **3600**. The one or more wheels or pairs of wheels **3610a-e** are configured to guide the motion of the retractable cleaner **3600** along one or more interior surfaces of the enclosed channel **3100** as the plunger arm **3612** advances the retractable cleaner **3600** down the length of the enclosed channel **3100** from in the inlet end I to the outlet end O. In implementations, the retractable cleaner **3600** comprises a plurality of spray ports **3615a-n** disposed along a continuous outer surface **3620** of the retractable cleaner **3600** facing the one or more interior surfaces of the enclosed channel **3100**. A service line **3625** is in fluid communication with the plurality of spray ports **3615a-n**. The service line **3625** is configured to provide a cleaning fluid for application to the one or more interior surfaces via the plurality of spray ports **3615a-n**. In implementations, the cleaning fluid comprises at least one of steam, water, a detergent, a germicide, and a pesticide.

In implementations, the service line **3625** further comprises at least one of a vacuum line and a power conduit. Additionally, in implementations, the retractable cleaner **3600** further comprises a plurality of evacuation ports **3630a-n** disposed along the continuous outer surface **3620** of the retractable cleaner facing the one or more interior surfaces of the enclosed channel. The plurality of evacuation ports **3630a-n** is in operative communication with the vacuum line for suctioning remaining moisture from the one or more interior surfaces of the enclosed channel **3100** upon advancement of the retractable cleaner **3600** through the enclosed channel **3100**.

Additionally, in implementations, the retractable cleaner **3600** comprises a squeegee **3635** on a trailing edge of the continuous outer surface **3620** of the retractable cleaner **3600** facing the one or more interior surfaces of the enclosed channel.

As described with regard to implementations, the device **3000** comprises a plurality of arms **3115a-c** for separating a plurality of deformable articles and intelligently sorting the articles one at a time into one or more batches for washing. As previously described, each of the plurality of arms **3115a-c** is configured to pan, tilt, extend, and retract within an associated work volume **3105a-c** of the enclosed channel **3100**.

As shown in FIGS. **36-38**, the plurality of arms **3115a-c** each extend from a corresponding anchor **3118a-c** at corresponding individually anchored positions as shown, for example, in the implementations of FIGS. **10-11**. In implementations, the anchor **3118a-c** comprises a columnar pedestal or base affixed to the floor **10** beneath the device **3000** and adjacent the enclosed channel **3100**. In implementations, each arm **3115a-c** comprises a fully extended length of between about 0.25 m and 4 m. The plurality of arms **3115a-c** are each configured to tilt and extend to a hoist height **H1**. In implementations, the hoist height comprises a predetermined height. Additionally or alternatively, the hoist height can vary depending on the size of a raised article **12**.

The controller **3005** can dynamically determine a final hoist height, based on, for example, a received sensor signal, that the article **12** is suspended above the floor **3110** of the channel **3100**. In implementations, the hoist height comprises a range of between about 0.5 to 4 m above the stationary floor **3110**.

Turning to FIGS. **36-38**, the arm **3115a-c** comprises at least one drive motor **3125a-c** disposed on an anchor **3118a-c**, and, in implementations, the at least one drive motor comprises a pan drive motor **3125a**, a tilt drive motor **3125b**, and an extend drive motor **3125c** as will be described in detail subsequently. In implementations, the plurality of anchors **3118a-c** are each associated with one of the plurality of arms **3115a-c** and disposed on at least one of a wall **3112a-d**, the stationary floor **3110**, and the ceiling **3111** of the enclosed channel **3100**. In implementations, each anchor is disposed outside the enclosed channel **3100** and the associated one of the plurality of arms **3115a-c** moveably engaged therewith extends through a side wall **3112c-d** of the enclosed channel **3100**.

In implementations, the enclosed channel **3100** comprises a plurality of openings in a sidewall, each opening being configured to receive one of the plurality of arms **3115a-c** therethrough. Implementations, as described with regard to FIG. **25**, a seal or covering **3117** is disposed about each of the plurality of openings through which each one of the plurality of arms extends. In implementations, the seal comprises a flexible material configured to stretch as the rod extends, pans, tilts, and retracts. Additionally or alternatively, the seal is pleated and compressible. As described with regard to the implementation of FIG. **35**, the seal is configured to enable the arm **3115a-c** to retract so that only the terminal gripper **312a-c** remains exposed within the enclosed channel **3100** for cleaning and sanitizing. In implementations, the flexible material comprises at least one of NEOPRENE, vinyl, rubber, plastic, leather, urethane, silicone, and elastane (SPANDEX).

In implementations, as shown in FIGS. **6-7** and **10-11**, for example, the plurality of arms **3115a-c** are disposed along a length of the enclosed channel **3100** at individually anchored positions spaced apart from each of the other anchored positions by between about 150 cm to 400 cm. In one implementation, the plurality of arms **3115a-c** are spaced apart by a distance of between about 4 to 9 feet (e.g., 4 ft, 4.25 ft, 4.5 ft, 4.75 ft, 5 ft, 5.25 ft, 5.5 ft, 5.75 ft, 6 ft, 6.25 ft, 6.5 ft, 6.75 ft, 7 ft, 7.25 ft, 7.5 ft, 7.75 ft, 8 ft, 8.25 ft, 8.5 ft, 8.75, 9 ft). In implementations the plurality of arms **3115a-c** comprises at least two arms. In implementations, the plurality of arms **3115a-c** comprises at least three arms. In implementations, each one of the plurality of arms **3115a-c** comprises an arm with no joints. In some implementations, at least one arm of the plurality of arms **3115a-c** comprises one or more joints. In implementations, one of the one or more joints is a spherical joint. In alternative implementations one or more of the plurality of arms **3115a-c** comprises a stationary vertical riser along which a gripper translates up and down. In still yet other implementations, one or more of the anchors **3118a-c** comprises a rotatable riser along which a gripper **3120** translates bidirectionally. In implementations, rather than rotating between work volumes as described previously, one or more of the plurality of arms **3115a-c** can be movably mounted to slide or motor along one or more tracks disposed above and/or aside the floor **3110** of the channel **3100**. The one or more movably mounted plurality of arms are configured to slide linearly between at least one of vertical and horizontal positions, the horizontal positions extending the length of each work

volume **3105a-c**. In implementations, the movably mounted arms are configured to at least one of extend and tilt. Additionally, in implementations, the plurality of arms movably mounted to rails comprise one or more joints.

In the implementation of FIG. 11, the device **3000** comprises three arms **3115a-c** connected to bases **3118a-c** each anchored aside the enclosed channel **3100**. In implementations, one or more of the bases **3118a-c** is anchored to a floor **10** beneath the enclosed channel **3100**. In other implementations, one or more of the bases **3118a-c** is anchored to a ceiling **3111** or support frame or beam **3119** located above the floor **3110** for providing access to an associated plurality of work volumes **3105a-d**.

As previously described with regard to implementations, each of the plurality of arms **3115a-c** comprises at least one drive motor **3125a-c**, **a'-c'**, **a"-c"** schematically represented in FIG. 6 and shown in FIGS. 36-38. (Although FIGS. 34-36 show a single arm **3115**, all elements described herein are considered applicable to each arm and where applicable elements are generically referenced.) Each arm **3115**, **3115a-c** (hereinafter referred to as an arm **3115**) of the plurality of arms **3115a-c** can comprise between one and three degrees of freedom. As shown in FIGS. 6 and 37-38, in implementations, each arm **3115** of the plurality of arms **3115a-c** can include a pan motor **3125a**, **a'**, **c'** for rotating each associated arm **3115a-c** about a vertical axis P through a rotational angular direction  $\alpha$  and parallel to schematically represented vertical axis  $L_z$ . In implementations, each arm **3115** is disposed at anchored positions spaced apart by at least about a distance of at least 5-20 inches (e.g., approximately 12-50 cm) from the channel **3100** exterior surfaces so as to not interfere with the enclosed channel **3100** while maintaining effective working volumes for successfully grasping, hoisting, and rotating one or more articles **12** down the channel **3100**. As shown in FIG. 5, in implementations, the pan motor **3125a-a"** comprises an encoder **3157a-a"** for detecting a rotational position of the arm **3115a-c**, **a'-c'**, **a"-c"**. In implementations, the pan motor **3125a-a"** is a controllable servo motor and comprises a speed encoder in operable communication with at least one of the processor **3155**, **3155a-c** and the controller **3005**.

In implementations, each arm **3115** of the plurality of arms **3115a-c** can include a tilt motor **3125b**, **b'**, **b"** for raising and lowering the arm **3115** and associated terminal gripper **3120** with respect to the floor **3110**, wherein the floor **3110** is in a plane defined by axes  $L_{HX}$  and  $L_{HY}$  as shown in FIG. 7. The arm tilt motor **3125b**, **b'**, **b"** is positioned at least a distance of 300 mm over the floor **3110**. In implementations, a tilt motor **3125b-b"** comprises an encoder **3157b-b"** for detecting a position of the arm **3115**, **3115a-c**. As shown in FIGS. 36-38, the tilt motor **6120** of a lifter **6100** is configured to tilt an arm **6110** in a rotational tilt direction  $\theta$  about a tilt axis T approximately aligned with a longitudinal axis of the tilt motor **6210**, thus moving a gripper **6105** upward along a the vertical  $L_z$  (e.g., z-axis).

As shown in FIGS. 37-38, in implementations, each arm **3115** of the plurality of arms **3115a-c** can include an extend motor **3125c-c"** for pushing and pulling an associated arm **3115**, **3115a-c** forward and back in a linear direction along an axis E of each arm **3115** and thereby drive each gripper **3120** toward and away from its associated base **3118** of the plurality of bases **3118a-c**. For example, as shown in FIGS. 37-38, the extend motor **3125c** drives a friction wheel **3126** configured to engage a surface of the arm **3115**. The arm **3115** is seated in two or more rotatable support wheels **3127a-c** configured to hold the arm in steady alignment as the friction wheel **3126** retracts and extends the arm **6110**

therealong into and out of the work volume **3105**, **3105a-d**. In implementations, the rotatable support wheels **6127a-c** comprise v-groove ball bearings and one or more corners of an arm **3155** are disposed on and movably supported by the v-groove of each bearing. Additionally or alternatively, in implementations, the rotatable support wheels **3127a-c** comprise one or more crowned rollers having rounded edges to guarantee no wear on an engaged arm **3115**, **3115a-c**. In implementations, the rotatable support wheels **3127a-c** are configured to withstand maximum radial and axial loads during high-acceleration motions of a heavy article (e.g., an article comprising a weight in a range of between about 3 kg to 5 kg) supported by each arm **3115a-c**. Additionally or alternatively the arm **3115** further comprises a rack disposed thereon for engaging with a gear (not show) to prevent the arm **3115** from slipping during extend and retract motions in the direction of the bidirectional arrow representing axis E.

The one or more drive motors **3125a-c**, **a'-c'**, **a"-c"** associated with each arm **3115a-c** can operate simultaneously, in some sub-combination, or alternate operating to move the each gripper **3120a-c** to a location within the enclosed channel **3100** for engaging a deformable laundry article **12** disposed therein. Each gripper **3120a-c** is configured to releasably engage the deformable laundry article **12** and operate at least one of independently of and in tandem with another of the grippers **3120a-c** to at least one of raise and suspend the deformable laundry article above the floor **3110** of the enclosed channel **3100**.

In implementations, each arm **3115**, **3115a-c** can comprise a rod, such as an extruded beam, configured to extend from an associated base **3118**, **3118a-c**. In implementations, an arm **3115** can have no joints along its length, and a length from end to end that measures between about 0.25 m and 4 m (e.g. 0.25 m, 0.5 m, 1.0 m, 1.25 m, 1.5 m, 1.75 m, 2.0 m, 2.25 m, 2.5 m, 2.75 m, 3.0 m, 3.25 m, 3.5 m, 3.75 m, 4.0 m). In implementations, each arm **3115** of the plurality of arms **3115a-c** is an extendable arm comprising a fully extended length of between about 0.25 m and 4 m (e.g. 0.25 m, 0.5 m, 1.0 m, 1.25 m, 1.5 m, 1.75 m, 2.0 m, 2.25 m, 2.5 m, 2.75 m, 3.0 m, 3.25 m, 3.5 m, 3.75 m, 4.0 m). In examples, the extendable arm can include at least one of one or more flexible and/or compliant joints and two or more telescoping sections. In implementations, the at least one compliant joint comprises a compliant wrist disposed between the extendable rod of the arm **3115** and the terminal gripper **3120**. Additionally or alternatively, the wrist of an arm **3115** comprises one or more of a swivel joint and hinge joint for bending the wrist and aligning the terminal gripper to close on a grippable edge of a hoisted article **12** rather than trying to pinch a planar surface.

Joints and telescoping arms can be implemented to accommodate space constraints, but the additional moving sections can create pinch points for potential entangling the deformable laundry article **12**. Therefore, in implementations, each arm of the plurality of arms **3115a-c** comprises no joints. In implementations, the motions of each arm **3115**, **3115a-c** have a resolution of  $\pm 5$  mm in all three cardinal directions ( $L_{HX}$ ,  $L_{HY}$ ,  $L_z$ ). This precision enables alignment of an associated gripper **3120**, **3120a-c** before grabbing a grip point **15a-f** on a deformable laundry article **12**. In implementations, each arm **3115**, **3115a-c** moves the associated gripper **3120**, **3120a-c** within a spherical work volume having a radius defined by the arm **3115**, **3115a-c**. In implementations, the linear error introduced by degrees of pan and/or tilt at a full extension of the arm **3115**, **3115a-c** is  $\pm 5$  mm.



As previously described, in implementations, the two or more arms **3115**, **3115a-c** comprises three arms anchored along a length of the enclosed channel. In implementations, as shown in FIGS. 15A-17B, each arm **3115**, **3115a-c** has a range of motion that extends into an adjacent work volume **3105a-c**. In implementations, adjacent work volumes **3105a-d** overlap for at least 0.30 meter (e.g., about 1 ft) for the full vertical height of the work volume **3105a-d**, from the floor **3110** to a maximum suspension height (e.g., maximum hoist height) within the work volumes **3105a-c**. In implementations, each one of the plurality of arms **3115a-c** is configured to extend to any point on the floor within an associated work volume **3105a-c** and throughout the width, length, and height H of the work volume **3105a-c**, which is the volume of space extending between the floor **3110** and the ceiling **3111** that is accessible by the arm **3115a-c** at full extension, though a maximum pan range of movement and maximum tilt range of movement. In implementations, the pan motor **3125a-a"** comprises a power output in a range of between about 30-1800 W. In implementations, the tilt motor **3125b-b"** comprises a power output in a range of between about 120-3550 W motor. In implementations, the extend motor **3125c-c"** comprises a power output in a range of between about 60-1690 W motor. The bottom end of the ranges comprise power ratings for pan, tilt, and extend motors controlling an arm **3115** repositioning an article **12** having a weight between about 0.1-1.25 kg or an article having a weight in the range of about 3-5 kg traversing a work volume slowly (2-5 seconds). The top end of the ranges comprise requirements for moving an engaged article **12** having a weight of between about 3-5 kg traversing the work volume quickly (1-2 seconds), wherein traversing the work volume comprises moving through a full range of motion of any individual motor **3125a-c**, **a'-c'**, **a"-c"** (e.g., pan, tilt, extend). These ranges and values are intended to address the ranges and values of the plurality of varied laundry article types typically generated by a household. In any of the above implementations, traversing a work volume **3105a-c** is defined as any traversal including at least one of a full range of pan, full range of tilt, and full range of extend motions of the arm **3115a-c** and associated gripper **3120a-c**.

In addition to pan, tilt, and extend motions, in implementations, additionally or alternatively, the controller **3005** is further configured to drive the at least one drive of an arm **3115** of the plurality of arms **3115a-c** in at least one of alternating side-to-side and alternating up and down motions to shake one or more grasped deformable article **12** of the plurality of deformable articles at the hoist height. By shaking the terminal gripper **3120** at the hoist height, the arm **3115**, **3115a-c** can free any articles **12a-n** that may be stuck together, e.g., statically attracted, or entangled. This is possible because the terminal grippers **3120** are designed to securely grasp an article **12**.

As shown in the system schematic of FIG. 5, the device **3000** comprises three or more arms **3115a-c** in operable communication with at least one of their respective processors **3155a-c** and the at least one controller **3005**. In implementations, each one of the three or more arms **3115a-c** comprises a pan drive **3160**, tilt drive **3162**, and extend drive **3164** configured to drive motors **3125a-c**, **a'-c'**, **a"-c"** configured to pan, tilt, and extend an arm **3115**, **3115a-c** as described with regard to implementations. In implementations, the pan motors **3125a-a"**, tilt motors **3125b-b"**, and extend motors **3125c-c"** comprise controllable motors (e.g., a brushless DC motor (BLDC)). Each arm **3115**, **3115a-c** comprises a network interface **3166**, **3166a-c** configured to communicate data and sensor signals to at least one of the

respective processors **3155**, **3155a-c** and the at least one controller **3005** of the system **400** (via a wireless or wired communication network **230**) for processing. The sensor signals can be output from one or more optical sensors **3140**, **3145**, **3147**, one or more encoders **3157a-c**, **a'-c'**, **a"-c"**, and one or more position sensors **3168**, **3168a-c** and routed via a sensor interface **3170**, **3170a-c**.

Additionally, each arm **3115**, **3115a-c** comprises a gripper drive **3172a-c** and a gripper actuator **3174**, **3174a-c** in communication with at least one of the respective processors **3155**, **3155a-c** and the at least one controller **3005** of the system **400** (via a wireless or wired communication network **230**). Additionally, in implementations, each arm **3115**, **3115a-c** comprises one or more gripper sensors **3176**, **3176a-c** (e.g., a Hall sensor for detecting an angular position of a gripper wrist that flexes relative to the longitudinal arm axis B) and fingertip pressure sensors disposed in the fingers of the gripper for detecting contact forces with an article of clothing and/or the workspace floor **3110**.

As previously described, each arm **3115** of the plurality of arms **3115a-c** terminates at an associated gripper **3120**, **3120a-c**. In implementations, each gripper **3120**, including gripper fingers, can be manufactured from a lightweight, impact resistant material, such as aluminum or steel. In implementations, as shown in FIGS. 39A-41B, each gripper **3120** comprises at least two actuatable fingers **3707a-b**. In implementations, the at least two actuatable fingers comprise an overmold **3708a-b** comprising a durometer of between about 40 A to 80 A. For example, the overmold can comprise at least one of a polymer or copolymer including at least one of a rubber, a thermoplastic elastomer, (TPE), thermoplastic polyurethane (TPU), thermoplastic vulcanizates (TPV), and silicone. The overmold provides protection of the encapsulated fingers and any delicate fabrics of the deformable laundry article **12**. Additionally, having a soft fingertip enables finer grasping or grabbing of deformable laundry articles **12** off of a surface, such as the floor **3110** of the enclosed channel **3100**. In implementations, a gripping surface of each finger of a gripper **3120**, **3120a-c** comprises a textured surface, e.g., ribs, bumps, ridges, and/or other protuberance, for assisting with gripping the fabric of an article **12** with some degree of friction and/or perturbation. Additionally or alternatively, an outside surface (e.g., opposite the gripping surface) of each finger of a gripper **6105a-d** comprises a smooth surface for preventing the fabric of an article **12** from sticking to an outside surface of the gripper **3120**, **3120a-c**. In implementations, the gripper **3120**, **3120a-c** is washable and capable of withstanding heavy liquid spray and/or immersion and can have an IP rating of at least one of IP65, IP66, and IP56. In implementations, each gripper **3120** is about 300 mm long, about 100 mm high, and weighs about 500 grams.

In implementations, as shown in FIGS. 42A-B, the gripper **3120**, **3120a-c** comprises a glove **3104** or covering to prevent a deformable article from getting caught on at least one of a topography or interface of movable components of the gripper **3120**, **3120a-c** during the separating and sorting process. In implementations, the covering **3104** comprises a flexible, dirt repellant fabric. Additionally or alternatively, in implementations, the covering **3104** comprises a liquid-impermeable material configured for enabling washing of the covered gripper. In implementations, the covering **3104** can be at least one of polyester, rayon, thermoplastic polyurethane, nitrile, closed-cell foams, rubbers, silicone, and NEOPRENE. The glove, or covering **3104**, is flexible and/or stretchable such that the fingers **3707a-b** can move apart and together (FIG. 42B) without any disruptive resistive forces.



The at least two actuatable fingers **3707a-b** can rotate about parallel pivot points **3706a-b**. In implementations, the at least two actuatable fingers **3707a-b** are configured to be actuated by a drive assembly **3709** (e.g., FIGS. **41A-B**) to rotate simultaneously while gripping a deformable laundry article **12**. The drive assembly **3709** can be in operable communication with the controller **3005**. In implementations, the drive assembly **3709** can be cable driven or pneumatically driven. The drive **3709**, as shown in FIGS. **41A-B**, can be mounted to the arm **3115** and can be 100 mm long and weigh 500 grams. In implementations, the drive assembly **3709** comprises a cross section radius **3711** of less than 100 mm from the axis E of the arm **3115** in any direction.

In implementations, a gripper **3120** can comprise the following design factors shown in table 2:

TABLE 2

Grip strength	50 N
Finger strength-to-force ratio	2.0
Grip force	25 N
Contact distance	80 mm
Grip torque	2 N-m
Gripper transmission factor	22 mm
Cable tension	90 N (20 lbs)
Cable	2045 SN [220 lb breaking strength, 7 × 19 construction, 1.12 mm diameter]
Motor pulley radius	14 mm
Motor torque	1.26 N-m

In implementations, the following definitions apply to the design factors of table 2. Grip strength is the maximum force that can be applied to moving the deformable article **12**. It can also be thought of as the force required to pull a deformable laundry article **12** out of a gripper **3120**. The at least two actuatable fingers **3107a-b** make contact with the deformable laundry article **12** and directly impart the force that moves the deformable laundry article **12** (grip strength). This force is due to a combination of friction (when the force is generally parallel to the gripping surface) and normal tension (for instance, when the deformable laundry article **12** is wrapped over one of the two or more fingers **3707a-b**). In implementations, such as that depicted in FIGS. **40A-B**, the gripper **3120** comprises a sweet spot SS which comprises the volume between the two fingers **3107a-b** in which an article must be (e.g., the contact area CA) when the gripper actuates in order for the grasp to be successful.

Grip force is the force the two or more fingers **3707a-b** push against each other (when empty) or the deformable laundry article **12** (when engaged). The grip force is determined by the grip torque and the contact distance (distance between finger pivot **3706** and contact point with the deformable laundry article **12**). If the deformable laundry article **12** is engaged at a single point, the grip force equals the grip torque divided by the contact distance. In embodiments, calculations are based on the center of the contact area defining the contact point. Strength-to-force ratio is the ratio between grip strength and grip force. In implementations, grip strength and grip force are directly proportional so that the ratio is fixed for a given combination of finger **3707**, deformable laundry article **12** type and shape. In other implementations, grip strength and grip force have a sigmoidal relationship. For example, this applies to grippers **3120** that create a normal force or otherwise 'lock' the deformable laundry article **12** into place between the fingers **3707a-b**. Grip torque is the torque on the joints of the fingers **3707a-b**. This is dependent on the cable tension and gripper geometry and can be increased by increasing the lever arm

in the gripper **3120**, but this increases the gripper size. Cable tension is dependent on the motor torque and lever arm at the motor. This sets the minimum diameter of the cable. Cable tension can be increased by decreasing the motor lever arm, but in implementations using a pulley wheel, a minimum diameter is required to ensure the cable does not break. Motor torque is minimized to reduce cost and weight of the motor.

FIGS. **39A-B** show exemplary grippers comprising linkages and pulleys for moving the fingers **3707a-b** by turning translational cable displacement into angular motion. In one implementation employing a pulley (FIG. **39B**), two cables **3713** are threaded through the finger joints **3716**. In another implementation employing linkages (FIG. **39A**), a single cable is looped around a pin. The linkage system is configured to amplify torque as the fingers **3707a-b** close.

In other implementations, the grippers **3120**, **3120a-b** can comprise pneumatic actuators. A cable, or pneumatic tube, is snaked through the arm **3115**. The gripper mechanism is driven by a linear motion, which is translated into finger rotation by linkages or pulleys. In implementations, the fingers **3107a-b** are joined by linkages to one another and an actuatable cylinder. The pneumatic gripper **3120** is lightweight, quickly actuated, and built to withstand cycles on order of magnitude in the millions or higher. In implementations, at least one pneumatic tube runs through a hollow conduit extending the length of the arm **3115**. In implementations, two pneumatic tubes run through the hollow conduit, each one of the pneumatic tubes configured to be in fluid connection with one of two sides of a pneumatic actuator. In implementations, the controller **3005** actuates the gripper **3120** to close (e.g., clamp shut) the fingers **3107a-b** by pressurizing one side of a pneumatic actuator. In implementations, the controller **3005** actuates the gripper **3120** to open (e.g., spread apart) the fingers **3107a-b** by pressurizing the other side of the pneumatic actuator. Additionally or alternatively, in implementations, the fingers can be held open by a cylinder and return spring assembly, which can be weak enough to allow any tangled deformable laundry article **12** to slip off the fingers. Pneumatic actuators have the advantage of being easy to seal against ingress of dirt and germs. Pneumatics actuators have the advantage of being easy to seal against ingress of dirt and germs. In implementations comprising a pneumatic cylinder at 100 psi, a gripper **3120** can comprise the following design factors shown in table 3:

TABLE 3

Grip strength	50 N
Finger strength-to-force ratio	2.0
Grip force	25 N
Contact distance	80 mm
Grip torque	2 N-m
Gripper transmission factor	22 mm
Piston force	90 N (20 lbs)
Piston bore size (assuming 100 psi)	7/16"

Turning to FIGS. **43A** through **44** In implementations, the gripper **3120** further comprises a wrist **3750** comprising a plurality of sensors **3755a-d**, **3765** configured to sense an application of force on the gripper **3120** as applied various directions including at least one of up and down, sided to side, and axially. The plurality of sensors **3755a-d**, **3765** are configured to output a signal to the controller **3005**. The wrist **3750** is disposed between the fingers **3707a-b** and the arm **3115**. In implementations, the wrist **3750** comprises a plurality of compression springs **3760a-d** configured to flex and compress under an application of force and a rod **3767**

61

configured to trip one or more limit switch sensors **3755a-d**, **3760** under an application of a threshold force. For example, as shown in the magnified view M1 of FIG. 44, the rod **3767** can compress and trip one of the one or more limit switch sensors **3755a-d**, **3765** under an application of force in a range of between about 4 to 5 pounds of force. Although the sensors are described as limit switches, in implementations, the plurality of sensors **3755a-d**, **3765** can be one or more analog sensors configured to detect how much the terminal gripper has moved. In implementations, the sensor **3765** behind the rod **3767** is configured to detect if the gripper **3120** has hit the floor **3110** of the enclosed channel head on, thereby applying an axial force.

In implementations, the controller **3005** receives one or more signals from the plurality of sensors **3755a-d**, **3765** and determines the application of a side-to-side force indicative of a deformable article being snagged on a first arm or terminal gripper while the terminal gripper of a subsequent arm of the plurality of arms grasps the article. In implementations, the controller **3005** receives one or more signals from the plurality of sensors **3755a-d**, **3765** and determines the application of a threshold amount of axial force applied as the terminal gripper **3120** pushes against the floor **3110** of the channel **3100** to sweep up and grasp an article resting on the floor. For example, an article such as a thin silk scarf, may be smooth and comprises a low profile. The terminal gripper **3120** can comprise flexible fingers **3707a-b** and be configured to accommodate being driven into the floor with a threshold amount of force (e.g., 11 bf, 21 bf, 31 bf, e.g., 4.4 N, 8.9 N, 13.3 N) while enabling the flexible fingers **3707a-b** to be actuated in a grasping motion. In implementations, the controller **3005** receives one or more signals from the plurality of sensors **3755a-d**, **3765** and determines the application of a threshold amount of axial force applied as the terminal gripper **3120** pushes against a pile of deformable articles to ensure the terminal gripper **3120** is positioned with the pile of deformable articles for successfully grasping at least one article.

Additionally or alternatively, as shown in FIG. 5, one or more sensors can include sensors **3176**, **3176a-c** disposed on or in one or more portions of the grippers **3120**, **3120a-c**. In implementations, the one or more sensors **3176**, **3176a-c** can include a finger torque and position sensor disposed on the gripper **3120** to sense when the fingers **3707a-b** have closed. This allows the robot **300** to operate quickly because the closed sensor can signal moving onto the next step. Additionally or alternatively, a force/torque sensor can be disposed on a wrist of a gripper **3120** to determine if the gripper has collided with anything, is pulling too hard on a deformable laundry article **12**, or is tangled in the deformable laundry article **12**. This sensor assists with pinching the fingers **3707a-b** to grasp clothes off of a surface (e.g., the conveyor) by determining when contact is made with the surface. Additionally, a force/torque sensor can output a signal to the processor **3155** for estimating a weight of a deformable laundry article **12**. Additionally or alternatively, one or more force/torque sensors can be disposed at a tilt axis driven by the arm tilt motor **3125b-b"**. In implementations, a torque sensor can be disposed on or in a motor for the gripper **3120**. Additionally or alternatively, in implementations, strain gauges can be disposed in the bases of the fingers **3707a-b** (not fingertips). Additionally or alternatively, in implementations, a tension sensor can be disposed in-line with a cable for rotating and closing the fingers **3707a-b**. In all implementations, a torque sensor could provide an output signal for determining whether or not the fingers **3707a-b** of each gripper **3120** are engaged with a

62

deformable laundry article **12**. In other implementations, engagement can be detected by force/pressure sensors (not shown) disposed on the fingertips of the two or more fingers **3707a-b**. The force/pressure sensor(s) can be one of the gripper sensor(s) **3176**, **3176a-c** configured to communicate a sensor signal to the controller **3005**, as shown in FIG. 5.

Referring now to FIG. 45, any of the examples and implementations described previously with regard to an autonomous separating and sorting device **3000** are applicable to implementations described herein with regard to a method **3900** of robotically separating and sorting a deformable article **12** (e.g., also referred to herein as a "deformable laundry article") from an amassed plurality of deformable articles **12a-n**. Any of the methods described hereinafter applicable in combination with any and all of the processes, devices, and systems described previously with regard to implementations.

In implementations, a method **3900** of autonomously (e.g., robotically) sorting a plurality of deformable laundry articles **12a-n** into loads for washing, comprises receiving **53905**, at a controller, a signal from at least one sensor disposed at least one of on, adjacent to, and within at least one of a plurality of sequential work volumes within an enclosed channel, the signal being indicative of at least one of the plurality of deformable laundry articles being disposed within at least one of the plurality of sequential work volumes. In implementations, the at least one sensor is disposed in a first bay or work volume of a continuous, enclosed channel comprising a plurality of sequential work volumes. The method comprises determining **53910**, based on the received signal, a location of the at least one of the plurality of deformable articles on a stationary floor of the associated one of the plurality of sequential work volumes.

At the start of the separating and sorting process, all of the at least one of the plurality of deformable articles are disposed in a first work volume of the enclosed channel. As described previously with regard to implementations, the plurality of sequential work volumes **3105a-d** are constituent to an enclosed channel **3100** and the stationary floor **3110** of the enclosed channel **3100** extends between an inlet end I and an outlet end O of the enclosed channel. A portion of the stationary floor **3110** adjacent the inlet end I is configured to receive thereon the plurality of deformable laundry articles **12a-n** when introduced into the channel **3100**. If the controller **3005** determines, based on the received signal, that a laundry article is not detected, in implementations, the method comprises receiving **S3912** a second signal from another of the at least one sensor. For example, in implementations, the first signal can be at least one of a 2D and 3D image and the second signal can be another at least one of a 2D and 3D image. In implementations, the first and/or second signal can be, for example as shown in FIG. 46, a 2D mask **3800** derived from an image of the floor **3110** of enclosed channel. The 2D mask comprises an outline of the peripheral edge of an article **12** disposed on the floor **3110**. In implementations the first signal can include an IR grayscale image or RGB image of the floor **3110** and the second signal can include an IR grayscale image or RGB image of the article disposed on the floor. The controller can take an absolute difference in luminance value of the background image of the floor and the luminance value of the article to find an edge between the article and floor thereby creating a mask, or outline, of the article. Additionally or alternatively, in implementations, the controller **3005** receives the input signal of one or more sensors (e.g., one or more sensors **3140a-c**, **3145a-c**, **3147a-c**), takes an absolute difference between the bits of background and running images, uses a

threshold to make that difference image black and white, and then applies at least one of eroding and blurring to generate the final mask. This reduces potential errors caused by lighting differences.

The method comprises determining **53913** wherein at least one article **12** is detected in each of the work volumes. If no article is detected, the method concludes by sending a collection bin containing one or more separated and sorted deformable laundry articles **12** to one or more washing and drying robots **4000**. If an article is detected in a work volume, the method comprises identifying **S3915** a grip point on the article and instructing **S3920** at least one drive of at least one of a plurality of arms **3115a-c** disposed in series along the enclosed channel **3100** to at least one of rotate, tilt, extend, and retract a terminal gripper **3120** configured to selectively grasp at least one of the plurality of deformable laundry articles at the determined grip point. As described herein with regard to implementations, each one of the plurality of arms is associated with one of the plurality of sequential work volumes. The controller instructs an actuator of the terminal gripper to close on the at least one of the plurality of deformable laundry articles. The method comprises instructing the at least one drive to raise **S3925** the closed terminal gripper and the grasped at least one of the plurality of deformable laundry articles to a hoist height above the stationary floor **3110**, and move **S3940** the gripper **3120** (e.g., at least one of pan, tilt, and extend, e.g., rotate) toward the outlet end **O** into an adjacent work volume **3105b-d**. In implementations, the method comprises determining **53930** whether the gripper missed grasping the grip point and repeats the instructions of identifying **S3915** a grip point, instructing the arm to pan, tilt, extend and/or retract the gripper to the grip point, instruct the gripper to grasp the grip point, and instruct the arm **S3925** to raise the gripper and grasped article to a hoist height.

As described previously with regard to implementations, the method can comprise the controller **3005** executing a subroutine for a miss recovery if the controller **3005** determines the gripper has not grasped the article **12**. In implementations, the miss recovery routine comprises moving the target grip point **15** inward from an detected edge of the one or more articles **12a-n** by a distance in a range of between about 5-10 mm with each subsequent attempt after a missed grab (e.g., grasp by the gripper). Additionally or alternatively, in implementations, the controller **3005** can determine a center of mass of the mask of the at least one article **12** on the floor **3110** of the work volume and move the targeted grip point **15** from the outer most edge of the at least one article **12** toward the center of mass with each subsequent attempt after a missed grab.

In implementations, method comprises the controller **3005** selecting the alternate grip point locations randomly, or by iterating attempted grasps at alternate grip point locations in a deterministic manner. This ensures that the gripper **3120** will find a graspable portion of the article **12**, accounting for any spacing between extensions and the core of a garment, such as between sleeves and the torso portions of a shirt, which may place a center of mass in an open location not occupied by the article **12**. Additionally or alternatively, in implementations, the controller **3005** is configured to create a bounding box **3805** around the mask **3800** of the article **12** as shown in FIG. **46**, the bounding box comprising a length **LB** and a width **WB** that places the mask **3800** inside the bounding box **3805**. The controller **3005** is configured to choose a random point as the target grip point **15** based on the length **LB** and width **WB** of the bounding box, determine whether the grip point **15** is within the mask (e.g., grip point

**15b**) and not just within in the bounding box (e.g., **15a**), and instruct a gripper **3120** to grasp the grip point **15b** within the mask area corresponding to the location of the article **12**. If the grip point was not within the mask **3800**, the controller **3005** randomly selects a new target grip point with the bounding box **3805** and iteratively continues randomly selecting target grip points until a target point is within both the bounding box **3805** and the mask **3800**. The randomness of determining a grip point **15** within the bounding box **3805** accounts for the difference in size between an end effector in software path planning (e.g., a single point) and the volume of the gripper **3120**, which is a 3D element and not a single point, and results in successful grabs of the article **12** regardless of article size. This enables a gripper **3120** to grab very small items such as baby socks, for example. By comparison, targeting a center of mass could result in the joint at the base of the fingers of the gripper **3120** touching the floor **3110** of the channel **3100** and not reaching the article, even though the center of the gripper **3120** was directly above the given target point, such as an edge point of the small article or a point moved inward from an edge point toward a center of mass.

Additionally or alternatively, prior to instructing the at least one drive to move or rotate **S3940** the arm toward the outlet end into an adjacent work volume, the method comprises determining **3935** whether the arm holding the article at the hoist height is adjacent a collection bin at an outlet end of the enclosed channel. If the arm is not adjacent the collection bin, the method comprises instructing **S3945** the actuator of the terminal gripper to open the gripper to release the at least one of the plurality of deformable laundry articles in the adjacent work volume (e.g., the receiving work volume). The method comprises receiving **S3950** a signal from at least one sensor in the receiving work volume of the plurality of sequential work volumes, and determining **S3955**, based on the received signal, a state comprising at least one of one or more of the plurality of deformable laundry articles are present on the stationary floor, and one or more of the plurality of deformable laundry articles are not present on the stationary floor.

If the controller determines, based on the received signal, that the laundry article is not detected, in implementations, the method comprises receiving **S3960** a second signal from another of the at least one sensor. For example, in implementations, the first signal can be at least one of a 2D and 3D image and the second signal can be another at least one of a 2D and 3D image. In implementations, the second signal can be, for example as shown in FIG. **46**, a 2D mask **3800** derived from an image of the floor **3110** of enclosed channel. The 2D mask comprises an outline of the peripheral edge of an article disposed on the floor **3110**. In implementations the first signal can include an IR greyscale image or RGB image of the floor **3110** and the second signal can include an IR greyscale image or RGB image of the article disposed on the floor. The controller can take an absolute difference in luminance value of the background image of the floor and the luminance value of the article to find an edge between the article and floor thereby creating a mask, or outline, of the article. Additionally or alternatively, in implementations, the controller **3005** receives the input signal of one or more sensors (e.g., one or more sensors **3140a-c**, **3145a-c**, **3147a-c**), takes an absolute difference between the bits of background and running images, uses a threshold to make that difference image black and white, and then applies at least one of eroding and blurring to generate the final mask. This reduces potential errors caused by lighting differences.

65

The method comprises determining S3962 whether the second signal indicates an article being detected in the receiving work volume. If any article is not detected, the method returns to determining S39390 whether the previous gripper missed the grab or potentially dropped the article prior to entering the receiving (adjacent) work volume. If the article is on the floor of the prior work volume, the method returns to identifying S3915 a grip point, instructing S3920 the gripper to travel to the grip point, and instructing S3925 the previous arm to hoisting the article.

If the article is determined S2962 to be in the receiving work volume, either detected from the signal of a first of the at least one sensor or a second signal of the at least one sensor, the method comprises identifying S3965 a grip point of the laundry article and instructing S3970 a gripper of the arm associated with the receiving work volume (e.g., the "adjacent work volume") to travel to and grasp the grip point. The method comprising instructing S3975 the arm to raise the article engaged in the gripper to a suspension height and confirm S3980 whether the laundry article is raised. If the article is not detected in the gripper at the hoist height, the method comprises repeating the steps of identifying S3965 a grip point of the laundry article, instructing S3970 a gripper of the arm associated with the receiving work volume to travel to and grasp the grip point, and instructing S3975 the arm to raise the article engaged in the gripper.

The method comprises determining S3980 whether the gripper missed grabbing the grip point. If the gripper missed, the method comprises executing a miss recovery subroutine as previously described. If the gripper did not miss, the method comprises determining S3935 whether the arm holding the article at the hoist height is adjacent a collection bin at an outlet end of the enclosed channel. If the arm is not adjacent the collection bin, the method iteratively repeats S3940-S3980 until the arm holding the article is the arm closes to the outlet orifice and collection bin. The method comprises determining S3985 at least one characteristic of the laundry article 12 and instructing S3990 alignment of a collection bin (e.g., sorting bin) associated with the at least one characteristic within reach of the arm and engage gripper. As described previously with regard to implementations, the collection bin can be one of a plurality of bins disposed on a carousel or load constructor in operable communication with the controller for shuffling bins beneath the channel for receiving separated articles into one or more bins containing articles of matching one or more washing and drying characteristics. The method comprises instructing S3992 the arm to rotate and the gripper to release the article into the collection bin associated with the at least one characteristic. The robot 3000 thus intelligently batches one or more articles into loads for washing and drying with appropriate collective washing and drying cycle parameters (e.g., water temperature, air temperature, cycle durations, agitation speed, etc.).

In implementations, the method comprises receiving a signal indicative of at least one of a weight and an occupied volume of the collection bin receiving the laundry article. The method comprises determining whether the at least one of weight and volume are above a threshold value. If at least one of the weight and volume exceeds a threshold, the method comprises sending S3998 the collection bin to a washing and drying robot 4000 for laundering.

In implementations, the method comprises stopping iterating the grasps, rotations, and releases when each one of the plurality of deformable laundry articles exits the enclosed channel through the outlet orifice as a solitary deformable article. In implementations, the method comprises instruct-

66

ing two or more of the plurality of arms to operate simultaneously within each associated one of the plurality of sequential work volumes. In implementations, the method comprises instructing terminal grippers of two or more of the plurality of arms operating simultaneously to simultaneously grasp at least one of the plurality of deformable articles. In implementations, the method comprises instructing the at least one drive of the arm with an engaged terminal gripper to move the terminal gripper in at least one of alternating side-to-side and alternating up and down motions to shake a grasped deformable article at the hoist height. In implementations, the method comprises receiving a contact sensor signal from at least one contact sensor on a gripping surface of the terminal gripper indicative of none of the plurality of deformable laundry articles being grasped in the terminal gripper at the hoist height. In implementations, the rather than an engaged gripper releasing each article 12 on the floor 3110 of an adjacent work volume 3105 following a hoist, the gripper 3120 of an available arm 3115 in a receiving work volume 3105 can grip an edge of the article 12 (e.g., a lowest hanging point), hoist the gripped edge to the hoist height and the longest engaged gripper can release the article 12.

As depicted in FIG. 47, the separating and sorting device 3000 is a state machine that operates based on a current state of the enclosed channel. Between runs of processing loads of one or more deformable articles, the enclosed channel 3100 and the plurality of arms 3115a-c therein are in a dormant state 3855, the channel 3100 being devoid of any articles. Once a load of dirty one or more articles 12a-n enter the channel 3100, the arms 3115a-c are in a stowed position 3860 at rest. The device 3000 captures images 3865, evaluates 3870 the environment of the channel 3100 and based on a state of the one or more articles 12a-n within the channel 3100, moves the arms 3875 to action as described previously with regard to implementations. The device 3000 iteratively cycles through the states of capturing images 3865, evaluating 3870 the environment, and moving the arms 3115a-c until all of the one or more articles 12a-n are sorted out of the channel 3100. The arms 3115a-c then resume their stowed state 3860 and the device 3000 again is in a dormant state 3855 awaiting at least one of cleaning and receiving a next load of one or more deformable articles 12a'-n'.

All of the methods and tasks described herein may be performed and fully automated by a computer system. The computer system may, in some cases, include multiple distinct computers or computing devices (e.g., physical servers, workstations, storage arrays, etc.) that communicate and interoperate over a network to perform the described functions. Each such computing device typically includes a processor (or multiple processors or circuitry or collection of circuits, e.g. a module) that executes program instructions or modules stored in a memory or other non-transitory computer-readable storage medium. The various functions disclosed herein may be embodied in such program instructions, although some or all of the disclosed functions may alternatively be implemented in application-specific circuitry (e.g., ASICs or FPGAs) of the computer system. Where the computer system includes multiple computing devices, these devices may, but need not, be co-located. The results of the disclosed methods and tasks may be persistently stored by transforming physical storage devices, such as solid state memory chips and/or magnetic disks, into a different state.

Although the subject matter contained herein has been described in detail for the purpose of illustration, it is to be understood that such detail is solely for that purpose and that

67

the present disclosure is not limited to the disclosed embodiments, but, on the contrary, is intended to cover modifications and equivalent arrangements that are within the spirit and scope of the appended claims. For example, it is to be understood that the present disclosure contemplates that, to the extent possible, one or more features of any embodiment can be combined with one or more features of any other embodiment.

Other examples are within the scope and spirit of the description and claims. Additionally, certain functions described above can be implemented using software, hardware, firmware, hardwiring, or combinations of any of these. Features implementing functions can also be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations.

What is claimed is:

1. An autonomous sorting device for sorting a plurality of deformable articles, comprising:

an enclosed channel comprising a plurality of sequential work volumes and a stationary floor extending between an inlet end and an outlet end of the channel, a portion of the stationary floor within a first work volume of the plurality of sequential work volumes being configured to receive thereon the plurality of deformable articles adjacent the inlet end;

a plurality of arms disposed in series along the enclosed channel, each one of the plurality of arms comprising an actuatable terminal gripper configured to selectively grasp at least one of the plurality of deformable articles and at least one drive configured to at least one of rotate, tilt, extend, and retract the terminal gripper, each of the plurality of arms being associated with one of the plurality of sequential work volumes;

an inlet orifice disposed in at least one of a ceiling and a wall of the enclosed channel, the plurality of deformable articles being received into the enclosed channel through the inlet orifice;

an outlet orifice disposed adjacent the outlet end in at least one of a wall of the enclosed channel and the stationary floor, each one of the plurality of deformable articles exiting the enclosed channel through the outlet orifice;

at least one sensor disposed at least one of on, adjacent to, and within one or more of the plurality of sequential work volumes, the at least one sensor configured to detect at least one of the plurality of deformable articles disposed within at least one of the plurality of sequential work volumes, and

output a signal indicative of at least one of a presence and a location of the at least one of the plurality of deformable articles relative to the terminal gripper of one of the plurality of arms associated with the at least one of the plurality of sequential work volumes within which that at least one of the plurality of deformable articles is detected; and

a controller in operable communication with the at least one drive and the at least one sensor, the controller configured to

receive a signal from the at least one sensor indicative of detecting at least one of the plurality of deformable articles being disposed within at least one of the plurality of sequential work volumes,

determine a location of the at least one of the plurality of deformable articles on the stationary floor,

instruct the at least one drive to position a terminal gripper to grasp the at least one of the plurality of deformable articles, the terminal gripper being dis-

68

posed on one of the plurality of arms associated with the at least one of the plurality of sequential work volumes within which the at least one of the plurality of deformable articles is detected,

instruct the terminal gripper to close on the at least one of the plurality of deformable articles,

instruct the at least one drive to

raise the closed terminal gripper of the associated arm and the at least one of the plurality of deformable articles to a hoist height above the stationary floor, and

rotate toward the outlet end into an adjacent work volume,

instruct the actuator of the terminal gripper to open the gripper to release the at least one of the plurality of deformable articles in the adjacent work volume,

receive a signal from the at least one sensor configured to detect the released at least one of the plurality of deformable articles within the adjacent work volumes, and

determine, based on the received signal, a state comprising at least one of

one or more of the plurality of deformable articles are present on the stationary floor,

none of the plurality of deformable articles are present on the stationary floor, and

one of the plurality of deformable laundry articles exited the enclosed channel through the outlet orifice.

2. The device of claim 1, wherein the plurality of sequential work volumes comprises three or more work volumes, and wherein the plurality of arms comprises three or more arms, each of the three or more arms being associated with one of the three or more work volumes.

3. The device of claim 2, wherein an outlet-facing end of each of the three or more work volumes overlaps with an inlet-facing end of an adjacent sequential one of the three or more work volumes such that each arm of the plurality of arms is configured to extend into one or more adjacent work volumes of the plurality of sequential work volumes.

4. The device of claim 2, wherein the controller is further configured to, based on determining one or more of the plurality of deformable articles are present on the stationary floor in the adjacent work volume, iteratively

determine a location of the at least one of the plurality of deformable articles on the stationary floor relative to an arm associated with the adjacent work volume,

instruct the at least one drive of the arm associated with the adjacent work volume to position the terminal gripper of the arm associated with the adjacent work volume at the determined location to grasp the at least one of the plurality of deformable articles,

instruct the terminal gripper of the arm associated with the adjacent work volume to close on the at least one of the plurality of deformable articles,

instruct the at least one drive to

raise the closed terminal gripper of the arm associated with the adjacent work volume and the grasped at least one of the plurality of deformable articles to a hoist height above the stationary floor, and

rotate toward the outlet end into a next sequential adjacent work volume of the three or more work volumes,

instruct the terminal gripper to open the gripper to release the at least one of the plurality of deformable articles in the next sequential adjacent work volume,

receive a signal from at least one sensor configured to detect the at least one of the plurality of deformable articles, and

determine, based on the received signal, a state comprising at least one of

one or more of the plurality of deformable articles are present on the stationary floor,

none of the plurality of deformable articles are present on the stationary floor, and

one of the plurality of deformable articles exited the enclosed channel through the outlet orifice.

5. The device of claim 1, wherein the controller is further configured to instruct two or more of the plurality of arms to operate simultaneously within each associated one of the plurality of sequential work volumes, wherein terminal grippers of the two or more of the plurality of arms operating simultaneously are configured to each simultaneously grasp at least one of the plurality of deformable articles.

6. The device of claim 1, wherein the enclosed channel is fully enclosed on all sides and at the inlet and outlet ends, and wherein the inlet orifice and outlet orifice each further comprise an actuated covering for selectively exposing and sealing each of the orifices, the controller being in operative communication with the actuation of each covering.

7. The device of claim 1, wherein one or more bins are configured to be disposed beneath the exit orifice, each of the one or more bins being configured to receive one or more of the plurality of deformable articles having one or more characteristics associated with at least one of the one or more bins.

8. The device of claim 7, wherein the one or more characteristics comprise at least one of a common color, size, material composition, article type, degree of dirtiness, and fabric heat tolerance of the one or more deformable articles received therein.

9. The device of claim 8, further comprising an actuated carousel in operable communication with the controller, the actuated carousel being configured to receive thereon the one or more bins and rotate the one or more bins beneath the enclosed channel to match a characteristic of one of the one or more bins positioned beneath the outlet orifice with the one or more characteristics of each one of the plurality of deformable articles exiting the enclosed channel.

10. The device of claim 9, further comprising a memory in communication with the controller, the memory configured to store at least one relation comprising one of the one or more characteristics associated with the bin, a bin identification marker for each of the one or more bins, and a customer identity shared by the plurality of deformable articles received into the enclosed channel.

11. The device of claim 1, wherein the at least one sensor is configured to detect the one or more characteristics of each one of the plurality of deformable articles and output a signal to the controller comprising the detected one or more characteristics.

12. The device of claim 11, wherein the at least one sensor comprises at least one of a 3-D camera, an IR sensor, a 2-D camera, LIDAR, LADAR, a sonar proximity sensor, an ultrasonic ranging sensor, a radar sensor, a pair of stereo depth cameras, a colorimeter and a spectrometer.

13. The device of claim 12, wherein the controller is further configured to determine, based on a comparison of a received output signal of the at least one sensor to data stored in a memory in communication with the controller, at least one of an article type, an article color, an article size, a degree of dirtiness, and an article fabric.

14. The device of claim 13, wherein the memory further comprises a neural network, and wherein determining the one or more characteristics of each one of the plurality of deformable articles comprises processing the received output signal of the at least one sensor with a neural network classifier.

15. The device of claim 1, further comprising a retractable cleaner configured to advance through the enclosed channel from the inlet end to the outlet end while cleaning one or more interior surfaces, the retractable cleaner comprising an actuatable cleaning drive in operable communication with the controller, wherein, upon determining that none of the plurality of articles remain on the stationary floor in any of the sequential work volumes, the controller is configured to instruct the retractable cleaner to advance from the inlet end to the outlet end of the enclosed channel.

16. The device of claim 15, further comprising a plurality of spray ports disposed along a continuous outer surface of the retractable cleaner facing the one or more interior surfaces of the enclosed channel, and wherein a cleaning fluid comprises at least one of steam, water, detergent, germicide, and pesticide.

17. The device of claim 1, wherein the plurality of deformable articles comprises one or more loads of dirty household laundry, and wherein the plurality of deformable articles comprises two or more article types of at least one of different sizes, different shapes, different colors, and different fabrics.

18. The device of claim 1, wherein the plurality of arms each further comprise a rod configured to extend from an anchor at corresponding individually anchored positions, the rod comprising a fully extended length of between about 0.25 m and 4 m, wherein the anchor comprises the at least one drive, and wherein the at least one drive comprises a pan drive, a tilt drive, and an extend drive.

19. The device of claim 18, wherein the controller is further configured to drive the at least one drive in at least one of alternating side-to-side and alternating up and down motions to shake a grasped deformable article of the plurality of deformable articles at the hoist height.

20. The device of claim 19, wherein the terminal gripper of each of the plurality of arms comprises at least two actuatable fingers and wherein the terminal gripper of each of the plurality of arms is at least one of cable driven and pneumatically driven.

21. The device of claim 19, wherein each anchor is disposed on a base outside the enclosed channel and the associated one of the plurality of arms disposed on the base extends through one of a plurality of openings in a sidewall of the enclosed channel, each of the plurality of openings configured to receive a rod of each one of the plurality of arms therethrough, and a seal disposed about each of the plurality of openings through which the rod of each one of the plurality of arms extends, the seal comprising a flexible material configured to stretch as the rod extends, pans, tilts, and retracts.

22. The device of claim 1, wherein the at least one sensor comprises at least one of a 3-D camera, an IR sensor, a 2-D camera, LIDAR, LADAR, a sonar proximity sensor, an ultrasonic ranging sensor, a radar sensor, and a pair of stereo depth cameras.

23. The device of claim 22, wherein determining a location of the at least one of the plurality of deformable articles on the stationary floor further comprises determining one or more grip points on the at least one of the plurality of deformable articles, wherein the one or more grip points are at least one of disposed on a high point of the at least one of

71

the plurality of deformable articles, disposed on an edge of the at least one of the plurality of deformable articles, and disposed within an area of a mask of the at least one of the plurality of deformable articles.

24. A method of robotically sorting a plurality of deformable laundry articles into loads for washing, comprising:

receiving, at a controller, a signal from at least one sensor disposed at least one of on, adjacent to, and within one or more of a plurality of sequential work volumes, the signal being indicative of at least one of the plurality of deformable laundry articles being disposed within at least one of the plurality of sequential work volumes; determining, based on the received signal, a location of the at least one of the plurality of deformable articles on a stationary floor within at least one of the plurality of sequential work volumes, the plurality of sequential work volumes being constituent to an enclosed channel and the stationary floor extending between an inlet end and an outlet end of the enclosed channel, a portion of the stationary floor adjacent the inlet end being configured to receive thereon the plurality of deformable laundry articles;

instructing at least one drive of at least one of a plurality of arms disposed in series along the enclosed channel to at least one of rotate, tilt, extend, and retract a terminal gripper configured to selectively grasp at least one of the plurality of deformable laundry articles at the determined location, each one of the plurality of arms being associated with one of the plurality of sequential work volumes;

instructing, by the controller, an actuator of the terminal gripper to close on the at least one of the plurality of deformable laundry articles;

instructing the at least one drive to

raise the closed terminal gripper and the grasped at least one of the plurality of deformable laundry articles to a hoist height above the stationary floor, and

rotate toward the outlet end into an adjacent work volume;

instructing the actuator of the terminal gripper to open the gripper to release the at least one of the plurality of deformable laundry articles in the adjacent work volume;

receiving a signal from at least one sensor in the adjacent work volume of the plurality of sequential work volumes; and

determining, based on the received signal, a state comprising at least one of

one or more of the plurality of deformable laundry articles are present on the stationary floor,

one or more of the plurality of deformable laundry articles are not present on the stationary floor, and

one the plurality of deformable laundry articles exited the enclosed channel through an outlet orifice disposed in the stationary floor adjacent the outlet end.

72

25. The method of claim 24, wherein the at least one sensor comprises at least one of a 3-D camera, an IR sensor, a 2-D camera, LIDAR, LADAR, a sonar proximity sensor, an ultrasonic ranging sensor, a radar sensor, and a pair of stereo depth cameras.

26. The method of claim 25, wherein determining a location of the at least one of the plurality of deformable articles on the stationary floor further comprises determining one or more grip points on the at least one of the plurality of deformable articles, and wherein the one or more grip points are at least one of disposed on a high point of the at least one of the plurality of deformable articles, disposed on an edge of the at least one of the plurality of deformable articles, and disposed within a mask of the at least one article.

27. The method of claim 24, wherein determining a location of the at least one of the plurality of deformable laundry articles on the stationary floor relative to the associated arm comprises the controller executing a series of instructions to perform a background subtraction routine on an input signal comprising a 2D image to locate at least one of the plurality of deformable laundry articles disposed on the stationary floor.

28. The method of claim 27, wherein the background subtraction routine comprises outputting a location of a perimeter of the at least one of the plurality of deformable laundry articles on the stationary floor relative to the at least one sensor and a current position of the terminal gripper.

29. The method of claim 24, wherein one or more bins are configured to be disposed beneath the stationary floor, each of the one or more bins being configured to receive one or more of the plurality of deformable laundry articles having one or more characteristics associated with at least one of the one or more bins, wherein the one or more characteristics comprise at least one of color, size, article type, degree of dirtiness and fabric heat tolerance.

30. The method of claim 29, further comprising actuating a carousel in operable communication with the controller, the carousel being configured to receive thereon the one or more bins.

31. The method of claim 30, wherein actuating the carousel comprises repositioning the one or more bins beneath the enclosed channel to match a characteristic of one of the one or more bins positioned beneath the outlet orifice with the one or more characteristics of each one of the plurality of deformable laundry articles exiting the enclosed channel.

32. The method of claim 31, further comprising storing on a memory in communication with the controller, at least one relation comprising one of the one or more characteristics associated with the bin, a bin identification marker for each of the one or more bins, and a customer identity shared by the plurality of deformable laundry articles received into the enclosed channel.

\* \* \* \* \*